



Borehole **22-04-11**

Log Event A

Borehole Information

Farm : <u>BY</u>	Tank : <u>BY-104</u>	Site Number : <u>299-E33-249</u>
N-Coord : <u>45,940</u>	W-Coord : <u>53,365</u>	TOC Elevation : <u>650.00</u>
Water Level, ft :	Date Drilled : <u>6/1/1974</u>	

Casing Record

Type : <u>Steel-welded</u>	Thickness : <u>0.280</u>	ID, in. : <u>6</u>
Top Depth, ft. : <u>0</u>	Bottom Depth, ft. : <u>100</u>	

Borehole Notes:

According to the driller's records, this borehole was not perforated or grouted.

Equipment Information

Logging System : <u>2</u>	Detector Type : <u>HPGe</u>	Detector Efficiency: <u>35.0 %</u>
Calibration Date : <u>03/1995</u>	Calibration Reference : <u>GJPO-HAN-1</u>	Logging Procedure : <u>P-GJPO-1783</u>

Log Run Information

Log Run Number : <u>1</u>	Log Run Date : <u>8/9/1995</u>	Logging Engineer: <u>Mike Widdop</u>
Start Depth, ft.: <u>0.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>100.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>



Borehole

22-04-11

Log Event A

Analysis Information

Analyst : S.E. Kos

Data Processing Reference : Data Analysis Manual Ver. 1

Analysis Date : 1/18/1996

Analysis Notes :

This borehole was logged in one log run. The pre- and post-field verification spectra indicated that the logging system was operating properly during data collection. The energy/channel drift observed during the logging runs exceeded the search parameters of the analysis software, and multiple energy calibrations were required to process the data.

The casing thickness is 5/16 (0.3125) in. The casing correction used to process the data was for 0.330-in. casing; therefore, slight over-estimation of radionuclide concentrations were calculated.

Cs-137 and Co-60 were the only man-made radionuclides detected. Cs-137 was detected from the surface to a depth of 43.5 ft, and at a few isolated locations. Co-60 was detected at the bottom of the borehole.

Details regarding the interpretation of the data for this borehole are presented in the Tank Summary Data Report for tank BY-104.

Log Plot Notes:

Separate log plots show the man-made (e.g., Cs-137) and the naturally occurring radionuclides (K-40, U-238, and Th-232). The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations.

A combination plot includes both the man-made and natural radionuclides, in addition to the total gamma derived from the spectral data and the Westinghouse Hanford Company (WHC) Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data from WHC with no attempt to adjust the depths to coincide with the SGLS data.

Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the minimum detection level (MDL). The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.