



Borehole **30-07-05**

Log Event A

Borehole Information

Farm : <u>C</u>	Tank : <u>C-107</u>	Site Number : <u>299-E27-89</u>
N-Coord : <u>42,823</u>	W-Coord : <u>48,447</u>	TOC Elevation : <u>646.00</u>
Water Level, ft :	Date Drilled : <u>10/31/1974</u>	

Casing Record

Type : <u>Steel-welded</u>	Thickness : <u>0.280</u>	ID, in. : <u>6</u>
Top Depth, ft. : <u>0</u>	Bottom Depth, ft. : <u>100</u>	

Borehole Notes:

This borehole was drilled in October 1974 and completed to a depth of 100 ft with 6-in. casing. The casing thickness is presumed to be 0.280 in., on the basis of the published thickness for schedule-40, 6-in. steel tubing. No information was available that indicated the borehole was perforated or grouted; therefore, it is assumed that the borehole was not perforated or grouted. The top of the casing, which is the zero reference for the SGLS, is flush with the ground surface.

Equipment Information

Logging System : <u>2</u>	Detector Type : <u>HPGe</u>	Detector Efficiency: <u>35.0 %</u>
Calibration Date : <u>10/1996</u>	Calibration Reference : <u>GJO-HAN-13</u>	Logging Procedure : <u>P-GJPO-1783</u>

Log Run Information

Log Run Number : <u>1</u>	Log Run Date : <u>03/19/1997</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>99.5</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>53.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>
Log Run Number : <u>2</u>	Log Run Date : <u>03/20/1997</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>54.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>0.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>



Borehole **30-07-05**

Log Event A

Analysis Information

Analyst : E. Larsen

Data Processing Reference : MAC-VZCP 1.7.9

Analysis Date : 07/29/1997

Analysis Notes :

This borehole was logged by the SGLS in two log runs. The pre- and post-survey field verification spectra met the acceptance criteria established for the peak shape and detector efficiency, confirming that the SGLS was operating within specifications. The energy calibration and peak-shape calibration from these spectra were used to establish the peak resolution and the channel-to-energy parameters used in processing the spectra acquired during the logging operation.

Casing correction factors for a 0.280-in.-thick steel casing were applied during analysis.

The man-made radionuclide Cs-137 was detected in this borehole. Intermittent to continuous Cs-137 contamination was detected from the ground surface to 35.5 ft. The presence of Cs-137 was also detected continuously from 49 to 53.5 ft and intermittently from 56 to 77 ft.

The K-40 concentration values increase at 40 ft and remain elevated to depth of 48.5 ft. A sharp decrease in the K-40 concentrations occurs at about 50 ft. The K-40 concentration values remain elevated and exhibit moderate variability from 52 ft to the bottom of the logged interval.

Shape factor data analysis was performed using the SGLS data from this borehole.

Additional information and interpretations of log data are included in the main body of the Tank Summary Data Reports for tanks C-104 and C-107.

Log Plot Notes:

Separate log plots show the man-made and the naturally occurring radionuclides. The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations.

Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the MDL. The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.

A combination plot includes the man-made and natural radionuclides, the total gamma derived from the spectral data, and the Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data. No attempt has been made to adjust the depths of the gross gamma logs to coincide with the SGLS data.