

Hanford Site Solid Waste Acceptance Criteria

Prepared for the U.S. Department of Energy
Assistant Secretary for Environmental Management

Contractor for the U.S. Department of Energy
under Contract DE-AC06-08RL14788



CH2MHILL
Plateau Remediation Company

P.O. Box 1600
Richland, Washington 99352

Approved for Public Release;
Further Dissemination Unlimited

TRADEMARK DISCLAIMER

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

This report has been reproduced from the best available copy.

Printed in the United States of America

HNF-EP-0063, REVISION 15

Hanford Site Solid Waste Acceptance Criteria

HNF-EP-0063, Revision 15

This page intentionally left blank.

Contents

1	Introduction	1-1
1.1	Purpose and Scope	1-1
1.2	Roadmap to the Waste Acceptance Criteria	1-2
1.3	Waste Acceptance Process.....	1-3
1.4	Generator Responsibilities.....	1-3
1.4.1	Waste Certification Program.....	1-3
1.4.2	Quality Assurance Program.....	1-3
1.4.3	Waste Minimization Program.....	1-3
1.4.4	Waste Forecast	1-3
1.5	Evaluation of Generator Waste Certification Program	1-4
1.6	Exceptions to the Waste Acceptance Criteria.....	1-4
1.6.1	WFMP Project-Approved Exceptions.....	1-5
1.6.2	DOE-Approved Exceptions.....	1-5
1.6.3	Regulatory Agency-Approved Exceptions.....	1-5
1.7	Precedence of Requirements.....	1-5
2	General Requirements	2-1
2.1	General Radioactive Classes of Waste Managed At Hanford Site TSD Units.....	2-1
2.2	Composition of Waste and Containers	2-1
2.3	Prohibited Waste.....	2-1
2.4	Physical and Chemical Characterization	2-1
2.4.1	Types of Knowledge	2-2
2.4.2	General Waste Knowledge Requirements.....	2-2
2.4.3	Land Disposal Restrictions Waste Knowledge	2-3
2.4.4	Exceptions to Physical and Chemical Characterization Requirements.....	2-3
2.4.5	Recertification	2-3
2.5	Radiological Characterization.....	2-4
2.5.1	Identification of Major Radionuclides.....	2-4
2.5.2	Methods for Establishing Radionuclide Inventory.....	2-4
2.5.3	Additional Detail on Mobile Radionuclide Characterization.....	2-6
2.5.4	Recertification	2-6
2.5.5	Radioactive Material Shipments Less Than Values Specified In 49 CFR 173.436 or Derived According to 49 CFR 173.433.....	2-6
2.6	Waste Segregation and Treatment and/or Disposal Path.....	2-6
2.6.1	Segregation of Uncontaminated Waste from Radioactive Waste.....	2-6
2.6.2	Radiological Release of Waste.....	2-7
2.6.3	Segregation for Treatment, Storage, and/or Disposal.....	2-7

2.6.4	Waste Streams Having No Established Treatment/Disposal Path.....	2-7
2.6.5	Low-Level Mixed Waste from Non-PRC Generators.....	2-7
2.7	Management and Certification of Transuranic Waste	2-8
2.8	Records	2-8
2.9	Classified and Accountable Nuclear Material	2-8
2.10	Waste Verification	2-8
2.11	Physical and Chemical Criteria.....	2-8
2.11.1	Chemical Compatibility	2-8
2.11.2	Asbestos-Containing Waste	2-9
2.11.3	Heat Generation.....	2-9
2.11.4	Gas Generation.....	2-9
2.12	Radiological Criteria.....	2-9
2.12.1	Criticality Safety Limits	2-9
2.12.2	Dose Equivalent Curie Limits	2-9
2.12.3	Package Removable Contamination Limits	2-10
2.13	Packaging Criteria.....	2-10
2.13.1	Container Selection	2-10
2.13.2	Condition of Containers	2-10
2.13.3	Securing Waste and Shielding.....	2-10
2.13.4	Labeling.....	2-10
3	Acceptance Criteria for Disposal in the Low-Level Burial Grounds.....	3-1
3.1	Facility Description and Function.....	3-1
3.2	Prohibited Waste.....	3-1
3.3	Physical and Chemical Criteria.....	3-3
3.3.1	Liquids and Liquid-Containing Waste	3-3
3.3.2	Land Disposal Restrictions.....	3-3
3.3.3	Compatibility of Waste with Liner.....	3-4
3.3.4	Gas Generation.....	3-5
3.4	Radiological Criteria.....	3-5
3.4.1	Radiological Concentration Limits.....	3-5
3.4.2	Criticality Safety Limits	3-6
3.4.3	Package Dose Rate Limits.....	3-6
3.5	Packaging Criteria.....	3-6
3.5.1	Package Construction.....	3-6
3.5.2	Handling of Packages.....	3-7
3.5.3	Minimization of Subsidence.....	3-7
3.5.4	Labeling.....	3-7
3.5.5	Bulk (Noncontainerized) Waste	3-7

4	Acceptance Criteria for the Central Waste Complex.....	4-1
4.1	Facility Description and Function.....	4-1
4.2	Prohibited Waste.....	4-1
4.3	Physical and Chemical Criteria.....	4-1
4.3.1	Liquids and Liquid-Containing Waste	4-1
4.4	Radiological Criteria.....	4-1
4.4.1	Package Dose Rate Limits.....	4-1
4.5	Packaging Criteria.....	4-3
4.5.1	Container Selection	4-3
4.5.2	Protective Coatings and Liners.....	4-3
4.5.3	Packaging of Liquid Waste in Labpacks	4-3
4.5.4	Package Size and Weight Limits.....	4-3
4.5.5	Stacking.....	4-4
4.5.6	Waste Pallets	4-4
5	Acceptance Criteria for the T Plant Complex	5-1
5.1	Facility Description and Function.....	5-1
5.2	Prohibited Waste.....	5-1
5.3	Radiological Criteria.....	5-1
5.3.1	Package External Dose Rate Limits	5-1
5.3.2	Internal Dose Rate and Contamination Limits for Decontamination and Processing	5-1
5.4	Packaging Criteria.....	5-3
5.4.1	Container Selection	5-3
5.4.2	Protective Coatings and Liners for Stored Waste.....	5-3
5.4.3	Container Size Limits.....	5-3
5.4.4	Container Weight Limits.....	5-3
6	Acceptance Criteria for the Waste Receiving and Processing Facility.....	6-1
6.1	Facility Description and Function.....	6-1
6.2	Prohibited Waste.....	6-1
6.3	Packaging Criteria.....	6-1
6.3.1	Protective Coatings and Liners for Stored Waste.....	6-1
6.3.2	Noncombustible Containers	6-3
6.3.3	Package Size Limits	6-3
6.3.4	Package Weight Limits	6-3
6.3.5	Labeling.....	6-3
6.4	Package Dose Rate Limits	6-3
7	References	7-1

Appendices

Appendix A	Radiological Calculation Methods	A-i
Appendix B	Fissionable Material Content Limits	B-i
Appendix C	Labeling of Waste Containers	C-i
Appendix D	Selection of Compatible Containers, Coatings, and Liners.....	D-i
Appendix E	Selection and Use Of Void Fillers, Sorbents, and Stabilizing Materials.....	E-i
Appendix F	Radiological Release of Waste.....	F-i
Appendix G	Contact-Handled Transuranic Waste Certification Requirements	G-i
Appendix H	Approved Vents	H-i
Appendix I	Remote-Handled Transuranic Waste Acceptance Criteria.....	I-i

Tables

Table 3-1. LLBG Dangerous Waste Numbers	3-2
Table 3-2. Chemical Constituents Known to be Incompatible with Liner System	3-4
Table 4-1. CWC Dangerous Waste Numbers.....	4-2
Table 4-2. Central Waste Complex Container Size and Floor Loading Limits.....	4-4
Table 5-1. T Plant Complex Dangerous Waste Numbers	5-2
Table 6-1. The WRAP Dangerous Waste Numbers	6-2

This page intentionally left blank.

Terms

AK	acceptable knowledge
ALARA	as low as reasonably achievable
ASTM	American Society for Testing of Materials
CBFO	Carlsbad Field Office
CERCLA	<i>Comprehensive Environmental Response, Compensation and Liability Act of 1980</i>
CFR	<i>Code of Federal Regulations</i>
CHPRC	CH2M HILL Plateau Remediation Company
CH-TRAMPAC	contact handled transuranic waste authorized methods for payload control
CH TRU	contact-handled transuranic
CIN	container identification number
CPR	cellulosics, plastics, and rubber
CPS	criticality prevention specification
CSER	criticality safety evaluation report
CSR	criticality safety representative
DQO	data quality objective
CWC	Central Waste Complex
DE-Ci	dose equivalent curie
DOE	U.S. Department of Energy
DOT	U.S. Department of Transportation
EPA	U.S. Environmental Protection Agency
FGE	fissile gram equivalent
g/swb	gram per standard waste box
GW	gross weight
HEPA	high-efficiency particulate air
HIC	high-integrity container
HNF	Hanford Nuclear Facility (document identifier)
HPC	high performance coating

HQ	headquarters
HTO	tritiated water
H/X	Hydrogen to fissile atom ratio
ICRP	International Commission of Radiological Protection
LDR	land disposal restrictions
LLBG	Low-Level Burial Grounds
LPC	low performance coating
MDSA	Master Documented Safety Analysis
MPC	medium performance coating
NDA	nondestructive assay
NDE	nondestructive examination
NRC	U.S. Nuclear Regulatory Commission
PCB	polychlorinated biphenyl
PE-Ci	plutonium equivalent curie
QAP	quality assurance program
RCRA	<i>Resource Conservation and Recovery Act of 1976</i>
RH TRU	remote-handled transuranic
RL	U.S. Department of Energy, Richland Operations Office
SAR	Safety Analysis Report
SWB	standard waste box
SWIFT	Solid Waste Integrated Forecast Technical
SWOC	Solid Waste Operations Complex
TDOP	ten drum overpack
TMU	total measurement uncertainty
TRU	transuranic
TRUCON	TRUPACT-II Content Code
TRUPACT II	transuranic package transporter II
TSCA	<i>Toxic Substances Control Act of 1976</i>
TSD	treatment, storage, and/or disposal
VIPAC	vibratory compaction fuel pins

WAC	<i>Washington Administrative Code</i>
WFMP	Waste & Fuels Management Project
WIPP	Waste Isolation Pilot Plant
WRAP	Waste Receiving and Processing Facility
WSRd	waste specification record

This page intentionally left blank.

Definitions

Acceptable knowledge. Characterization information collected by a generator to meet waste management requirements and determined to be adequate by the treatment, storage, and/or disposal (TSD) unit.

Asbestos-containing waste material. Mill tailings or any waste that contains commercial asbestos and is generated by a source subject to Title 40, *Code of Federal Regulations* (CFR) 61 Subpart M. This term includes filters from control devices, friable asbestos waste material, and bags or other similar packaging contaminated with commercial asbestos. As applied to demolition and renovation operations, this term also includes regulated asbestos-containing material waste and waste materials contaminated with asbestos including disposable equipment and clothing (40 CFR 61.141).

Bulk waste. Waste that is not containerized for disposal and contains potentially dispersible radiological contamination, such as soil and rubble.

Byproduct material. (1) Any radioactive material (except special nuclear material) yielded in or made radioactive by exposure to the radiation incident to the process of producing or utilizing special nuclear material, and (2) the tailings or wastes produced by the extraction or concentration of uranium or thorium from any ore processed primarily for its source material content (DOE M 435.1-1).

Certifiable form. The waste is in a form capable of being certified for shipment to and disposal at the Waste Isolation Pilot Plant.

Chelating agent. Amine polycarboxylic acids (e.g., Ethylenediamine Tetraacetic Acid, Diethylenetriaminepentaacetic Acid), hydroxy-carboxylic acids, and polycarboxylic acids (e.g., citric acid, carboic acid, and glucinic acid) (10 CFR 61.2).

Class IV oxidizer. An oxidizer that can undergo an explosive reaction due to contamination or exposure to thermal or physical shock. In addition, the oxidizer will enhance the burning rate and could cause spontaneous ignition of combustible materials (UFC, 1997).

Combustible waste. Any waste that does not meet the definition of non-combustible waste.

Contact handled. Packaged waste whose external surface dose rate does not exceed 2 milliSieverts/ hour (200 millirem/ hour), except that packages larger than 208 L (55 gal) could have a marked point on the bottom or side with a surface dose rate up to 10 milliSieverts/ hour (1,000 millirem/ hour).

Container. Any portable device in which a material is stored, transported, treated, disposed, or otherwise handled (*Washington Administration Code* [WAC] 173-303-040).

Corrosive material. (Class 8) means a liquid or solid that causes full thickness destruction of human skin at the site of contact within a specified period of time. A liquid that has a severe corrosion rate on steel or aluminum based on the criteria in 49 CFR 173.137(c)(2) is also a corrosive material (49 CFR 173.136).

Corrosive waste. A dangerous waste that exhibits the characteristic of corrosivity defined in WAC 173-303-090(6).

Dangerous waste. Solid waste designated in WAC 173-303-070 through WAC 173-303-100 as dangerous or extremely hazardous waste, or mixed waste (WAC 173-303-040).

Dangerous waste constituents. Those constituents listed in WAC 173-303-9905 and any other constituents that have caused a waste to be a dangerous waste under WAC 173-303.

Decontamination. The removal of radioactive material from facilities, equipment, or soils by washing, heating, chemical or electrochemical action, mechanical cleaning, or other techniques.

Disposal facility. The land, structures, and equipment comprising a facility at which hazardous waste is intentionally placed into or on any land or water, and at which waste will remain after closure.

Dose equivalent curie (DE-Ci). A method of normalizing the radiotoxicity of various radionuclides to plutonium-239 for use in establishing that operations remain within approved safety bases at certain Hanford Site waste management units. The normalization is based on the relative committed effective dose equivalent from inhalation of each radionuclide to that of plutonium-239 using the conversion factors from the International Commission of Radiological Protection (ICRP) Publication 71, "Age-dependent doses to members of the public from intake of radionuclides: Part 4, Inhalation dose coefficients."

U.S. Environmental Protection Agency (EPA) hazardous waste numbers. The number assigned by EPA to each hazardous waste listed in 40 CFR 261, Subpart D, and to each characteristic identified in 40 CFR 261, Subpart C.

Explosive waste. A waste that meets the definition of WAC 173-303-090 (7)(a)(vi), (vii) or (viii).

Extremely hazardous waste. Dangerous waste and mixed waste designated in WAC 173-303-100 as extremely hazardous (WAC 173-303-040).

Facility. All contiguous land, structures, other appurtenances, and improvements on the land, used for recycling, reusing, reclaiming, transferring, treating, storing, or disposing of dangerous waste. The Hanford facility consists of several TSD operational units (e.g., one or more landfills, surface impoundments, or combinations of these) (WAC 173 303-040).

Fissile material. Material made up of radionuclides that will sustain a chain reaction by thermal (slow) neutron-induced fission. For the Hanford Site criticality safety program, uranium-233, uranium-235, plutonium-239, and plutonium-241 are the primary radionuclides of interest.

Fissionable materials. Substances containing radionuclides capable of sustaining a nuclear fission chain reaction (regardless of neutron energy). Such material could be fissionable only by nature of its form, configuration, or environment. This includes, but is not limited to, uranium-233, uranium-235, plutonium-238, plutonium-239, plutonium-240, plutonium-241, neptunium-237, americium-241, and curium-244.

Flammable liquid. A liquid having a flash point of not more than 60.5° C (141° F), or any material in a liquid phase with a flash point at or above 37.8° C (100° F) that is intentionally heated and offered for transportation at or above its flash point in a bulk packaging (49 CFR 173).

Flammable solid. Any of the following types of materials: wetted explosives, self-reactive materials that are liable to undergo a strongly exothermal decomposition caused by excessively high temperatures or contamination, or readily combustible solids that might cause a fire through friction (49 CFR 173).

Free liquids. Those liquids determined to be present in a waste as defined by the Paint Filter Liquids Test, Method 9095 of Test Methods for Evaluating Solid Waste, Physical/Chemical Methods (SW-846).

Generator. Any person, by site, whose act or process produces radioactive or mixed waste or whose act first causes a waste to become subject to regulation under WAC 173-303. The term generator also includes any person or organization that manages a dangerous waste at the generating site on behalf of the generator.

Gross weight. The tare weight of a container plus the weight of its contents.

Hanford Site Treatment, Storage, and/or Disposal Unit or Hanford Site TSD Unit. Any one of the operational TSD units having acceptance criteria defined by this document. This specifically excludes all other TSD units identified on the Hanford Site.

Hazardous waste. Solid waste designated by 40 CFR 261 and regulated as a hazardous waste and/or mixed waste by EPA.

High-level waste. The highly radioactive waste material resulting from the reprocessing of spent nuclear fuel, including liquid waste produced directly in reprocessing and any solid material derived from such liquid waste that contains fission products in sufficient concentrations; and other highly radioactive material that is determined, consistent with existing law, to require permanent isolation (DOE M 435.1-1).

Ignitable waste. A dangerous waste that exhibits the characteristic of ignitability as described in WAC 173-303-090(5).

Incompatible waste. A dangerous waste that is unsuitable for placement in a particular device or facility because it might corrode or decay the containment materials or is unsuitable for mixing with another waste or material because the mixture might produce heat or pressure, fire or explosion, violent reaction, toxic dusts, fumes, mists, or gases, or flammable fumes or gases (WAC 173-303-040).

Infectious waste. Any waste that contains or is suspected of containing pathogenic microorganisms infectious to humans, including: cultures and stocks of infectious agents, human blood and body fluids, contaminated animal carcasses, body parts, bedding exposed to infectious agents, and human pathological waste. Waste that has been treated by heat (e.g., incineration, autoclaving) or chemical disinfectants to destroy pathogenic organisms is not considered infectious waste.

Inner liner. A continuous layer of material placed inside a tank or container that protects the construction materials of the tank or container from the contained waste or reagents used to treat the waste (WAC 173-303-040).

Lab pack. A packaging method where a number of inner containers of waste are packaged into an outer drum as specified in 49 CFR 173.12(b). For this document, the term also could be used for U.S. Department of Transportation (DOT) Class 7 materials packaged in the same manner.

Land disposal restrictions. The restrictions and requirements for land disposal of hazardous or dangerous waste as specified in 40 CFR 268 and WAC 173-303-140. (Refer to definitions for *Resource Conservation and Recovery Act of 1976* [RCRA] Land Disposal Restrictions and Washington State Land Disposal Restrictions.)

Low-level mixed waste. Waste that meets both the definition of low-level waste and mixed waste.

Low-level waste. Radioactive waste that is not high-level radioactive waste, spent nuclear fuel, transuranic waste, byproduct material (as defined in section 11e.(2) of the *Atomic Energy Act of 1954* (42 USC 2011 et seq.), or naturally occurring radioactive material (DOE M 435.1-1).

Mixed waste. A dangerous, extremely hazardous, or acutely hazardous waste that contains both a nonradioactive hazardous component and, as defined by 10 CFR 20.1003, source, special nuclear, or byproduct material subject to the *Atomic Energy Act of 1954* (42 USC 2011 et seq.) (WAC 173-303-040).

Major radionuclides. Those radionuclides in a waste that contribute significantly to the overall hazards of the waste, including criticality and human exposure by various pathways, as the waste is managed.

Mobile radionuclides. Radionuclides that tend to migrate readily through Hanford soil and pose the highest risk of impact to groundwater resources: tritium (hydrogen-3), carbon-14, chlorine-36, selenium-79, molybdenum-93, technetium-99, iodine-129, rhenium-187, uranium (all isotopes), and neptunium-237.

Non-biodegradable sorbent. A sorbent material meeting the requirements of 40 CFR 264.314(e).

Noncombustible waste. Containerized waste that shows no evidence of combustion or decomposition on exposure to 538° C (1,000° F) for 10 minutes as specified by NUREG-0782, or waste that has been stabilized by grouting or disposal in a high-integrity container (HIC).

Organic peroxide. Any organic compound containing oxygen (O) in the bivalent -O-O- structure and that might be considered a derivative of hydrogen peroxide, where one or more of the hydrogen atoms have been replaced by organic radicals.

Onsite. Any property within the Hanford Site boundary. (NOTE: DOT, *Comprehensive Environmental Response, Compensation and Liability Act of 1980* [CERCLA], and RCRA regulations have varying definitions of onsite; the precise DOT, CERCLA, and RCRA meanings of the term are not implied in the use of the term in this document.)

Operational safety requirements or technical safety requirements. Those requirements that define the conditions, safe boundaries, and bases thereof and the management or administrative controls required to ensure the safe operation of a nuclear facility.

Organic liquid. A chemical compound having carbon-carbon chemical bonds and that is a liquid at standard temperature and pressure. Typical organic liquids include organic solvents, petroleum oils, and synthetic oils.

Outer packaging. The outermost enclosure of a composite or combination packaging together with any absorbent materials, cushioning, and any other components necessary to contain and protect inner receptacles or inner packagings (49 CFR 171).

Performance assessment. An analysis of a radioactive waste disposal facility conducted to demonstrate there is a reasonable expectation that performance objectives established for the long-term protection of the public and the environment will not be exceeded following closure of the facility (DOE M 435.1-1).

Plateau Remediation Company. The current contract with the DOE to operate portions of the Hanford Site, including the facilities described in this document. CH2M HILL is the Plateau Remediation Company contractor.

Plutonium-equivalent curie (PE-Ci). A method of normalizing the radiotoxicity in transuranic waste to plutonium-239 for use in establishing the approved safety limits at the Waste Isolation Pilot Plant (WIPP) located near Carlsbad, New Mexico. The normalization is based on the relative committed effective dose equivalent from inhalation of a radionuclide to that of plutonium-239 using the conversion factors from DOE/EH-0071, "Internal Dose Conversion Factors for Calculation of Dose to the Public," as described in Appendix B of DOE/WIPP-02-3122.

Plutonium-239 fissile gram equivalent. A method of normalizing fissile and fissionable isotopes to plutonium-239 for use in establishing criticality safety limits for the Hanford Site Solid Waste Program. This is consistent with the method found in the safety analysis reports for the transuranic package transporter-II and 72-B casks for plutonium-239, uranium-233, and uranium-235 and in ANSI/ANS 8.15 for other fissile, fissionable, and special actinide elements.

Polychlorinated biphenyl (PCB). Any chemical substance that is limited to the biphenyl molecule that has been chlorinated to varying degrees or any combination of substances that contains such substance (40 CFR 761.3).

Process knowledge. Knowledge the generator applies to a solid waste to determine if it is a dangerous or mixed waste in light of the materials or the processes used, when such knowledge can be demonstrated to be sufficient for determining whether a solid waste is designated properly. Process knowledge includes information on waste obtained from existing published or documented waste analysis data or studies conducted on mixed waste from processes similar to that which generated the waste. Process knowledge for mixed waste also could include information obtained from surrogate material.

Pyrophoric material. A liquid or solid that, even in small quantities and without an external ignition source, can ignite within 5 minutes after coming in contact with air when tested as specified by 49 CFR 173.124.

Qualified analytical data. Data from waste analysis that is not fully compliant with an approved sampling and/or analysis method (e.g., where quality assurance/quality control deficiencies were identified from the sampling and/or analysis of the waste).

Radioactive waste. Any garbage, refuse, sludges, and other discarded material, including solid, liquid, semisolid, or contained gaseous material that must be managed for its radioactive content (DOE M 435.1-1).

RCRA land disposal restrictions. The requirements and restrictions for land disposal of hazardous waste codified in 40 CFR 268.

Reactive waste. A dangerous waste that exhibits the characteristic of reactivity as described in WAC 173-303-090(7).

Remote handled. Packaged waste whose external surface dose rate exceeds the limits for contact-handled waste.

Remote-handled transuranic waste. Packaged transuranic waste whose unshielded payload container external surface dose rate exceeds 2 milliSieverts/ hour (200 millirem/ hour), unless the shielding is part of a WIPP-approved pipe overpack configuration.

Secular equilibrium. Equilibrium that occurs between a parent radionuclide and daughter radionuclide where the half-life of the parent is significantly longer than the daughter.

Shock-sensitive waste. Reactive waste meeting the definition of WAC 173-303-090(7)(a)(vii) (waste is readily capable of detonation or explosive composition or reaction at standard temperature and pressure).

Solidification. Any technique that reduces the solubility and mobility of dangerous waste constituents and/or radionuclides by physical means rather than by bonding or chemically reacting with the stabilizing material.

Sorb. To absorb or adsorb.

Sorbent. A material used to soak up free liquids by either adsorption or absorption, or both.

Specific activity. The radiological activity (disintegrations per unit of time) of a radionuclide per unit mass of that radionuclide. The specific activity of a material in which the radionuclide is essentially uniformly distributed is the radiological activity per unit mass of the material.

Spent nuclear fuel. Fuel that has been withdrawn from a nuclear reactor following irradiation, the constituent elements of which have not been separated by reprocessing. Test specimens of fissionable material irradiated for research and development only, and not production of power or plutonium, may be classified as waste, and managed in accordance with the requirements of DOE M 435.1 when it is technically infeasible, cost prohibitive, or would increase worker exposure to separate the remaining test specimens from other contaminated material (DOE M 435.1-1).

Spontaneously combustible material. A pyrophoric or self-heating material (49 CFR 171).

Stabilization. Any technique that reduces the solubility and mobility of dangerous waste constituents and/or radionuclides by bonding or chemically reacting with the stabilizing material. The term stabilization to meet land disposal restrictions (LDR) is used when the specific definition of 40 CFR 268.42, Table 1, is implied.

Standard waste box. A payload container authorized for use with TRUPACT-II transportation packages for packaging of transuranic waste (NRC, 1996).

State-only dangerous waste. Any waste that is regulated as a dangerous waste under WAC 173-303 but is not regulated as a hazardous waste under 40 CFR 261 (WAC 173-303-040).

Storage. The holding of radioactive waste for a temporary period, at the end of which the waste is treated, disposed of, or stored elsewhere (DOE M 435.1-1).

Toxic. Having the properties to cause or to significantly contribute to death, injury, or illness of humans or wildlife (WAC 173-303-040).

Toxic Substances Control Act of 1976 PCB waste. Any PCB-containing waste that is regulated under the TSCA requirements codified in 40 CFR 761.

Transuranic mixed waste, or TRU-mixed waste. Waste that meets both the definitions of transuranic waste and mixed waste.

Transuranic waste. Radioactive waste containing more than 100 nanocuries (3,700 becquerels) of alpha-emitting transuranic isotopes per gram of waste, with half-lives greater than 20 years, except for: (1) high-level radioactive waste; (2) waste that the Secretary of Energy has determined, with the concurrence of the Administrator of EPA, does not need the degree of isolation required by the 40 CFR Part 191 disposal regulations; or (3) waste that the Nuclear Regulatory Commission (NRC) has approved for disposal on a case-by-case basis in accordance with 10 CFR 61 (DOE M 435.1-1).

Treatment. The physical, chemical, or biological processing of dangerous waste to make such waste nondangerous or less dangerous, safer for transport, amenable for energy or material resource recovery, amenable for storage, or reduced in volume, with the exception of compacting, repackaging, and sorting as allowed under WAC 173-303-400(2) and 173-303-600(3) (WAC 173-303-040).

Treatment, storage, and/or disposal unit manager or TSD unit manager. The individual, or delegate, having responsibility for the operation of a given TSD unit within the limits of the TSD unit RCRA Permit, safety basis, performance assessment, and/or other environmental requirements.

U.S. Department of Energy, Richland Operations Office (RL). The field element of the DOE responsible for the storage and disposal facilities listed in this document.

Washington State Land Disposal Restrictions or Washington State LDR. The land disposal restrictions of WAC 173-303-140(4).

Washington State-Only Dangerous Waste. State-only dangerous waste.

Waste Specification Record. A document that identifies the anticipated TSD methods to be applied to a given class of waste managed at Hanford Site TSD units.

Waste stream. A waste or group of wastes from a process or a facility with similar physical, chemical, or radiological properties (DOE M 435.1-1).

Water-reactive waste. Waste that meets the definition of WAC 173-303-090(7)(a)(ii), (iii) or (iv).

Waste & Fuels Management (WFMP) acceptance organization. The organization within the Waste & Fuels Management Project that is responsible for waste acceptance, including approval of waste stream profiles and approval of individual waste packages and shipments, and for coordinating the approval of case-by-case evaluations for specific criteria and exceptions to the acceptance criteria.

This page intentionally left blank.

1 Introduction

U.S. Department of Energy (DOE) Order 435.1, *Radioactive Waste Management*, requires that each treatment, storage, and/or disposal facility (referred to in this document as a treatment, storage, and/or disposal [TSD] unit) that manages low-level or transuranic (TRU) waste (including mixed waste and *Toxic Substances Control Act of 1976* [TSCA] polychlorinated biphenyl [PCB] waste) maintain waste acceptance criteria. This requirement is implemented through DOE/RL-2000-25, *Contracts Requirement Document 435.1, Radioactive Waste Management Plan*. The waste acceptance criteria for DOE, Richland Operations Office (RL) TSD units are provided, including criteria for the Low-Level Burial Grounds (LLBG), the Central Waste Complex (CWC), the T Plant, and the Waste Receiving and Processing (WRAP) Facility.

1.1 Purpose and Scope

The criteria for each TSD unit are established in this document to ensure newly generated waste accepted can be managed within the operating requirements of the unit, including, but not limited to, environmental regulations, DOE Orders, permits, technical safety requirements (HNF-11724, Section 9.1; HNF-15280, Section 5.6.12), waste analysis plans, and performance assessments. The requirements of DOE O 435.1 and DOE M 435.1-1 are implemented through DOE/RL-2000-25. Revisions to the acceptance criteria document require an Unreviewed Safety Question review to document that the changes are consistent with current applicable safety analyses.

All waste received for acceptance at the Solid Waste Operations Complex (SWOC) facilities will be disposal ready; meeting all applicable Federal and State land disposal restrictions (LDR) requirements, radiological stabilization requirements (GTC1 wastes and mobile radionuclides), 90 percent full requirements, and meeting the 50 per square inch (psi) compaction criteria for the disposal trenches. It is expected that all low-level waste/mixed low-level waste (LLW/MLLW) with a disposition path will have received treatment if required and shipped for final disposition. CWC will accept LLW/MLLW wastes with no identifiable disposition path using the exception process in Section 1.6. CWC will accept TRU/transuranic mixed (TRUM) wastes in certifiable form with no identifiable disposition path.

Acceptance criteria apply to the following RL TSD units:

- The lined trenches in the LLBG
- The Central Waste Complex (CWC)
- The WRAP Facility
- The T Plant Complex.

Waste from all generators, including Hanford Site and offsite facilities, must comply with these criteria. Exceptions can be granted as provided in Section 1.6.

Specific waste streams could have additional requirements based on the identified TSD pathway. These requirements are communicated in the waste specification records (WSRd) and/or waste stream profile sheet approvals.

The Hanford Site manages nonradioactive waste through direct shipments to offsite contractors. The waste acceptance requirements of the offsite TSD facility must be met for these nonradioactive wastes. This document does not address the acceptance requirements of these offsite facilities.

Selection of specific storage locations and container movements within a TSD unit are outside the scope of these acceptance criteria.

1.2 Roadmap to the Waste Acceptance Criteria

Chapter 1 provides introductory information and describes general administrative requirements that apply to generators.

Chapter 2 identifies requirements that generally apply to waste sent to any of the TSD units. These criteria relate primarily to overall characterization and segregation methods used by generators. In addition, acceptance criteria that are the same for all units are provided in this chapter.

Chapters 3 through 6 communicate the unit-based criteria for acceptance of waste. Each of these chapters contains a general description of the unit functions followed by identification of prohibited waste, physical/chemical acceptance criteria, radiological acceptance criteria, and packaging criteria. These TSD units and the general functions follow.

- Chapter 3: The lined trench portion (Trenches 31 and 34) of the 218-W-5 Burial Ground is a *Resource Conservation and Recovery Act of 1976 (RCRA)*-permitted disposal unit for certain MLLW and LLW that meets Federal and State LDR. The unit may also dispose of certain types of TSCA PCB waste.
- Chapter 4: The CWC is a storage unit for LLMW, low-level TSCA PCB waste, TRU waste, TRUM waste, TRU TSCA PCB waste, and other waste types that must be stored pending treatment and/or disposal.
- Chapter 5: The T Plant Complex is a multipurpose unit for storage, repackaging, treatment, and decontamination of radioactive waste. The T Plant Complex can accept LLW and TRU waste, including mixed and TSCA PCB waste.
- Chapter 6: The WRAP is a multipurpose unit for processing and treating LLW and TRU waste, including mixed and TSCA PCB waste. The WRAP can perform nondestructive assay (NDA) and nondestructive examination (NDE) of waste containers. The WRAP is the primary unit for repackaging and processing TRU waste for certification for disposal at the Waste Isolation Pilot Plant (WIPP).

Chapter 7 lists references for all chapters except the appendices. Each appendix has its own reference section.

Appendix A provides radiological calculation methods.

Appendix B provides fissionable material content limits.

Appendix C describes labeling of containers.

Appendix D describes selection of containers, coatings, and liners.

Appendix E describes selection of sorbents, stabilizing materials, and void fillers.

Appendix F, "Radiological Release of Waste," has been retired.

Appendix G provides contact-handled TRU waste acceptance criteria and certification requirements.

Appendix H provides a listing of approved vents.

Appendix I provides remote-handled TRU waste acceptance criteria.

1.3 Waste Acceptance Process

The process for obtaining approval to ship waste to the Hanford Site Waste & Fuels Management (WFMP) TSD units is described on the *Hanford Site Solid Waste Acceptance Program* Internet Web site (<http://www.hanford.gov/?page=577>). Use of the waste acceptance process is mandatory.

All non-Hanford Site waste generators must receive approval from the RL before acceptance and shipment of waste to Hanford Site TSD units.

1.4 Generator Responsibilities

Generators of radioactive waste have certain general responsibilities under DOE O 435.1. Acceptance of waste at Hanford Site TSD units is contingent on effectively fulfilling these responsibilities. The generator is responsible for all costs associated with the storage, treatment, disposition, and associated transportation for disposal-ready waste as stated in Section 1.1 of these acceptance criteria.

1.4.1 Waste Certification Program

Generators must implement and maintain a waste certification program to ensure any waste sent to a Hanford Site TSD unit meets the acceptance criteria of that unit (Sections III.J. and IV.J of DOE M 435.1-1). Generators are responsible financially for costs incurred by Hanford Site TSD units as a result of nonconformance with the acceptance criteria. All non-conforming containers can be returned to the generator for resolution. There is no obligation for WFMP TSD units to correct generator nonconformances.

1.4.2 Quality Assurance Program

Each generator shall have a Quality Assurance Program (QAP) as part of its overall waste certification program. The QAP shall implement the requirements of Title 10 *Code of Federal Regulations* (CFR) 830, "Subpart A—Quality Assurance Requirements," and DOE O 414.1C (DOE M 435.1-1). The generator QAP shall be subject to evaluation according to the requirements of Section 1.5.

1.4.3 Waste Minimization Program

Generators shall establish and maintain an auditable waste minimization program, including goals, incentives, procedures, and reports, to ensure the amount of radioactive waste generated and/or shipped for disposal is minimized (DOE M 435.1-1). For Hanford Site generators, the most current version of DOE/RL-91-31 defines the methods for meeting this requirement.

1.4.4 Waste Forecast

Generators that wish to ship waste to the Hanford Site TSD unit shall provide an annual waste forecast. This input is done through the Solid Waste Integrated Forecast Technical (SWIFT) tool. Integration of this data is summarized in the SWIFT Report and provides up-to-date life cycle information about radioactive solid waste expected to be managed by Hanford's WFMP Organization from onsite and offsite generators. The data contained in this report are the official data for solid waste forecasting. Requests to update this forecast are sent out semi-annually, in conjunction with the budget cycle.

The SWIFT report contains two volumes. Volume I provides strictly waste metrics in several forms; (e.g., volume, containers, radionuclides, etc.). Volume II gives detailed history and analyzes any changes to the metrics.

Customized data reports or analyses may be requested by contacting Ms. Linda Maiden:

E-mail: [Linda E Maiden@rl.gov](mailto:Linda_E_Maiden@rl.gov)

Phone: (509) 376-9126

This report and more information are also available at the following Web site address:

<http://www.hanford.gov/swift>.

1.5 Evaluation of Generator Waste Certification Program

Under DOE M 435.1-1, receiving TSD units must evaluate waste to ensure the waste meets the acceptance criteria of the unit. This requirement is implemented through review of information submitted by the generator and verification and confirmation inspections performed on waste containers. When repeated or serious nonconformances are found, additional evaluations will be performed as defined in the waste analysis plan for that TSD unit. When necessary, an onsite audit of the waste certification program of the generator, including applicable portions of the QAP, will be required.

1.6 Exceptions to the Waste Acceptance Criteria

Exceptions to these acceptance criteria may be granted in certain cases. The process to obtain approval of an exception is determined by the source and type of the requirements from which the specific acceptance criterion is derived. These requirements fall into three categories, each having a specific approval process, as described in the following sections.

A generator can request an exception from one or more of the criteria in this document. The request should be a written letter to the WFMP acceptance organization. The request must include the following:

- Specific requirement(s) in this document for which an exception is desired
- Waste type (e.g., TRU waste, TRUM waste, LLW, and MLLW)
- Waste characteristics (e.g., physical descriptions, dose rates, radiological constituents, and hazardous waste constituents)
- Packaging information (e.g., volume, weight, dimensions, internal configuration, and materials)
- Identification of the waste in SWIFT
- Efforts made to comply with the requirements of this document
- How the generator complied with the waste generation/life cycle planning requirements of DOE M 435.1-1
- Alternative analyses (including life cycle estimates) showing that acceptance of waste that is not compliant with requirement(s) of this document is the most cost-effective solution for DOE.

The WFMP acceptance organization will review the exception request and determine the appropriate category and approval process, based on the background documentation for these acceptance criteria. This documentation identifies the source(s) of each requirement in order for a determination to be made whether an exception could be approved by the WFMP acceptance organization, or whether RL and/or regulatory agency approvals are required. On completion of this review, the WFMP acceptance organization will respond in writing, identifying whether the exception is granted, rejected, or requires further evaluation or clarification.

1.6.1 WFMP Project-Approved Exceptions

An exception to these acceptance criteria can be granted when the WFMP acceptance organization demonstrates the exception does not affect compliance with (1) any applicable regulations and (2) any RL and/or regulatory agency-approved requirements. For example, a TSD unit's container size limits are operational requirements not related to any regulation or externally approved document. If a larger container could be managed at that TSD unit with special handling provisions, the WFMP acceptance organization can grant an exception to the container size requirement.

The WFMP acceptance organization, in conjunction with the TSD operations organization, documents and certifies that the exception being granted does not affect compliance with any applicable regulations or any of the externally approved requirements of the TSD units. Project-approved exceptions will include life cycle cost and the most cost-effective solution for DOE.

1.6.2 DOE-Approved Exceptions

Exceptions to acceptance criteria that could affect compliance with DOE-approved requirements documents (e.g., safety basis, performance assessment) or DOE Orders will require a RL waiver, RL approval of a safety document revision, or other RL approval. For this type of exception, the appropriate waiver request, document revision, or other applicable request for approval will be submitted by CH2M HILL Plateau Remediation Company (CHPRC) to the RL.

1.6.3 Regulatory Agency-Approved Exceptions

Exceptions to acceptance criteria that could affect compliance with regulations, permit conditions, compliance orders, or other requirements imposed by a regulatory agency must be submitted by the RL to the affected regulatory agency(ies).

1.7 Precedence of Requirements

Cases may arise where two or more similar requirements or limits occur in the acceptance criteria. All requirements and limits must be met. If it appears one requirement or limit is less restrictive than others, the more restrictive one must be met.

This page intentionally left blank.

2 General Requirements

Certain general requirements apply to acceptance of all waste at Hanford Site TSD units. These requirements are described as follows.

2.1 General Radioactive Classes of Waste Managed At Hanford Site TSD Units

The TSD units covered by these acceptance criteria manage LLW and TRU waste. This generally excludes acceptance of waste classified as high-level waste (HLW), spent nuclear fuel, and/or byproduct material.

2.2 Composition of Waste and Containers

For all waste, a detailed record must be kept of the contents, volume, and weight, as well as any added void fillers, sorbents, stabilization agents, or solidification agents (DOE M 435.1-1).

For containerized waste, the container type, weight, internal and external volume, any shielding provided, and the date packaged must be recorded (DOE M 435.1-1). In the case of lab packs, the record shall include the exact number, type, and volume of inner containers.

2.3 Prohibited Waste

The following waste types are not accepted:

- Dangerous waste not having dangerous waste numbers listed on the TSD unit's approved Part A, Form 3, permit application (Hanford Facility RCRA Permit, WA& 89000 8967, Unit Name Part A Form)
- Explosive waste (HNF-5841; HNF-21239)
- Shock sensitive waste (HNF-1886; HNF-2165; HNF-5841; HNF-9921; HNF-21239)
- Pyrophoric waste (HNF-1886; HNF-2165; HNF-5841; HNF-9921)
- Class IV oxidizer (see definitions) waste (HNF-1886; HNF-2165; HNF-5841; HNF-9921; HNF-21239)
- Waste that is readily capable of detonation, explosive decomposition, reaction at anticipated pressures and temperatures, or explosive reaction with water. Prior to storage, pyrophoric materials shall be treated, prepared, and packaged to be nonflammable (DOE M 435.1-1, Chapters III and IV, N.1)
- Containers packaged such that toxic air pollutants exceed small quantity emission rates in Washington Administrative Code (WAC) 173-460
- Infectious waste.

2.4 Physical and Chemical Characterization

The waste generator must determine the physical and chemical characteristics of the waste with sufficient accuracy and detail to properly designate and manage the waste in accordance with the unit-specific acceptance criteria and all applicable regulations (i.e., knowledge) (e.g., HNF-5841; HNF-9921; HNF-1886; HNF-2165; 40 CFR 264.13; WAC 173-303-300; 40 CFR 761).

The following sections describe the physical/chemical characterization requirements for waste acceptance.

2.4.1 Types of Knowledge

The types of information that can be used for physical/chemical characterization include data from analysis of the waste and knowledge of the materials and/or processes that generate the waste. Knowledge can be obtained using the following types of information:

- Analysis data from a representative sample of the waste or for a waste generated by a similar process
- Test data from a nonradioactive surrogate sample that is chemically representative of a radioactive waste stream
- Material Safety Data Sheets for commercial chemical products
- Mass balance data for the waste generating process, to the extent that such data provides a sufficient understanding of the characteristics of and constituents in the waste stream
- Interview information
- Logbooks
- Procurement records
- Qualified analytical data
- Radiation work packages
- Procedures and/or methods
- Process flow charts
- Inventory sheets
- Vendor information.

The following sections describe how this information may be used to meet the knowledge requirements and when analysis of a representative sample is required.

2.4.2 General Waste Knowledge Requirements

General waste knowledge must be sufficient to determine the waste stream designation and manage the waste in accordance with TSD unit-specific acceptance criteria necessary for proper management of the waste.

Analytical data and/or knowledge of the waste must be sufficient to determine whether the waste is regulated under 40 CFR 261, or 40 CFR 761, and/or WAC 173-303, and to assign correct waste numbers. Knowledge of the waste-generating process alone is used to determine whether a waste stream is a listed waste identified in WAC 173-303-080 through WAC-173-303-082. For other waste numbers and for classification under 40 CFR 761, if the available process knowledge is not sufficient to determine whether the waste is regulated and to assign waste numbers, analysis of a representative sample must be performed. The sampling and testing methods outlined in WAC 173-303-110 must be used for the toxicity characteristics, corrosivity, and free liquids. For other characteristic and state criteria designations, when testing is needed, an appropriate method must be used. Appropriate test methods can include SW-846 test methods or any other methods with proper quality assurance (QA) and quality control (QC).

In cases where one or more constituents are input into a process, but are not expected to be in the waste in concentrations that would cause the waste to be regulated, and when process knowledge is questionable, sampling and analysis should be performed to demonstrate the constituents are below regulated limits. This analysis could be met through chemical screening and considered process knowledge.

NOTE: If sampling and analysis were performed, it would only be needed for initial characterization of a consistent waste stream.

All waste must be characterized in a manner sufficient to ensure the waste can be managed in accordance with the unit-specific waste management requirements set forth in this document. This includes (but is not limited to) sufficient knowledge to demonstrate the waste is not prohibited from management at that unit, to segregate waste containers for compatibility, to ensure compatibility of waste with containers, to ensure the waste can be safely managed, and to segregate waste for TSD in accordance with the WSRds.

2.4.3 Land Disposal Restrictions Waste Knowledge

For waste that is a hazardous waste as defined in 40 CFR 261, waste characterization must be sufficient to establish whether the waste is a restricted waste under the LDR provisions of 40 CFR 268 and, if so, to determine the applicable LDR subcategories and treatment standard(s) for that waste. Testing of a representative sample at a Hanford Site laboratory or another independent laboratory is required when a generator or treatment facility certifies a waste stream meets a concentration-based treatment standard of 40 CFR 268. To certify a waste stream meets a specified technology treatment standard in 40 CFR 268, the generator or treatment facility must provide data; i.e., an LDR certification form that demonstrates the waste was properly treated by that treatment technology.

In addition, for waste that is a dangerous waste as defined in WAC 173-303, characterization must be sufficient to establish which, if any, of the Washington State LDR requirements of WAC 173-303-140 apply.

2.4.4 Exceptions to Physical and Chemical Characterization Requirements

The following exceptions can be made to the physical/chemical characterization requirements stated previously.

- Hazardous debris that is managed in accordance with the alternative treatment standards for hazardous debris (40 CFR 268.45) does not require sampling and analysis for adequate physical/chemical characterization.
- Hanford Site generators can transfer waste for storage at an onsite TSD unit without full characterization for designation and LDR status, provided the characterization is sufficient to demonstrate the waste can be managed in accordance with the unit-specific acceptance criteria and provided a representative sample (or samples) has been obtained or will be obtained at the TSD unit to fully characterize the waste.
- An alternative management path negotiated by the RL with the appropriate regulatory agency can characterize waste that cannot be characterized in accordance with the requirements stated previously because of factors such as unique chemical or radiological hazards of the waste. This type of exception will be handled by the method outlined in Section 1.6.3.

2.4.5 Recertification

Physical/chemical characterization data for a waste stream must be recertified annually, and whenever the waste-generating process changes. Recertification shall, at a minimum, identify changes to the generating process and any additional analytical data obtained from the waste stream. Sampling and analysis of the

waste stream is not required to be performed more frequently than required by the receiving TSD unit's waste analysis plan.

2.5 Radiological Characterization

The major radionuclides in the waste and the concentration of each major radionuclide must be established with sufficient sensitivity and accuracy to properly classify and manage the waste in accordance with the TSD unit-specific radiological limits (DOE M 435.1-1).

2.5.1 Identification of Major Radionuclides

For the purposes of the radiological criteria in this document, major radionuclides are defined as those radionuclides that meet any of the following conditions. Computational methods for determining these limits are described in Appendix A.

- Any TRU radionuclide present in the waste in concentration exceeding 1 nanocurie per gram.
- Any fissionable radionuclide present in the waste in a quantity exceeding 0.1 fissile gram equivalent per container.
- Any radionuclide present in concentration exceeding 1 percent of its respective Category 1 limit (Appendix A, Table A-2).
- NOTE: This reporting limit does not apply to TRU waste.
- Any mobile radionuclide present in concentration exceeding its reporting limit (Appendix A, Table A-2).
- NOTE: This reporting limit does not apply to TRU waste.
- For waste that has no detectable radiological activity but cannot be radiologically released, major radionuclides are those radionuclides believed to contribute more than 1 percent each to the radiological activity based on available process knowledge. The estimated concentration of the radionuclides should be based on the limit of detection of the analysis method used.
- The amount of uranium-235 and uranium-238 in each waste container must be reported if there is at least 0.1 gram of uranium-235 in the container, or if either isotope is a major radionuclide. The amount of uranium-233 in each waste container must be reported if it contains at least 0.1 gram of uranium-233.
- Any radionuclide that accounts for more than 1 percent of the total radiological activity of the waste must be reported. However, a radionuclide in concentration less than 1.0 E-6 curie per m³, and not otherwise reportable, is exempt from reporting.

2.5.2 Methods for Establishing Radionuclide Inventory

The radionuclide inventory of a waste must be established using a method or combination of methods capable of identifying and quantifying the major radionuclides present. The methods chosen must provide adequate sensitivity and accuracy to ensure the waste is categorized correctly (e.g., Category 1 and 3 limits for the LLBG, correct TRU determination). A graded approach (DOE M 435.1-1) should be applied when planning radiological characterization of waste streams. Using the graded approach, more frequent and detailed analysis is performed when a waste approaches one or more of the limits of these criteria. Conversely, waste that is far below applicable limits of these criteria would not require as extensive or frequent analysis. Use of the data quality objectives (DQO) process (or an equivalent process) in

accordance with DOE M 435.1-1, should help ensure the appropriate type, quantity, and quality of radiological characterization data are obtained.

Both direct and indirect methods can be used for characterization (DOE M 435.1-1). When indirect methods are used, these methods must be corroborated periodically with direct measurements. The frequency of corroborative analysis should be based on the variability of the waste-generating process, and the extent and consistency of previous analytical data. A graded approach should be applied when determining the appropriate type and frequency of corroborative analysis.

The following characterization methods can be used individually or in combination to establish the radionuclide inventory of the waste.

- Process knowledge—Process knowledge includes documented knowledge of the radioactive materials used and the processes that contributed to the radiological content of the waste, along with historical analysis of waste and radiological contamination from the process. Process knowledge can be used to establish the suspected major radionuclides in a waste stream. In addition, process knowledge can be used to eliminate from further consideration those radionuclides not present in sufficient concentration to be major radionuclides as defined in Section 2.5.1, as long as the basis of this determination is documented.
- Radionuclide material accountability—The content of a given radionuclide in a waste can be determined by documented logs detailing the mass or activity of that radionuclide added to and leaving the waste in a controlled process. In addition, data relating to the total inventory of a radionuclide in a process or facility can be used to determine the radionuclide inventory, but must be corroborated periodically with direct measurement methods.
- Field and laboratory analysis methods—Field and laboratory analysis methods, such as NDA, radiochemical analysis, and surveys with field instruments, must be selected as appropriate to detect and quantify the major radionuclides with adequate sensitivity and accuracy for waste classification. Analysis methods that measure gross activity (i.e., not radionuclide-specific) must be used in conjunction with other methods to determine the relative concentration (scaling factors) of each suspected radionuclide, and must be corroborated periodically with radionuclide-specific analysis.
- Computer modeling—Computer modeling, applied appropriately, could be used in conjunction with other methods for radiological characterization. An individual who is knowledgeable and experienced in the use and limitations of the model must perform the modeling. The assumptions and measurements used as inputs to computer modeling must be documented. The computer software must be controlled in a manner that meets conventional QA requirements. Computer models must be corroborated periodically with direct measurement methods.
- Scaling factors—Scaling factors can be used to relate the concentration of a readily measured radionuclide to more difficult-to-measure radionuclides. Scaling factors must be developed from one of the previous methods, and must be corroborated periodically with radionuclide-specific analysis.

Other methods of radiological characterization could be used, but must be documented clearly and approved by the WFMP acceptance organization. Documentation of the method must include a detailed description of the method, the radionuclides identifiable by the method, and a discussion of precision, accuracy, QA and QC methods.

2.5.3 Additional Detail on Mobile Radionuclide Characterization

For LLW and MLLW, mobile radionuclide reporting is critical for compliance with the LLBG performance assessments (WHC-EP-0645 and WHC-SD-WM-TI-730). Because of the low reporting limits and difficulty of analysis of certain mobile radionuclides, this section provides additional detail concerning acceptable knowledge and characterization.

The concentration of each mobile radionuclide must be established and compared to the Appendix A, Table A-2, reporting limit using process knowledge and/or analysis. If process knowledge alone is used to determine a mobile radionuclide is not present in a waste stream at the reporting limit, the basis for this determination must be clearly documented. If available analytical techniques cannot detect a mobile radionuclide at its reporting limit, the concentration could be estimated using a combination of process knowledge, scaling factors, and analytical detection limits.

Mobile radionuclide reporting is intended to measure only the quantity of isotopes that exceeds Hanford Site natural background concentrations. For waste forms that contain uranium that originates from natural background on the Hanford Site, the background concentration of that radionuclide can be subtracted from the total concentration.

2.5.4 Recertification

The radiological characterization of waste streams must be recertified with sufficient frequency to account for changes in the generating process, radiological composition, and radiological decay.

2.5.5 Radioactive Material Shipments Less Than Values Specified In 49 CFR 173.436 or Derived According to 49 CFR 173.433

- All shipments of radioactive materials having activities or activity concentrations less than those listed in 49 CFR 173.436 or derived according to 49 CFR 173.433, are exempt from DOT Regulations. These materials shall be shipped in a container that ensures no loss of the radioactive material during loading, inspections, transportation, and unloading.
- The shipping documentation shall have the following statement placed on it. "The following Container(s) _____ Contain Radioactive Material at concentrations that are not regulated for transportation per DOT Regulations in 49 CFR 173.403, but are not releasable per DOE Order 5400.5 (1990/1993)."
- A radiological survey report shall identify the package radiation exposure rates (i.e., contact and 30 cm [11.8 in.] readings), the expected radionuclides, associated activity levels, and package contamination levels, including an evaluation of hard-to-detect radionuclides (e.g., H-3), when necessary. The radiological survey report shall be sent with the shipment as part of the shipping documents.

2.6 Waste Segregation and Treatment and/or Disposal Path

The following sections discuss waste segregation and the treatment and/or disposal path.

2.6.1 Segregation of Uncontaminated Waste from Radioactive Waste

Generators shall segregate uncontaminated waste from radioactive waste to minimize waste volume and the cost of waste treatment and disposal (DOE M 435.1-1).

2.6.2 Radiological Release of Waste

Generators shall attempt to obtain radiological release of dangerous waste and TSCA PCB waste generated from radioactive material areas in accordance with their site/facility radiological release criteria, unless one or more of the following conditions apply (for Hanford Site Project Hanford Management Contract [PHMC] generators, the Site release criteria are discussed in HNF-PRO-20377 and HNF-13536).

- Radiological surface contamination exceeds the values established in HNF-5173, Table 4-1. Materials/equipment with potential radioactivity in volume above background from DOE operations cannot be released unless DOE has approved an authorized limit or the conditions of HNF-PRO-20377 for TSCA/RCRA waste are satisfied.
- Process knowledge clearly identifies that radiological contamination was introduced into the waste.
- The analytical limit of detection for the waste matrix is above the Site/facility radiological release limits (for Hanford Site PHMC generators, HNF-PRO-20377 and HNF-13536).
- The waste is treated and directly disposed as radioactive waste at a cost that is lower than the cost of radiological release and disposal as nonradioactive waste.
- The basis for use of these conditions must be documented as part of the radiological characterization record(s) for the waste.

2.6.3 Segregation for Treatment, Storage, and/or Disposal

All waste shall be segregated by the WSRds and waste stream profiles to facilitate proper TSD. The WSRds identify major waste streams, grouped in a manner that defines currently available storage and disposal methods and, for waste requiring treatment, the anticipated treatment and/or disposal methods. When it is not technically feasible or it is cost prohibitive to segregate a given waste stream by WSRd and profile, the generator must document the basis for not segregating the waste. Acceptance of non-segregated waste is contingent on either (1) the WFMP acceptance organization identifying a treatment/disposal pathway or (2) approval by the RL to receive the waste stream for storage.

WSRds will include certain waste stream-specific requirements to facilitate TSD. These criteria must be met in addition to the criteria identified in this document.

The current set of WSRds, along with instructions for selecting the appropriate WSRd, can be obtained from the *Hanford Site Solid Waste Acceptance Program* Internet Web site (<http://www.hanford.gov/?page=581>).

2.6.4 Waste Streams Having No Established Treatment/Disposal Path

Every effort shall be made to avoid the generation of waste for which no treatment/disposal path has been identified.

Written RL approval is required for acceptance of any waste stream that has no established treatment/disposal path.

2.6.5 Low-Level Mixed Waste from Non-PRC Generators

MLLW from PRC and non-PRC generators that requires treatment to meet LDR requirements shall be treated as required to meet LDR treatment standards prior to delivery to PRC disposal units. Non-LDR-compliant MLLW presented for storage will be considered on a case-by-case basis when no treatment

path is available or for treatment and disposal when treatment at the disposal facility is proposed. See Section 1.6 for exception to non-LDR-compliant waste.

2.7 Management and Certification of Transuranic Waste

TRU waste has a unique set of management and certification requirements based on DOE/WIPP-02-3122 and DOE/WIPP-02-3214. The Hanford Site meets these requirements through implementation of HNF-2600 and HNF-2599. Requirements applicable to generators of contact- and remote-handled TRU waste are identified in Appendices G and I, respectively. If TRU waste does not meet the requirements of Appendices G and I, an exception to HNF-EP-0063 would be required in order for the waste to be accepted at a SWOC facility. For TRU waste that meets general SWOC requirements, but not Appendices G and I, DOE-RL will be contacted for consultation of the exception.

2.8 Records

The generator must retain all record copy material used for waste characterization and designation in accordance with Federal and State requirements and DOE Orders. These records include process knowledge, sampling information, analytical data, inventory records, and related information. The generator must transfer copies of certain records as requested by the WFMP acceptance organization through the waste acceptance process described on the *Hanford Site Solid Waste Acceptance Program* Internet Web site (<http://www.hanford.gov/?page=586>).

2.9 Classified and Accountable Nuclear Material

Radioactive waste to which access has been limited for national security reasons and that cannot be declassified shall be managed in accordance with the requirements of DOE M 470.4-2 and DOE O 470.4A (DOE M 435.1-1).

During the acceptance process, the generator shall notify the WFMP acceptance organization of any classified waste. Classified waste is managed on a case-by-case basis.

A DOE/NRC 741 form must be completed for waste that contains accountable nuclear material (DOE O 470.4A).

2.10 Waste Verification

A portion of the waste containers sent to Hanford Site TSD units must be verified by physical inspection (nondestructive examination, visual examination) or chemical screening as stated in the waste analysis plans for the TSD units (i.e., HNF-1886; HNF-5841; HNF-2165; or HNF-9921). For most waste types, this verification will be performed at the generator's location by physical inspection before or during packaging. In cases where the verification cannot be performed at the generator's location, the generators must notify the Hanford Site Technical Services organization prior to packaging the waste. The Performance Evaluation System Committee will evaluate the individual cases and determine if verification for the waste will be performed at one of the Hanford Site TSD units.

2.11 Physical and Chemical Criteria

The following are the physical and chemical criteria for acceptance of all waste.

2.11.1 Chemical Compatibility

All waste placed in a given outer container shall be chemically compatible (WAC 173-303-630).

2.11.2 Asbestos-Containing Waste

Asbestos-containing waste material shall be packaged in accordance with 40 CFR 61.150. Wetting with water is allowed as long as the liquid does not exceed applicable free liquid requirements (Section 3.3.1).

2.11.3 Heat Generation

If heat generation from radiological decay in the waste package exceeds 3.5 watts/m³ (0.1 watt/ft³), the package must be evaluated to ensure the heat does not affect the integrity of the container or surrounding containers in storage. This evaluation must be provided to and approved by the WFMP acceptance organization.

2.11.4 Gas Generation

Generators shall provide evidence of compliance with DOE M 435.1-1. When vents are required by this section, a certificate of conformance shall be provided, stating the vent model number that has been installed on the waste container and that the waste packaging meets the requirements of this section.

When LLW is packaged, vents or other measures shall be provided if the potential exists for pressurizing or generating flammable or explosive concentrations of gases within the waste container (DOE M 435.1-1, Chapter IV, L.1.b). Unless otherwise specified by the WFMP acceptance organization, a minimum 5-year time value shall be used to demonstrate compliance when performing gas generation calculations for LLW going directly to disposal.

When a container of newly generated TRU waste is packaged, vents or other mechanisms shall be provided at the time the waste is packaged to prevent pressurization of the container or generation of flammable or explosive concentrations of gases. Containers of currently stored waste shall meet this requirement as soon as practical unless analyses demonstrate that the waste can otherwise be managed safely (DOE M 435.1-1, Chapter III, L.1.b).

If required, the following mitigating measures (or alternative measures approved by the WFMP acceptance organization) must be used.

- Control of hydrogen from radiolytic decomposition: Use an approved vent, as listed in Appendix H, or an approved alternative. All container liners and inner bags must be closed in a manner that allows gas to reach the vent filter (e.g., twist and tape method for bags). When 90-mil liners are used, the hole size used to vent the liner shall be documented. In addition to filtering, palladium or platinum catalyst packs may be used to control hydrogen concentrations in the container.
- Control of hydrogen from biological decomposition: Waste containing readily biodegradable organic materials (e.g., animal waste, vegetation) must be vented with an approved vent, as listed in Appendix H, or an approved alternative. In addition, slaked lime shall be added to the waste to reduce biological decomposition if filtering alone is not sufficient to control combustible gas generations.

2.12 Radiological Criteria

The following are the radiological criteria for acceptance of waste.

2.12.1 Criticality Safety Limits

The fissile and fissionable material content limits are provided in Appendix B.

2.12.2 Dose Equivalent Curie Limits

Waste must meet the safety basis limit of 82.5 dose-equivalent curies per container. Radionuclide quantities greater than 82.5 dose-equivalent curies per container may be accepted based on specific

container and waste forms but must be evaluated to ensure compliance with safety basis criteria (HNF-15280).

Un-vented drums equal to or greater than 33 dose-equivalent curies without overpack are prohibited (HNF-15280).

Additionally, each facility has inventory limits as described in HNF-15280. Waste receipts are controlled by each facility to maintain the inventory within these limits.

2.12.3 Package Removable Contamination Limits

Removable contamination on accessible surfaces of waste packages shall not exceed the limits of HNF-5173, Table 2-2. Use of fixatives is not allowed to meet the criteria. For returnable overpacks, the contamination limits and fixative prohibition also applies to the outside of the inner package.

In addition, elevated concentrations of tritium may accumulate when tritium diffuses as tritiated water (HTO) vapor from containers and concentrate in the cargo area. Shipments that are greater than 100 Ci of tritium should be shipped in open conveyances.

2.13 Packaging Criteria

The following are the packaging criteria for acceptance of waste.

2.13.1 Container Selection

The packages for waste shall meet applicable 49 CFR container requirements for the hazard class/division of the waste, except packaging for onsite transfers under an approved package-specific safety document might be allowed where cost or technical constraints make the use of a DOT-compliant package unfeasible. If the waste does not meet the definition of any DOT hazard class, a container meeting the general requirements of 49 CFR 173.410 is adequate.

2.13.2 Condition of Containers

Outer containers shall be in good condition, with no visible cracks, holes, dents, bulges, pit or scale corrosion, or other damage that could compromise container integrity (WAC 173-303-630). Minor external surface rust that can be sanded or brushed off will be acceptable. Containers having some pit or scale corrosion could be acceptable for storage, provided the integrity of the container is confirmed. Polyurea-coated containers must have a Flame Spread rating of 25 or less for acceptance into CWC.

2.13.3 Securing Waste and Shielding

For newly generated waste, drums on pallets shall be strapped together prior to loading on the shipping transport vehicle. Large, heavy items must be secured in containers by bracing, blocking, or other means to prevent damage to the container during handling and transportation. When shielding is used to reduce the surface dose rate of a waste container, the shielding and waste must be secured to prevent shifting during handling and transportation. Externally attached shielding is prohibited.

2.13.4 Labeling

Packages shall be labeled according to the instructions in Appendix C.

3 Acceptance Criteria for Disposal in the Low-Level Burial Grounds

This chapter outlines the criteria necessary in order to comply with the regulatory, permitting, safety, environmental, and operational requirements for the LLW and MLLW TSD in the LLBG.

3.1 Facility Description and Function

Trenches 31 and 34 of the 218-W-5 Burial Ground are RCRA-compliant units for TSD of certain MLLW. Currently, only LLW and MLLW originally designated with RCRA characteristic numbers D001 through D043, certain listed, discarded chemical product waste numbers (U- and P-listed waste), certain F-listed waste F001 through F012, F019, F028, and F039 (derived from F001 through F012, F019, and F028), and Washington state-only dangerous waste (except waste number WSC2-acid) are accepted in Trenches 31 and 34 (Table 3-1). Waste accepted for disposal at Trenches 31 and 34 must be disposal ready and meet the LDR treatment standards of 40 CFR 268, WAC-173-140, radiological stabilization, 90 percent full requirements and meeting the 50 psi compaction criteria for the disposal trenches. There also are safety-based limits on the radionuclide concentrations of waste received. The unit may also dispose of certain types of TSCA PCB waste.

3.2 Prohibited Waste

The following types of waste are not disposed in Trenches 31 and 34.

- Waste designated with WSC2-acid (Hanford Facility RCRA Permit, WA7 89000 8967, Unit Name Part A Form).
- TSCA-regulated PCB waste, except as specifically authorized by 40 CFR 761.
- Waste that does not comply with the requirement of DOE M 435.1-1, Chapter IV, G.1.d.1. LLW must contribute to and not detract from achieving long-term stability of the facility, minimizing the need for long-term active maintenance, minimizing subsidence, and minimizing contact of water with waste. Void spaces within the waste and, if containers are used, between the waste and its container shall be reduced to the extent practical (DOE M 435.1-1, Chapter IV, G.1.d.1).
- Waste that does not comply with the requirement of DOE M 435.1-1, Chapter IV, G.1.d.2. Liquid LLW or LLW containing free liquid must be converted into a form that contains as little freestanding liquid as is reasonably achievable, but in no case shall the liquid exceed 1 percent of the waste volume when the LLW is in a disposal container, or 0.5 percent of the waste volume after it is processed to a stable form (DOE M 435.1-1, Chapter IV, G.1.d.2).
- Waste that does not comply with the requirement of DOE M 435.1-1, Chapter IV, G.1.d.3. LLW must not be readily capable of detonation or of explosive decomposition or reaction at anticipated pressures and temperatures, or of explosive reaction with water. Pyrophoric materials contained in waste shall be treated, prepared, and packaged to be nonflammable (DOE M 435.1-1).
- Waste that does not comply with the requirement of DOE M 435.1-1, Chapter IV, G.1.d.4. LLW must not contain, or be capable of generating by radiolysis or biodegradation, quantities of toxic gases, vapors, or fumes harmful to the public or workers or disposal facility personnel, or harmful to the long-term structural stability of the disposal site (DOE M 435.1-1). Additional requirements related to these criteria are listed in Section 2.11.4.
- Waste that does not comply with the requirement of DOE M 435.1-1, Chapter IV, G.1.d.5. LLW in a gaseous form must be packaged such that the pressure does not exceed 1.5 atmospheres absolute at

20° C (68° F) (DOE M 435.1-1). Additional requirements related to these criteria are listed in Section 2.11.4.

- Waste that does not meet all applicable treatment standards of 40 CFR 268 and WAC 173-303-140.
- TRU waste and waste that exceeds other radiological limits of Section 3.4.
- Waste that is incompatible with the trench liner, as defined in Section 3.3.3 (40 CFR 264.301; WAC 173-303-665; HNF-5841).

Table 3-1. LLBG Dangerous Waste Numbers

Characteristic Waste "D" Series	Nonspecific Source "F" Series	Discarded Chemical Product "U" Series	Discarded Chemical Product "P" Series	Washington State-Only "W" Series
D001-D043	F001	U001-U012	P001-P006	WT01
	F002	U014-U039	P008-P018	WT02
	F003	U041-U053	P020-P024	WP01
	F004	U055-U064	P026-P031	WP02
	F005	U066-U099	P033	WP03
	F006	U101-U103	P034	WSC2*
	F007	U105-U138	P036-P051	WPCB
	F008	U140-U174	P054	
	F009	U176-U194	P056-P060	
	F010	U196	P062-P078	
	F011	U197	P081	
	F012	U200-U211	P082	
	F019	U213-U223	P084	
	F028	U225-U228	P085	
	F039	U231-U240	P087-P089	
		U243-U244	P092-P099	
		U246-U249	P101-P106	
		U271	P108-P116	
		U278-U280	P118-P123	
		U328	P127	
		U353	P128	
		U359	P185	
		U364	P188-P192	
		U367	P194	
		U372	P196-P199	
		U373	P201-P205	
		U375		
		U387		
		U389		
		U394		
		U395		

U401–U404

U407

U409–U411

*See Section 3.2.

*Acceptable dangerous waste numbers may be added or deleted at any time due to changes in regulations. See the currently approved Dangerous Waste Permit Application, Part A Form, Section XIV, "Description of Dangerous Waste," to verify the dangerous waste numbers acceptable at the LLBG.

3.3 Physical and Chemical Criteria

The following are the physical and chemical criteria for acceptance of waste in the LLBG.

3.3.1 Liquids and Liquid-Containing Waste

All free liquids must be absorbed or stabilized in accordance with Appendix E, or otherwise removed from the waste, except when specifically allowed as follows.

- Containerized free liquids are allowed in the following situations, but cannot exceed 1 percent of the volume of the waste (40 CFR 264.314; HNF-5841).
 - Free liquids in a very small container, such as an ampule.
 - Small articles that contain free liquids required for the article to function (e.g., batteries or capacitors).
- For liquid-containing waste where condensate could form in inner plastic packaging (e.g., bags) subsequent to packaging, the condensate shall be eliminated to the maximum extent practical by placing sorbents within the inner plastic packaging (HNF-5841). The type and amount of sorbent required shall be in accordance with Appendix E. In any case, the amount of liquid may not exceed 1 percent of the volume of the waste or 0.5 percent of waste processed to a stable form (DOE M 435.1-1).
- Residual liquids in large debris items shall be sorbed or removed. In cases where it is not practical to remove suspected liquids and it is impossible to sample to determine if liquids are present, the liquids shall be removed to the maximum extent possible by draining suspected liquids at low points and placing an adequate amount of sorbent around each item (HNF-5841). In any case, the amount of liquid cannot exceed 1 percent of the volume of the waste (DOE M 435.1-1).

3.3.2 Land Disposal Restrictions.

All waste subject to RCRA LDR (40 CFR 268) and/or the Washington State LDR (WAC 173-303-140) must be demonstrated to meet all applicable treatment standards and requirements. For waste that has concentration-based treatment standards for specific hazardous constituents under 40 CFR 268, the waste must be tested at a Hanford Site laboratory or another independent laboratory in accordance with 40 CFR 268. For waste that has treatment standards that are not concentration-based, the generator and/or treatment facility must demonstrate the waste meets the applicable treatment standards using process knowledge and/or by waste analysis, as required by the applicable sections of 40 CFR 268 and WAC 173-303-140 (HNF-5841).

3.3.3 Compatibility of Waste with Liner

All waste disposed in the LLBG must be compatible with the landfill liner system (HNF-5841). A variety of chemical constituents have been evaluated for compatibility with the liner system, and it is believed that waste that meets LDR requirements and the other acceptance criteria of this chapter will be compatible (HNF-5841; WHC-SD-WM-TI-714). An assessment will be performed by the WFMP acceptance organization on each waste stream to confirm the compatibility of the waste with the liner. In cases where a waste contains constituents that have not been evaluated previously for liner compatibility, testing by Method 9090 of SW-846 could be required.

NOTE: Table 3-2 lists certain chemical constituents, in concentrated form, that have been evaluated and determined to be incompatible with the liner.

Table 3-2. Chemical Constituents Known to be Incompatible with Liner System

Chemical Constituent	Chemical Abstract Service Number(s)
Aqua regia	8007-56-5
Bromic acid	7789-31-3
Bromine (elemental)	7726-95-6
Bromobenzene	108-86-1
Bromoform	75-25-2
Calcium bisulfite	13780-03-5
Calcium sulfide	20548-54-3
Chlorine (elemental)	7782-50-5
1-Chloropentane (amyl chloride)	543-59-9
1,1-Dichloroethylene (vinylidene chloride)	75-35-4
1,2-Dichloropropane (propylene dichloride)	78-87-5
Diethyl benzene	105-05-5, 135-01-3, 141-93-5
Diethyl ether	60-29-7
Chloroethane (ethyl chloride)	75-00-3
Fluorine (elemental)	7782-41-4
Nitrobenzene	98-95-3
Sulfur trioxide	7446-11-9
Sulfuric acid, fuming	8014-95-7
Tetrachloroethylene	127-18-4
Thionyl chloride	7719-09-7
Trichloroethylene	79-01-6, 52037-46-4

Source: WHC-SD-WM-TI-714, 1995, *High-Density Polyethylene Liner Chemical Compatibility for Radioactive Mixed Waste Trenches*, Rev. 0, Westinghouse Hanford Company, Richland, Washington.

3.3.4 Gas Generation

Radioactive animal carcasses must be packaged as follows.

- The waste must be packaged in an inner and outer metal package, where the outer package has a capacity at least 40 percent greater than that of the inner package. The outer package must be a metal container that meets applicable transportation requirements for shipment to the LLBG.
- The inner package shall be lined with a minimum 4-mil plastic liner. The animal carcass(es) in the inner package must be surrounded with slaked lime. The plastic liner and inner package must be sealed.
- A minimum of 7.6 cm (3 in.) of mineral sorbent must be placed in the bottom of the outer package. The inner package must be placed into the outer package, and the void space filled between the two packages with additional mineral sorbent.
- The outer package must be sealed.

3.4 Radiological Criteria

The following are the radiological criteria for acceptance of waste in the LLBG.

3.4.1 Radiological Concentration Limits

The methodology for classification of the radionuclide content of waste according to the various limits listed in the following sections is provided in Appendix A. A waste must meet all of the following conditions to be disposed in the LLBG.

- TRU content limit. TRU content (as calculated by Method A1.1 of Appendix A) shall not exceed 100 nanocuries (3,700 becquerels) per gram of waste (DOE M 435.1-1).
- Waste category (as calculated by Methods A1.4 and A1.5 of Appendix A) shall not exceed Category 3, except with an analysis coordinated by the WFMP acceptance organization demonstrating that the LLBG performance assessment conditions are met (WHC-EP-0645; WHC-SD-WM-TI-730).
- Category 3 waste (as calculated by Methods A1.4 and A1.5 of Appendix A) can be disposed of only if the waste meets one of the following waste form stability criteria (WHC-EP-0645; WHC-SD-WM-TI-730).
 - Packaging in a HIC that is procured through WHC-S-0486 specification.
 - Packaging in a HIC approved by the WFMP acceptance organization.
 - NOTE: A list of approved HICs is available on the *Hanford Site Solid Waste Acceptance Program* Internet Web site (<http://www.hanford.gov/?page=581>).
 - Placement in monoliths in the LLBG using the exception process in Section 1.6.
 - Stabilization in concrete or other stabilization agents. The stabilized waste must meet the leach index and compression strength criteria of the U.S. Nuclear Regulatory Commission (NRC) *Technical Position Paper on Waste Form*, Section C.2 and Appendix A (NRC, 1991). Several Hanford-approved concrete mix formulas have been developed that can be used to meet the stabilization criteria. Contact the WFMP acceptance organization for information on use of these formulas.

- Inherently stable waste that meets the stability requirements of 10 CFR 61.56 and the NRC *Technical Position Paper on Waste Form* (NRC, 1991).
- Mobile radionuclides. If the concentration of any mobile radionuclide exceeds the Mobile Radionuclide Reporting Limit of Appendix A, Table A-2, stabilization could be required (WHC-EP-0645; WHC-SD-WM-TI-730). The WFMP acceptance organization will perform a case-by-case evaluation based on the LLBG performance assessment (WHC-EP-0645; WHC-SD-WM-TI-730) to determine whether the waste requires stabilization to meet the groundwater pathway dose criteria. Stabilization normally would consist of placing the waste container in a HIC, but additional stabilization might be required based on a number of factors such as waste form and radionuclide content. The WFMP acceptance organization will coordinate this evaluation.

3.4.2 Criticality Safety Limits

The fissile and fissionable material limits are provided in Appendix B. Note that fissile waste packages can be accepted only with an approved criticality safety evaluation.

3.4.3 Package Dose Rate Limits

Containers with dose rates less than or equal to 2 milliSieverts/ hour (200 millirem/ hour) at contact and less than 1 milliSievert/ hour (100 millirem/ hour) at 30 cm (11.8 in.) are acceptable at the LLBG. Contact-handled containers (see definitions) exceeding these limits require container-specific review and approval.

Remote-handled waste is acceptable at the LLBG if approved through both a waste stream profile sheet and a container-specific shipment. Remote-handled waste shall meet the applicable dose rate restrictions of DOT or an approved package-specific safety document. Remote-handled waste shall be configured for unloading such that personnel exposures are maintained as low as reasonably achievable (ALARA).

3.5 Packaging Criteria

The following are packaging criteria for acceptance in the LLBG.

3.5.1 Package Construction

Containers must meet one of the following criteria to ensure compliance with HNF-21239, *Solid Waste Operations Complex Fire Hazard Analysis*.

- Constructed of metal, concrete, or masonry.
- Constructed of wood that is either (1) pretreated wood having the Underwriters Laboratories FR-S stamp, or (2) painted with a fire-retardant paint that has been approved by Underwriters Laboratories or Factory Mutual.
- Constructed of rigid plastic that has a maximum flame spread rating of 25 when tested by a nationally recognized testing laboratory to American Society for Testing of Materials (ASTM) Standard Test Method for Surface Burning Characteristics of Building Materials (ASTM E-84, most current version). These containers will only be accepted if approved by WFMP Fire Protection Engineering.
- Constructed of flexible plastic packaging provided the waste matrix is limited to soils, metals, concrete, or masonry. Incidental amounts of organic material such as personal protective equipment (PPE) are allowed in flexible packaging.

- Other containers as authorized under the LLBG Fire Hazards Analysis and approved by WFMP Fire Protection Engineering.
- Sacrificial rigging shall not contain regulated materials, such as lead.

Containers shall be compatible with the waste and maintain containment during handling and storage before disposal. Where required, an appropriate combination of protective coatings and liners shall be used to prevent loss of container integrity.

3.5.2 Handling of Packages

All packages must be configured for safe unloading by forklift or crane. Alternate means of unloading could be allowed with approval from the TSD unit manager or designee. Packages that must be unloaded by crane shall be equipped with a lifting system designed to safely lift the fully loaded package. All slings and lifting devices shall meet the requirements of the most current version of DOE/RL-92-36. For packages that have special unloading requirements, information must be provided to the WFMP acceptance organization concerning the methods for unloading before the shipment is scheduled. Sacrificial rigging shall be provided for remote-handled waste packages. Rigging shall not contain regulated materials, such as lead.

3.5.3 Minimization of Subsidence

All waste shall be packaged in a form that minimizes settling and subsidence to the maximum extent feasible (DOE M 435.1-1; WHC-EP-0645; and WHC-SD-WM-TI-730). All waste accepted for disposal in the LLBG must meet one of the following minimization of subsidence criteria at the time of disposal:

- Packaged in a HIC that is procured through the WHC-S-0486 specification
- Packaged in a HIC approved by the CHPRC WFMP
- Compactable waste that has been compacted to a minimum pressure of 3.52 kg/cm² (50 lb/in.²)
- Placed in a Hanford-provided in-trench structural monolith meeting the requirements of HNF-1981 specification for concrete encasements using the exception process in Section 1.6
- A solid with a minimum “confined” compressive strength of 3.52 kg/cm² (50 lb/in.²).
- All containerized waste must be at least 90 percent full when placed in the disposal unit (WAC 173-303-665).

3.5.4 Labeling

Bulk waste and remote-handled waste containers that are removed from reusable overpacks are exempt from labeling requirements at the LLBG. For unusual waste forms, special labeling provisions can be arranged with the WFMP acceptance organization.

3.5.5 Bulk (Noncontainerized) Waste

Bulk waste can be disposed in the LLBG, on a case-by-case basis. Waste shall meet the following requirements to be considered.

- Certain types of waste can be disposed in bulk rather than packaging in containers. This includes soil, vegetation, building rubble, and other homogeneous waste having relatively low concentrations of radionuclides and hazardous chemical constituents. To avoid unnecessary conservatism, universally applicable limits have not been developed for the LLBG acceptance criteria. Instead, a case-by-case evaluation will be performed on request to determine whether a

given waste stream can be disposed in bulk. Any mitigating measures required to meet the conditions of the safety basis will also be determined on a case-by-case basis.

- Waste types that are not surface contaminated with readily dispersible radiological or hazardous chemical contamination, such as activated metal or internally contaminated equipment may be considered containerized. As such, they are subject to the radionuclide and chemical concentration requirements for containerized waste rather than the bulk waste requirements.

4 Acceptance Criteria for the Central Waste Complex

This chapter outlines the criteria necessary in order to comply with the regulatory, permitting, safety, environmental, and operational requirements at the CWC.

4.1 Facility Description and Function

The CWC is a storage and treatment unit for MLLW; TRU, TRUM, TSCA PCB waste; and other waste types requiring treatment before disposal. Waste stored at the CWC will be treated and repackaged as required for disposal as treatment capabilities become available.

The CWC manages waste having characteristic waste numbers D001 through D043, certain listed, discarded chemical product waste numbers (U- and P-listed waste), certain F-listed waste (F001 through F012, F019 through F023, F026 through F028, and F039), and all Washington State-only waste numbers. Table 4-1 lists the acceptable dangerous waste numbers from the approved CWC Part A, Form 3 (Hanford Facility RCRA Permit, WA7 89000 8967, Unit Name Part A Form). In addition, the CWC manages TSCA PCB waste from Hanford Site generators in accordance with 40 CFR 761. The CWC also can store waste from CERCLA cleanup activities.

4.2 Prohibited Waste

The following wastes are not accepted for storage at the CWC.

- Liquid waste, except if packaged in lab packs or overpacks in quantities less than or equal to 57 L (15 gal) per outer container.
- Compressed gases packaged at pressures in excess of 1.5 atmospheres (152 kilopascals absolute pressure) at 20° C (68° F), except that pressurized aerosol cans can be accepted (DOE M 435.1-1). Additional requirements related to these criteria are listed in Section 2.11.4.
- See Section 2.3.

4.3 Physical and Chemical Criteria

The following are the physical and chemical criteria for acceptance of waste at the CWC.

4.3.1 Liquids and Liquid-Containing Waste

Sorption of liquids is allowed, but must be compatible with the treatment methods anticipated for disposal. Liquids must be sorbed or stabilized in accordance with Appendix E.

For waste that could form condensate during storage, sufficient sorbent shall be added to the container to sorb any condensate formed.

4.4 Radiological Criteria

The following are the radiological criteria specific to the CWC

4.4.1 Package Dose Rate Limits

Waste packages shall not exceed 1 milliSievert/ hour (100 millirem/ hour) at 30 cm (1 ft) from the waste package and 2 milliSieverts/ hour (200 millirem/ hour) at any point on the surface of the package. Containers exceeding these limits may be acceptable but will require container-specific review and approval by CWC Operations.

Table 4-1. CWC Dangerous Waste Numbers

Characteristic Waste "D" Series	Nonspecific Source "F" Series	Discarded Chemical Product "U" Series	Discarded Chemical Product "P" Series	Washington State-Only "W" Series	
D001-D043	F001	U001-U012	P001-P006	WT01	
	F002	U014-U039	P008-P018	WT02	
	F003	U041-U053	P020-P024	WP01	
	F004	U055-U064	P026-P031	WP02	
	F005	U066-U099	P033	WP03	
	F006	U101-U103	P034	WSC2	
	F007	U105-U138	P036-P051	WPCB	
	F008	U140-U174	P054		
	F009	U176-U194	P056-P060		
	F010	U196	P062-P078		
	F011	U197	P081		
	F012	U200-U211	P082		
	F019	U213-U223	P084		
	F020	U225-U228	P085		
	F021	U231-U240	P087-P089		
	F022	U243-U244	P092-P099		
	F023	U246-U249	P101-P106		
	F026	U271	P108-P116		
	F027	U278-U280	P118-P123		
	F028	U328	P127		
	F039	U353	P128		
			U359	P185	
			U364	P188-P192	
			U367	P194	
			U370	P196-P199	
			U372	P201-P205	
			U373		
			U376		
			U387		
			U389		
		U394			
		U395			
		U401-U404			
		U407			
		U409-U411			

*Acceptable dangerous waste numbers may be added or deleted at any time due to changes in regulations. See the currently approved Dangerous Waste Permit Application, Part A Form, Section XIV, "Description of Dangerous Waste," to verify the dangerous waste numbers acceptable at the CWC.

4.5 Packaging Criteria

The following are the packaging criteria for acceptance at the CWC.

4.5.1 Container Selection

Outer containers shall be constructed of noncombustible materials. Wood, fiberboard, and plastic outer containers are prohibited (HNF-15280). See Section 1.6 for exception if the outer container is combustible.

4.5.2 Protective Coatings and Liners

The packaging for stored waste shall include coatings and/or liners sufficient to maintain the integrity of the containment system during the anticipated storage life of the waste, as follows.

- The exterior coating of containers shall be alkyd enamel, galvanized, or an alternative coating with performance equivalent to or better than alkyd enamel.
- The interior coatings and liners shall be chemically compatible with the waste and protect the containment system from corrosion over the anticipated storage life of the waste (WAC 173-303-630). Unless otherwise specified by the WFMP acceptance organization, the storage life should be assumed to be 20 years. For containers procured under Hanford Site container procurement specifications, Appendix D defines preferred coating and liner options.

4.5.3 Packaging of Liquid Waste in Labpacks

The following are requirements for packaging of liquid waste as lab packs and overpacked liquids.

- Up to 57 L (15 gal) of liquid can be packaged in inner glass, metal, or plastic containers. Glass containers shall not exceed 4-L (1.1-gal) capacity each. Sufficient head space must be left in the inner containers to prevent breakage because of expansion in temperatures up to 55° C (131° F) and freezing conditions.
- Inner containers shall be securely closed. The lids of glass containers shall be sealed with Teflon¹ or equivalent lid seals (gaskets). After closure, glass lids shall be taped.
- All inner containers shall be compatible with the waste contents over the anticipated storage life of the waste.
- Each inner container shall be labeled with its contents.
- A sufficient quantity of suggested sorbent (selected in accordance with Appendix E) shall be packaged around the inner containers to sorb twice the volume of the liquid in the inner containers. The sorbent shall be placed around the inner containers in a manner that prevents shifting and breakage.

4.5.4 Package Size and Weight Limits

The following are the baseline size limits for the CWC storage modules (Table 4-2). Larger containers could be accepted into specific storage modules with special loading procedures. Drums smaller than 208 L (55 gal) are not accepted on a routine basis, but could be approved on a case-by-case evaluation.

¹Teflon is a registered trademark of E. I. DuPont de Nemours & Company, Wilmington, Delaware.

4.5.5 Stacking

Packages must be designed to withstand the weight of two layers of 208 -L (55-gal) drums weighing 454 kg (1,000 lb) each stacked on top.

4.5.6 Waste Pallets

Waste shall be stored on metal or wood pallets. However, wood pallets must meet the requirements of HNF-FMP-07-32540-RO. For the specific requirements, refer to the *Hanford Site Solid Waste Acceptance Program* Internet Web site (<http://www.hanford.gov/?page=581>).

Table 4-2. Central Waste Complex Container Size and Floor Loading Limits

Storage Units	Package Size Limit	Floor Loading Limit
Alkali metal modules	321-L (85-gal) drum	1,225 kg/m ² (250 lb/ft ²)
Low-flash point modules	321-L (85-gal) drum	1,225 kg/m ² (250 lb/ft ²)
2401-W Building	3.0 m high by 3.4 m wide (10 ft high by 11 ft wide)	2,200 kg/m ² (450 lb/ft ²)
2402-W Building	3.0 m high by 3.4 m wide (10 ft high by 11 ft wide)	3,430 kg/m ² (700 lb/ft ²)
2402-WB through WL Buildings, 2403-W and 2404- W Facilities	3.0 m high by 3.4 m wide (10 ft high by 11 ft wide)	9,800 kg/m ² (2,000 lb/ft ²)

5 Acceptance Criteria for the T Plant Complex

This chapter outlines the criteria necessary in order to comply with the regulatory, permitting, safety, environmental, and operational requirements at the T Plant Complex.

5.1 Facility Description and Function

The T Plant Complex is a treatment and storage unit having a number of functions, including equipment decontamination, waste treatment, storage, sampling, NDE, and repackaging. The 221-T Building is prepared for the storage of K Basin sand from the sand filter. In addition, this building can be used for decontamination, treatment, and storage of equipment and waste. The 2706-T Building is used for the decontamination, treatment, storage, etc., of equipment and waste having relatively low levels of radiological contamination. The 214-T Building is for storage purposes.

Wastes that can be managed at the T Plant Complex include LLW, and TRU, TRUM, hazardous/dangerous low-level mixed, and TSCA PCB (40 CFR 761) waste. Table 5-1 lists the acceptable dangerous waste numbers from the approved T Plant Complex; Part A, Form 3 (Hanford Facility RCRA Permit, WA7 89000 8967, Unit Name Part A Form).

Waste managed at the T Plant Complex could be sent to other Hanford Site TSD units for TSD. The acceptance criteria for these units must be met subsequent to processing at the T Plant Complex.

5.2 Prohibited Waste

The following waste types are not accepted at the T Plant Complex:

- Compressed gases packaged at pressures in excess of 1.5 atmospheres (152 kilopascals absolute pressure) at 20° C (68° F), except that pressurized aerosol cans can be accepted (DOE M 435.1-1). Additional requirements related to these criteria are listed in Section 2.11.4.
- See Section 2.3.

5.3 Radiological Criteria

The following are the radiological acceptance criteria specific to the T Plant Complex.

5.3.1 Package External Dose Rate Limits

Waste packages that exceed 1 milliSievert/ hour (100 millirem/ hour) at 30 cm (1 ft) from the waste package or 2 milliSieverts/ hour (200 millirem/ hour) at any point on the surface of the package, require case-by-case evaluation for acceptance. When these dose rates are exceeded, the generator must provide detailed radiological survey data.

5.3.2 Internal Dose Rate and Contamination Limits for Decontamination and Processing

The contact dose rate for equipment and waste to be decontaminated or processed will be determined on a case-by-case basis during acceptance review. When internal contact dose rates exceed 1 milliSievert/ hour (100 millirem/ hour), the generator must provide detailed radiological survey information.

In addition, items with detectable alpha contamination may not be acceptable for decontamination or processing at the 2706-T Building. If the waste contains detectable alpha contamination, the generator must provide detailed radiological survey information to determine whether the waste can be processed.

Table 5-1. T Plant Complex Dangerous Waste Numbers

Characteristic Waste "D" Series	Nonspecific Source "F" Series	Discarded Chemical Product "U" Series	Discarded Chemical Product "P" Series	Washington State-Only "W" Series
D001-D043	F001-F012	U001-U012	P001-P006	WT01
	F019-F023	U014-U039	P008-P018	WT02
	F026-F028	U041-U053	P020-P024	WP01
	F039	U055-U064	P026-P031	WP02
		U066-U099	P033	WP03
		U101-U103	P034	WSC2
		U105-U138	P036-P051	WPCB
		U140-U174	P054	
		U176-U194	P056-P060	
		U196	P062-P078	
		U200-U211	P081	
		U213-U223	P082	
		U225-U228	P084	
		U231-U240	P085	
		U242	P087-	
		U244	P089	
		U246-U249	P092-P099	
		U271	P101-P106	
		U278-U280	P108-P116	
		U328	P118-P123	
	U353	P127		
	U359	P128		
	U364	P185		
	U367	P188-P192		
	U372	P194		
	U373	P196-P199		
	U387	P201-P205		
	U389			
	U394			
	U395			
	U401			
	U404			
	U409-U411			

*Acceptable dangerous waste numbers may be added or deleted at any time due to changes in regulations. See the currently approved Dangerous Waste Permit Application, Part A Form, Section XIV, "Description of Dangerous Waste," to verify the dangerous waste numbers acceptable at the T Plant Complex.

5.4 Packaging Criteria

The following are the packaging criteria for acceptance of waste at the T Plant Complex.

5.4.1 Container Selection

Outer containers shall be constructed of metal or concrete, except that fire-retardant wooden boxes can be used. Wooden boxes shall be constructed of wood that is either (1) pretreated wood having the Underwriters Laboratories FR-S stamp, or (2) painted with a fire-retardant paint that has been approved by Underwriters Laboratories or Factory Mutual. Poly HICs are prohibited at T Plant Complex.

5.4.2 Protective Coatings and Liners for Stored Waste

The packaging for waste to be stored shall include coatings and/or liners sufficient to maintain the integrity of the containment system during the anticipated storage life of the waste as follows.

- The exterior coating of containers shall be alkyd enamel, galvanized, or an alternative coating with performance equivalent to or better than alkyd enamel.
- The interior coatings and liners shall be chemically compatible with the waste and shall protect the containment system from corrosion over the anticipated storage life of the waste (WAC 173-303-630). Unless otherwise specified by the WFMP acceptance organization, the storage life should be assumed to be 20 years. For containers procured under Hanford Site container procurement specifications, Appendix D defines preferred coating and liner options.

5.4.3 Container Size Limits

Container size limits are as follows:

- 2706-T: 12.2 m (40 ft) long by 4.3 m (14 ft) high by 3.7 m (12 ft) wide
- 221-T: 6.7 m (22 ft) long by 4.0 m (13 ft) high by 5.5 m (18 ft) wide
- 214-T: 6.0 m (20 ft) long by 3.0 m (10 ft) high by 3 m (10 ft) wide.

These size limits may be exceeded on a case-by-case basis with approval from facility operations via a waste profile.

5.4.4 Container Weight Limits

General container weight limits are as follows. Heavier containers can be accepted on a case-by-case basis with T Plant Complex operations' approval.

Drums shall not exceed 454 kg (1,000 lb)

Boxes shall not exceed their rated weight capacity

Large equipment or packages shall not exceed the following limits:

- 2706-T: 5,400 kg (11,900 lb) (small vehicles); 9,100 kg (20,000 lb) per axle or 36,000 kg (80,000 lb) gross (heavy equipment). All limits can be exceeded on a case-by-case basis
- 221-T: 41,000 kg (90,000 lb)
- 214-T: 5,400 kg (11,900 lb) (small vehicles); 9,100 kg (20,000 lb) per axle or 36,000 kg (80,000 lb) gross (heavy equipment). All limits can be exceeded on a case-by-case basis.

This page intentionally left blank.

6 Acceptance Criteria for the Waste Receiving and Processing Facility

This chapter outlines the criteria necessary in order to comply with the regulatory, permitting, safety, environmental, and operational requirements at the WRAP.

The following acceptance criteria apply to newly generated waste sent to the WRAP. Newly generated TRU waste shall be managed in accordance with Section 2.7. Acceptance criteria for retrieved waste containers in the LLBG will be established through project-specific acceptance procedures.

6.1 Facility Description and Function

The WRAP is a treatment and storage unit. The WRAP receives waste containers for verification, sampling, NDA, NDE, treatment, and repackaging.

Wastes that can be managed at the WRAP include TRU waste, TRUM waste, LLW, MLLW, and TSCA PCB waste. Table 6-1 lists the acceptable dangerous waste numbers from the approved WRAP Part A, Form 3 (Hanford Facility RCRA Permit, WA7 89000 8967, Unit Name Part A Form).

Waste managed at the WRAP could be sent to other Hanford Site TSD units for TSD. The acceptance criteria for these TSD units must be met subsequent to reprocessing waste at the WRAP.

6.2 Prohibited Waste

The following waste types are not accepted at the WRAP:

- Compressed gases packaged at pressures in excess of 1.5 atmospheres (152 kilopascals absolute pressure) at 20° C (68° F), except pressurized aerosol cans can be accepted (DOE M 435.1-1). Additional requirements related to these criteria are listed in Section 2.11.4.
- Liquid waste, except if packaged in lab packs or overpacks in quantities less than or equal to 57 L (15 gal) per outer container.
- See Section 2.3.

6.3 Packaging Criteria

The following are the packaging criteria for acceptance at the WRAP.

6.3.1 Protective Coatings and Liners for Stored Waste

The packaging for mixed waste to be stored shall include coatings and/or liners sufficient to maintain the integrity of the containment system during the anticipated storage life of the waste.

- The exterior coating of metal containers shall be alkyd enamel, galvanized, or an alternative coating with performance equivalent to or better than alkyd enamel.
- The interior coatings and liners shall be chemically compatible with the waste and shall protect the containment system from corrosion over the anticipated storage life of the waste (WAC 173-303-630). Unless otherwise specified by the WFMP acceptance organization, the storage life should be assumed to be 20 years. For containers procured under Hanford Site container procurement specifications, Appendix D defines preferred coating and liner options.

Table 6-1. The WRAP Dangerous Waste Numbers

Characteristic Waste "D" Series	Nonspecific Source "F" Series	Discarded Chemical Product "U" Series	Discarded Chemical Product "P" Series	Washington State-Only "W" Series
D001-D043	F001-F012	U001-U012	P001-P006	WT01
	F019-F023	U014-U039	P008-P018	WT02
	F026-F028	U041-U053	P020-P024	WP01
	F039	U055-U064	P026-P031	WP02
		U066-U099	P033	WP03
		U101-U103	P034	WPCB
		U105-U138	P036-P051	WSC2
		U140-U174	P054	
		U176-U194	P056-P060	
		U196	P062-P078	
		U197	P081	
		U200-U211	P082	
		U213-U223	P084	
		U225-U228	P085	
		U231-U240	P087-P089	
		U243-U244	P092-P099	
		U246-U249	P101-P106	
		U271	P108-P116	
		U278-U280	P118-P123	
		U328	P127	
		U353	P128	
		U359	P185	
		U364	P188-P192	
	U367	P194		
	U372	P196-P199		
	U373	P201-P205		
	U376			
	U387			
	U389			
	U394			
	U395			
	U401-U404			
	U407			
	U409-U411			

*Acceptable dangerous waste numbers may be added or deleted at any time due to changes in regulations. See the currently approved Dangerous Waste Permit Application, Part A Form, Section XIV, "Description of Dangerous Waste," to verify the dangerous waste numbers acceptable at the WRAP.

WRAP = Waste Receiving and Processing (Facility).

6.3.2 Noncombustible Containers

Outer containers shall be constructed of metal, except that fire-retardant wooden boxes can be used for LLW only. Wooden boxes shall be constructed of wood that is either (1) pretreated wood having the Underwriters Laboratories FR-S stamp, or (2) painted with a fire-retardant paint that has been approved by Underwriters Laboratories or Factory Mutual. Additionally, wooden boxes must be overpacked in a metal box for NDA at the WRAP.

6.3.3 Package Size Limits

The container sizes that can be handled at WRAP are as follows. These dimensions are absolute dimensions including any attachments such as lifting bails, lid flanges, or pallets if they are necessary in order to handle the container.

6.3.3.1 NDE

- Drums and other cylindrical containers not exceeding 1.61 m (5 ft 3.5 in.) in diameter and 1.64 m (5 ft 4.75 in.) tall.
- Boxes less than the following dimensions.
- Must be less than 2.90 m (9 ft 6 in.) long; must be less than 1.61 m (5 ft 3.5 in.) wide at bottom; above 0.6 m (2 ft) from bottom must be less than 1.93 m (6 ft 4 in.) wide; and must be less than 1.64 m (5 ft 4.75 in.) high.

6.3.3.2 NDA

- Drums and other cylindrical containers not exceeding 1.39 m (54.7 in.) in diameter and 0.99 m (39 in.) tall
- Boxes not exceeding 1.83 m (72 in.) long by 1.39 m (54.7 in.) wide and 0.99 m (39 in.) tall.

6.3.4 Package Weight Limits

The maximum weights for containers handled at WRAP are as follows.

- NDE: 3,175 kg (7,000 lb)
- NDA: 1,814.3 kg (4,000 lb).

6.3.5 Labeling

Packages shall be labeled as described in Appendix C.

6.4 Package Dose Rate Limits

Containers with dose rates less than or equal to 2 milliSieverts/ hour (200 millirem/ hour) at contact and less than 1 milliSievert/ hour (100 millirem/ hour) at 30 cm (11.8 in.) are acceptable at WRAP. Containers exceeding these limits may be acceptable but will require container-specific review and approval by WRAP Operations.

This page intentionally left blank.

7 References

- 10 CFR 61, "Licensing Requirements for Land Disposal of Radioactive Waste," *Code of Federal Regulations*, as amended.
- 10 CFR 830, "Nuclear Safety Management," *Code of Federal Regulations*, as amended.
- 40 CFR 61, "National Emission Standards for Hazardous Air Pollutants," *Code of Federal Regulations*, as amended.
- 49 CFR 171, "Transportation," *Code of Federal Regulations*, as amended.
- 49 CFR 173, "Shippers—General Requirements for Shipments and Packagings," *Code of Federal Regulations*, as amended.
- 40 CFR 261, "Identification and Listing of Hazardous Waste," *Code of Federal Regulations*, as amended.
- 40 CFR 264, "Standards for Owners and Operators of Hazardous Waste Treatment, Storage and Disposal Facilities," *Code of Federal Regulations*, as amended.
- 40 CFR 268, "Land Disposal Restrictions," *Code of Federal Regulations*, as amended.
- 40 CFR 761, "Polychlorinated Biphenyls (PCBs) Manufacturing, Processing, Distribution in Commerce, and Use Prohibitions," *Code of Federal Regulations*, as amended.
- 49 CFR, "Transportation," *Code of Federal Regulations*, as amended.
- ANSI/ANS 8.15, 1981, *Nuclear Criticality Control of Special Actinide Elements*, American National Standards Institute/American Nuclear Society, New York, New York.
- ASTM Standard E-84, *Standard Test Method for Surface Burning Characteristics of Building Materials*, American Society for Testing of Materials, Philadelphia, Pennsylvania. (Use most current version.)
- Atomic Energy Act of 1954*, 42 USC 2011 et seq.
- Comprehensive Environmental Response, Compensation and Liability Act of 1980*, 42 USC 9601 et seq.
- DOE M 435.1-1, 2001, *Radioactive Waste Management Manual*, Chg. 1, U.S. Department of Energy, Washington, D.C.
- DOE M 470.4-2, 2005, *Physical Protection*, Chg. 1, U.S. Department of Energy, Washington, D.C.
- DOE O 414.1C, 2005, *Quality Assurance*, U.S. Department of Energy, Washington, D.C.
- DOE O 435.1, 2001, *Radioactive Waste Management*, Chg. 1, U.S. Department of Energy, Washington, D.C.
- DOE O 470.4A, 2007, *Safeguards and Security Program*, U.S. Department of Energy, Washington, D.C.
- DOE O 5400.5, 1993, *Radiation Protection of the Public and the Environment*, Chg. 2, U.S. Department of Energy, Washington, D.C.
- DOE/RL-91-31, 2001, *Hanford Site Waste Minimization and Pollution Prevention Awareness Program Plan*, U.S. Department of Energy, Richland Operations Office, Richland, Washington. (Use most current version.)

- DOE/RL-92-36, 2006, *Hanford Site Hoisting and Rigging Manual*, U.S. Department of Energy, Richland Operations Office, Richland, Washington. (Use most current version.)
- DOE/RL-2000-25, 2008, *Richland Operations Office Implementation Plan for DOE Order 435.1*, Rev. 5, U.S. Department of Energy, Richland Operations Office, Richland, Washington.
- DOE/WIPP-02-3122, 2006, *Contact-Handled Transuranic Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico. (Use most current version.)
- DOE/WIPP-02-3214, 2003, *RH TRU Waste Characterization Program Implementation Plan (WCPIP)*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico. (Use most current version.)
- Hanford Facility RCRA Permit, WA7 89000 8967, Unit Name Part A Form.
- HNF-1886, 2008, *Central Waste Complex Waste Analysis Plan*, Rev. 6, Fluor Hanford, Inc., Richland, Washington.
- HNF-1981, 1998, *Specification for Concrete Encasement for Contact-Handled Category 3 Waste*, Rev. 0, Waste Management Federal Services of Hanford, Inc., Richland, Washington.
- HNF-2165, 2007, *WRAP Facility Waste Analysis Plan*, Rev. 5, Waste Management Federal Services of Hanford, Inc., Richland, Washington.
- HNF-2599, 2004, *Hanford Site Transuranic Waste Characterization Quality Assurance Project Plan*, Rev. 11, Fluor Hanford, Inc., Richland, Washington.
- HNF-2600, 2004, *Hanford Site Transuranic Waste Certification Plan*, Rev. 13, Fluor Hanford, Inc., Richland, Washington.
- CHPRC-00073, 2009, *CH2M Hill Plateau Remediation Company Radiological Control Manual*, Rev. 0, CH2M Hill Plateau Remediation Company, Richland, Washington.
- HNF-5841, 2008, *Low-Level Burial Grounds Waste Analysis Plan*, Rev. 4, Fluor Hanford, Inc., Richland, Washington.
- HNF-9921, 2008, *T Plant Complex Waste Analysis Plan*, Rev. 5, Fluor Hanford, Inc., Richland, Washington.
- HNF-11724, 2007, *Hanford Safety Management Programs*, Rev. 5, Fluor Hanford, Inc., Richland, Washington.
- HNF-13536, *PHMC Radiological Control Procedures*, Section 4.1.1, "Standard Release Surveys for Material and Equipment," Fluor Hanford, Inc., Richland, Washington. (Use most current version.)
- HNF-14741, 2007, *Master Documented Safety Analysis (MDSA) for the Solid Waste Operations Complex (SWOC)*, Fluor Hanford, Inc., Richland, Washington. (Use most current version.)
- HNF-15280, 2007, *Technical Safety Requirements for the Solid Waste Operations Complex*, Fluor Hanford, Inc., Richland, Washington. (Use most current version.)
- HNF-21239, 2007, *Solid Waste Operations Complex Fire Hazard Analysis*, Rev. 2A, Fluor Hanford Inc., Richland, Washington.

- HNF-FMP-07-32540-RO, Pallets, 48 X 48 and 56 X 56 , Fluor Hanford, Inc., Richland, Washington.
- PRC-PRO-RP-20377, *Determination of the Radiological Status of RCRA/TSCA Waste*, Fluor Hanford, Inc., Richland, Washington.
- NRC, 1991, *Technical Position Paper on Waste Form*, Rev. 1, U.S. Nuclear Regulatory Commission Office of Nuclear Material Safety and Safeguards, Washington, D.C.
- NRC, 1996, *Safety Analysis Report for the TRUPACT II Shipping Package (SARP)*, NRC Docket No. 71-9218, Revision 19a, U.S. Department of Energy, Washington, D.C.
- NUREG-0782, "Licensing Requirements for Land Disposal of Radioactive Waste," Draft Environmental Impact Statement on 10 CFR Part 61, U.S. Nuclear Regulatory Commission, September 1981.
- Resource Conservation and Recovery Act of 1976*, 42 USC 6901 et seq.
- SW-846, *Test Methods for Evaluating Solid Waste: Physical/Chemical Methods*, 3rd ed., Office of Solid Waste, U.S. Environmental Protection Agency, Washington, D.C.
- Toxic Substances Control Act of 1976*, 15 USC 2601 et seq.
- WAC 173-303, "Dangerous Waste Regulations," *Washington Administrative Code*, as amended.
- WAC 173-460, "Controls for New Sources of Toxic Air Pollutants," *Washington Administrative Code*, as amended.
- WHC-EP-0645, 1995, *Performance Assessment for the Disposal of Low-Level Waste in the 200 West Area Burial Grounds*, Westinghouse Hanford Company, Richland, Washington.
- WHC-S-0486, 1998, *Specification for High Integrity Container, 300 Year*, Rev. 0A, Westinghouse Hanford Company, Richland, Washington.
- WHC-SD-WM-TI-714, 1995, *High-Density Polyethylene Liner Chemical Compatibility for Radioactive Mixed Waste Trenches*, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- WHC-SD-WM-TI-730, 1996, *Performance Assessment for the Disposal of Low-Level Waste in the 200 East Area Burial Grounds*, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- UFC, 1997, *Uniform Fire Code*, 1997 Edition, International Fire Code Institute, Austin, Texas.

This page intentionally left blank.

Appendix A
Radiological Calculation Methods

This page intentionally left blank.

A1 Radiological Calculation Methods

A variety of radiological calculations are required to determine whether a waste can be managed at Hanford Site treatment, storage, and disposal (TSD) units. The following sections describe the methodology for performing these calculations. For each calculation, the following assumptions shall be used.

- All major radionuclides in the waste, as defined in Section 2.5.1, must be considered in the calculations. If there is a major radionuclide in the waste that is not listed in Table A-1 and Table A-2 (presented at the end of this appendix), the generator must notify the Waste & Fuels Management (WFMP) acceptance organization to calculate the applicable limits and conversion factors.
- If a daughter radionuclide has a half-life less than 10 days and the parent radionuclide has a half-life greater than the daughter, the activity of the daughter should not be considered in the calculations.
- The volume of the outer waste container shall be used when limits are expressed in volume concentration. For example, a generator packaging a 1-L (0.001-m³) jar inside of a 208-L (55-gal) drum (0.208 m³ [0.7 ft³]) would use the 0.208-m³ (0.7-ft³) volume for radiological calculation purposes. An additional example is a concrete lined 208-L (55-gal) drum (0.208 m³ [0.7 ft³]) having a 0.15-m³ (0.5-ft³) waste capacity. The generator would again use 0.208 m³ (0.7 ft³) for the radiological calculation volume. If the waste is not containerized, the volume is the anticipated volume the waste will occupy in the TSD unit.

A1.1 Transuranic Waste Determination

To determine whether a waste is transuranic (TRU), compute the sum of the specific activity of the alpha-emitting radionuclides having half-lives greater than 20 years. These radionuclides are identified by footnote b in Table A-2. If the total alpha activity exceeds 100 nanocuries (3,700 becquerels) per gram, the waste is TRU (DOE M 435.1-1).

- For the mass of the waste matrix used in the TRU determination, the following direction will be used.
- The mass of added shielding, the container, and any rigid liners is excluded.
- The mass of stabilization media and similar materials added to meet waste acceptance criteria is used in accordance with DOE G 435.1-1, Chapter III.A.

A1.2 Calculation of Plutonium-239 Fissile Gram Equivalents

Fissile gram equivalent (FGE) is defined as the amount of plutonium-239 (in grams) that will produce the equivalent reactivity as another isotope at optimal shape, moderation, and reflection. FGE normally is calculated using the following steps.

- Multiply the grams of each fissionable isotope by the FGE conversion factor (FGE per gram) in Appendix B, Table B-1, to yield the FGE for the isotope.

Isotope mass (grams) x isotope conversion factor (FGE per gram) = Isotope FGE.

Sum the FGE for each fissionable isotope to a total FGE for all isotopes. If there is more than 1 g (0.03 oz) of uranium-235, the WFMP facility criticality safety representative could use an alternate method for determining the FGE for uranium-235 as discussed in Appendix B. Natural uranium (i.e., 0.72 percent uranium-235) and depleted uranium (i.e., <0.72 percent) is normally exempt for criticality purposes at

WFMP TSD units; however, the FGE from uranium-235 is counted for acceptance at the Waste Isolation Pilot Plant (WIPP).

A1.3 Calculation of Thermal Power

The thermal power of the waste in a container is calculated from the concentration of radionuclides in the waste and the heat of decay from Table A-1. The thermal power calculation is performed using the following steps.

- The concentration of each isotope is multiplied by the heat of decay for that isotope from the value in Table A-1, yielding the thermal power for each isotope.

$$\begin{aligned} & \text{Isotope concentration (curies per m}^3\text{)} \times \text{decay heat (watts/curie)} \\ & = \text{decay heat (watts per m}^3\text{)} \end{aligned}$$

Thermal power is the sum of the thermal power of all isotopes in the waste.

A1.4 Category 1 Determination

Classification of waste as Category 1 or greater than Category 1 is a sum-of-fractions calculation, performed using the following steps.

- The concentration of each isotope (expressed in curies per m³) is divided by its respective Category 1 limit from Table A-2.

The category is the sum of the fractions for all isotopes in the waste package.

If the sum of the fractions is less-than-or-equal-to 1, the waste is Category 1. If the sum of fractions exceeds 1, the waste is greater than Category 1, and the Category 3 determination described in A1.5 must be performed to classify the waste package.

A1.5 Category 3 Determination

Category 3 determination is performed in the same way as the Category 1 calculation, only using the Category 3 limits from Table A-2 using the following steps.

1. The concentration of each isotope (expressed in curies per m³) is divided by its respective Category 3 limit from Table A-2.

The category is the sum of the fractions for all isotopes in the waste.

If the sum of the fractions is less than or equal to 1, the waste is Category 3. If the sum of fractions exceeds 1, the waste is greater than Category 3.

A1.6 Mobile Radionuclide Reporting

This is a simple comparison of the concentration of each mobile isotope (hydrogen-3, carbon-14, chlorine-36, selenium-79, molybdenum-93, technetium-99, iodine-129, rhenium-187, total uranium, and neptunium-237) against its respective reporting value from Table A-2.

A1.7 Calculating Dose Equivalent Curies

Calculation of dose equivalent curies (DE-Ci) is a method of normalizing the exposure risk of various isotopes. Calculation of the DE-Ci of a waste container is performed using the following steps.

- Multiply the activity (in curies) of each isotope in a given container by its respective ICRP 71 Correction Factor from Table A-1.

The total DE-Ci of the waste package is the sum of the DE-Ci values for all isotopes in the waste multiplied by the assigned "Master Documented Safety Analysis (MDSA) DE-Ci Factor" (default value is 1.0). An MDSA DE-Ci Factor other than 1 may be applied based on the package factors described in MDSA Appendix 3B. The package factors are used to adjust the effective amount of material at risk. This is justified in those cases where the robustness of the waste packaging and dispersibility of the waste form are sufficiently different than the waste form and container used in the original analysis to adjust the facility or container DE-Ci limits.

A1.8 Calculating Plutonium-239 Equivalent Curies

The plutonium equivalent curie calculation is required for TRU waste to be shipped to the WIPP. The plutonium equivalent curie calculation is performed as specified in the WIPP waste acceptance criteria (DOE/WIPP-02-3122).

A2 References

- DFSNW-ECAL-043, 2001, *Calculations for Table A-1 of HNF-EP-0063*, Rev. 0, Duratek Federal Services, Inc., Northwest Operations, Richland, Washington.
- DOE G 435.1-1, Chapter 3, 1999, *Transuranic Waste Requirements*, U.S. Department of Energy, Washington, D.C.
- DOE M 435.1-1, 2001, *Radioactive Waste Management Manual*, Chg. 1, U.S. Department of Energy, Washington, D.C.
- DOE/WIPP-02-3122, 2006, *Contact-Handled Transuranic Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, Rev. 3, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico.
- Firestone, R. B., S. Y. F. Chu, and L. P. Ekstrom, 1999, *Table of Isotopes*, 8th ed., John Wiley & Sons, Inc., New York, New York. (*The Lund / LBNL Nuclear Data Search Database*, version 2.0 is available at <http://Nucleardata.nuclear.lu.se/nucleardata/toi>).
- HNF-14741, 2007, *Master Documented Safety Analysis (MDSA) for the Solid Waste Operations Complex (SWOC)*, Fluor Hanford, Inc., Richland, Washington. (Use most current version.)
- WHC-EP-0645, 1995, *Performance Assessment for the Disposal of Low-Level Waste in the 200 West Area Burial Grounds*, Westinghouse Hanford Company, Richland, Washington.
- WHC-SD-WM-TI-730, 1996, *Performance Assessment for the Disposal of Low-Level Waste in the 200 East Area Burial Grounds*, Rev. 0, Westinghouse Hanford Company, Richland, Washington.

A3 Tables

Table A-1. Conversion Factors for General Radiological Calculations

Isotope	Half-Life (second)	Specific Activity ^b (Curies/gram)	Decay Heat ^{a,c} (Watts/Curie)	ICRP 71 DE-Ci Correction Factor ^{a,d}
H-3	3.891 E+08	9.613 E+03	3.383 E-05	5.20 E-06
Be-7	4.605 E+06	3.491 E+05	1.996 E-03	1.00 E-06
Be-10	5.049 E+13	2.231 E-02	1.495 E-03	1.92 E-04
C-14	1.808 E+11	4.455 E+00	2.933 E-04	1.16 E-04

Table A-1. Conversion Factors for General Radiological Calculations

Isotope	Half-Life (second)	Specific Activity ^b (Curies/gram)	Decay Heat ^{a,c} (Watts/Curie)	ICRP 71 DE-Ci Correction Factor ^{a,d}
Na-22	8.214 E+07	6.244 E+03	1.420 E-02	2.60 E-05
P-32	1.232 E+06	2.864 E+05	4.119 E-03	1.54 E-05
Si-32	5.428 E+09	6.500 E+01	4.079 E-04	2.20 E-03
P-33	2.195 E+06	1.559 E+05	4.539 E-04	1.84 E-06
S-35	7.560 E+06	4.267 E+04	2.895 E-04	2.80 E-05
Cl-36	9.530 E+12	3.291 E-02	1.622 E-03	1.46 E-04
Ar-39	8.489 E+09	3.411 E+01	1.296 E-03	0.00 E+00
K-40	4.039 E+16	6.989 E-06	4.025 E-03	4.20 E-05
Ca-41	3.249 E+12	8.500 E-02	1.408 E-02	1.90 E-06
Ar-42	1.041 E+09	2.582 E+02	1.381 E-03	0.00 E+00
Ti-44 ^a	1.490 E+09	1.722 E+02	1.708 E-02	1.22 E-03
Ca-45	1.406 E+07	1.785 E+04	4.577 E-04	5.40 E-05
Sc-46	7.242 E+06	3.390 E+04	1.258 E-02	1.36 E-04
V-49	2.851 E+07	8.084 E+03	2.685 E-05	4.20 E-07
Cr-51	2.394 E+06	9.251 E+04	2.170 E-04	4.00 E-07
Mn-54	2.698 E+07	7.751 E+03	4.981 E-03	1.70 E-05
Fe-55	8.631 E+07	2.379 E+03	3.492 E-05	1.54 E-05
Co-56	6.679 E+06	3.020 E+04	2.200 E-02	9.60 E-05
Co-57	2.348 E+07	8.438 E+03	8.536 E-04	1.10 E-05
Co-58	6.122 E+06	3.181 E+04	5.990 E-03	3.20 E-05
Fe-59	3.845 E+06	4.979 E+04	7.749 E-03	4.40 E-05
Fe-60	4.752 E+13	1.300 E-04	2.900 E-02	5.60 E-03
Ni-59	2.398 E+12	7.982 E-02	4.248 E-05	3.60 E-06
Co-60	1.664 E+08	1.131 E+03	1.542 E-02	2.00 E-04
Ni-63	3.124 E+09	5.738 E+01	1.016 E-04	8.80 E-06
Zn-65	2.110 E+07	8.233 E+03	3.495 E-03	4.00 E-05
Ge-68	2.340 E+07	7.098 E+03	5.264 E-05	1.04 E-05
Se-75	1.034 E+07	1.457 E+04	2.400 E-03	2.00 E-05
Se-79	2.051 E+12	6.969 E-02	6.019 E-04	2.20 E-05
Sr-82	2.208 E+06	6.237 E+04	7.665 E-05	4.20 E-05
Rb-83	7.448 E+06	1.827 E+04	2.934 E-03	1.38 E-05

Table A-1. Conversion Factors for General Radiological Calculations

Isotope	Half-Life (second)	Specific Activity ^b (Curies/gram)	Decay Heat ^{a,c} (Watts/Curie)	ICRP 71 DE-Ci Correction Factor ^{a,d}
Rb-84	2.831 E+06	4.749 E+04	6.236 E-03	2.00 E-05
Kr-85	3.383 E+08	3.927 E+02	1.498 E-03	0.00 E+00
Sr-85	5.603 E+06	2.371 E+04	3.128 E-03	7.60 E-06
Rb-86	1.612 E+06	8.145 E+04	4.518 E-03	1.86 E-05
Y-88	9.213 E+06	1.393 E+04	1.603 E-02	8.20 E-05
Sr-89	4.365 E+06	2.907 E+04	3.460 E-03	2.00 E-05
Sr-90 ^a	9.037 E+08	1.388 E+02	6.695 E-03	4.80 E-04
Nb-91	2.146 E+10	5.783 E+00	1.021 E-04	2.20 E-04
Mo-93	9.504 E+10	1.278 E+00	9.834 E-05	2.00 E-05
Nb-93m	5.089 E+08	2.386 E+02	1.834 E-04	1.02 E-05
Zr-93	4.828 E+13	2.515 E-03	1.130 E-04	5.00 E-04
Nb-94	6.307 E+11	1.905 E-01	1.031 E-02	2.20 E-04
Nb-95	3.022 E+06	3.934 E+04	4.795 E-03	3.00 E-05
Zr-95 ^a	5.532 E+06	2.149 E+04	5.047 E-03	5.00 E-05
Tc-99	6.668 E+12	1.711 E-02	5.986 E-04	5.80 E-06
Ru-103 ^a	3.392 E+06	3.232 E+04	3.578 E-03	9.60 E-06
Ru-106 ^a	3.181 E+07	3.349 E+03	9.670 E-03	1.58 E-04
Pd-107	2.050 E+14	5.148 E-04	5.513 E-05	5.00 E-07
Ag-108m ^a	1.319 E+10	7.926 E+00	1.008 E-02	1.22 E-04
Cd-109	3.997 E+07	2.592 E+03	1.237 E-04	1.62 E-04
Ag-110m ^a	2.158 E+07	4.756 E+03	1.687 E-02	1.10 E-04
Cd-113m	4.323 E+08	2.311 E+02	1.086 E-03	2.20 E-03
Sn-113 ^a	9.944 E+06	1.005 E+04	2.498 E-03	1.08 E-05
Sn-119m	2.532 E+07	3.748 E+03	5.313 E-04	5.60 E-06
Sn-121m	1.736 E+09	5.376 E+01	2.396 E-04	1.60 E-05
Te-121	1.450 E+06	6.435 E+04	3.471 E-03	4.80 E-06
Te-123	3.154 E+20	2.911 E-10	1.342 E-05	7.80 E-05
Sb-124	5.205 E+06	1.749 E+04	1.331 E-02	2.60 E-05
I-125	5.135 E+06	1.759 E+04	3.655 E-04	1.02 E-04
Sb-125	8.707 E+07	1.037 E+03	3.150 E-03	2.80 E-05
Te-125m	5.011 E+06	1.802 E+04	8.582 E-04	1.02 E-05

Table A-1. Conversion Factors for General Radiological Calculations

Isotope	Half-Life (second)	Specific Activity ^b (Curies/gram)	Decay Heat ^{a,c} (Watts/Curie)	ICRP 71 DE-Ci Correction Factor ^{a,d}
Sb-126	1.071 E+06	8.363 E+04	1.847 E-02	2.00 E-05
Sn-126 ^a	3.156 E+12	2.839 E-02	1.056 E-03	2.20 E-04
Te-127m ^a	9.418 E+06	9.440 E+03	1.870 E-03	3.00 E-05
I-129	4.951 E+14	1.768 E-04	4.633 E-04	7.20 E-04
Te-129m ^a	2.920 E+06	2.997 E+04	4.127 E-03	2.60 E-05
Xe-131m	1.028 E+06	8.382 E+04	9.622 E-04	0.00 E+00
Ba-133	3.337 E+08	2.544 E+02	2.705 E-03	3.00 E-05
Cs-134	6.517 E+07	1.293 E+03	1.018 E-02	1.32 E-04
Cs-135	7.574 E+13	1.104 E-03	3.964 E-04	1.38 E-05
Cs-136	1.137 E+06	7.300 E+04	2.326 E-03	2.40 E-05
Cs-137 ^a	9.521 E+08	8.655 E+01	4.816 E-03	9.20 E-05
Ba-140 ^a	1.101 E+06	7.326 E+04	2.236 E-02	2.00 E-05
Ce-141	2.808 E+06	2.851 E+04	1.467 E-03	6.40 E-05
Ce-144 ^a	2.462 E+07	3.185 E+03	7.996 E-03	7.20 E-04
Nd-147	9.487 E+05	8.094 E+04	2.432 E-03	4.80 E-05
Pm-147	8.278 E+07	9.277 E+02	3.676 E-04	1.00 E-04
Sm-147	3.343 E+18	2.297 E-08	1.361 E-02	1.92 E-01
Eu-150	1.079 E+09	6.977 E+01	9.532 E-03	3.80 E-06
Sm-151	2.840 E+09	2.632 E+01	1.179 E-04	8.00 E-05
Eu-152	4.267 E+08	1.740 E+02	7.667 E-03	8.40 E-04
Gd-152	3.406 E+21	2.180 E-11	1.303 E-02	3.80 E-01
Gd-153	2.091 E+07	3.528 E+03	8.622 E-04	4.20 E-05
Eu-154	2.712 E+08	2.703 E+02	9.009 E-03	1.06 E-03
Eu-155	1.529 E+08	4.762 E+02	7.749 E-04	1.38 E-04
Tm-170	1.111 E+07	5.975 E+03	1.982 E-03	1.40 E-04
Hf-175	6.048 E+06	1.066 E+04	2.422 E-03	1.44 E-05
Hf-181	3.662 E+06	1.703 E+04	4.357 E-03	2.80 E-05
Ta-182	9.910 E+06	6.257 E+03	8.890 E-03	1.52 E-04
W-185	6.489 E+06	9.401 E+03	7.520 E-04	2.40 E-06
Re-187	1.577 E+18	3.827 E-08	3.913 E-06	4.00 E-08
Au-195	1.608 E+07	3.599 E+03	7.629 E-04	1.32 E-06

Table A-1. Conversion Factors for General Radiological Calculations

Isotope	Half-Life (second)	Specific Activity ^b (Curies/gram)	Decay Heat ^{a,c} (Watts/Curie)	ICRP 71 DE-Ci Correction Factor ^{a,d}
Hg-203	4.026 E+06	1.381 E+04	1.997 E-03	1.12 E-05
Tl-204	1.196 E+08	4.624 E+02	1.407 E-03	7.80 E-06
Bi-207	1.002 E+09	5.438 E+01	9.829 E-03	1.12 E-04
Pb-210	7.037 E+08	7.634 E+01	2.661 E-04	1.80 E-02
Po-210	1.196 E+07	4.493 E+03	3.206 E-02	1.22 E-02
Ra-226	5.049 E+10	9.885 E-01	2.888 E-02	7.00 E-02
Ac-227	6.871 E+08	7.232 E+01	5.021 E-04	1.10 E+01
Ra-228	1.815 E+08	2.727 E+02	1.391 E-04	5.20 E-02
Th-228	6.037 E+07	8.195 E+02	3.272 E-02	6.40 E-01
Th-229	2.316 E+11	2.127 E-01	3.055 E-02	2.20 E+00
Th-230	2.379 E+12	2.061 E-02	2.822 E-02	8.60 E-01
Pa-231	1.034 E+12	4.723 E-02	3.054 E-02	2.80 E+00
Th-232	4.434 E+17	1.097 E-07	2.426 E-02	9.00 E-01
U-232	2.203 E+09	2.207 E+01	3.210 E-02	7.40 E-01
U-233	5.026 E+12	9.633 E-03	2.912 E-02	1.92 E-01
Th-234	2.082 E+06	2.315 E+04	4.268 E-04	1.32 E-04
U-234	7.754 E+12	6.217 E-03	2.880 E-02	1.88 E-01
U-235	2.221 E+16	2.161 E-06	2.773 E-02	1.70 E-01
Pu-236	9.152 E+07	5.222 E+02	3.478 E-02	4.00 E-01
U-236	7.390 E+14	6.468 E-05	2.712 E-02	1.74 E-01
Np-237	6.753 E+13	7.047 E-04	2.944 E-02	4.60 E-01
Pu-238	2.768 E+09	1.712 E+01	3.315 E-02	9.20 E-01
U-238	1.410 E+17	3.361 E-07	2.532 E-02	1.60 E-01
Pu-239	7.609 E+11	6.202 E-02	3.109 E-02	1.00 E+00
Pu-240	2.071 E+11	2.269 E-01	3.115 E-02	1.00 E+00
Am-241	1.366 E+10	3.427 E+00	3.343 E-02	8.40 E-01
Pu-241	4.544 E+08	1.030 E+02	3.177 E-05	1.80 E-02
Am-242m	4.450 E+09	1.047 E+01	4.288 E-04	7.40 E-01
Cm-242	1.408 E+07	3.311 E+03	3.682 E-02	1.04 E-01
Pu-242	1.179 E+13	3.954 E-03	2.955 E-02	9.60 E-01
Am-243	2.324 E+11	1.997 E-01	3.225 E-02	8.20 E-01

Table A-1. Conversion Factors for General Radiological Calculations

Isotope	Half-Life (second)	Specific Activity ^b (Curies/gram)	Decay Heat ^{a,c} (Watts/Curie)	ICRP 71 DE-Ci Correction Factor ^{a,d}
Cm-243	9.467 E+08	4.903 E+01	3.683 E-02	6.20 E-01
Cm-244	5.712 E+08	8.093 E+01	3.499 E-02	5.40 E-01
Pu-244	2.525 E+15	1.831 E-05	2.909 E-02	9.40 E-01
Cm-245	2.682 E+11	1.716 E-01	3.334 E-02	8.40 E-01
Cm-246	1.493 E+11	3.072 E-01	3.282 E-02	8.40 E-01
Bk-247	4.352 E+10	1.049 E+00	3.425 E-02	1.38 E+00
Cm-247	5.049 E+14	9.043 E-05	3.174 E-02	7.80 E-01
Cm-248	1.073 E+13	4.239 E-03	1.244 E-01	3.00 E+00
Cf-249	1.108 E+10	4.089 E+00	3.945 E-02	1.40 E+00
Cf-250	4.128 E+08	1.093 E+02	3.727 E-02	6.80 E-01
Cm-250	2.525 E+11	1.787 E-01	8.263 E-01	1.68 E+01
Cf-251	2.834 E+10	1.586 E+00	3.663 E-02	1.42 E+00
Cf-252	8.347 E+07	5.362 E+02	7.258 E-02	4.00 E-01
Es-254	2.380 E+07	1.865 E+03	5.779 E-02	1.72 E-01

The conversion factor from seconds to years is 3.155 E+07 s/yr.

- a. Daughters with half-life less than 10 days (8.64×10^5 sec) and with parent radionuclide half-life greater than the daughter are not reportable as separate isotopes. Contributions from nonreportable daughters have been included in the decay heat and dose equivalence factors.
- b. Firestone, R. B., S. Y. F. Chu, and L. P. Ekstrom, 1999, *Table of Isotopes*, 8th ed., John Wiley & Sons, Inc., New York, New York. (*The Lund / LBNL Nuclear Data Search Database*, version 2.0 is available at <http://Nucleardata.nuclear.lu.se/nucleardata/toi>.)

Specific activity data: DFSNW-ECAL-043, *Calculations for Table A-1 of HNF-EP-0063*, Rev. 0, Duratek Federal Services, Inc., Northwest Operations, Richland, Washington.

- c. Decay heat: ORIGEN database.
- d. ICRP 71 Factor: HNF-14741, 2007, *Master Documented Safety Analysis (MDSA) for the Solid Waste Operations Complex (SWOC)*, Fluor Hanford, Inc., Richland, Washington. (Use most current version.)

DE-Ci = dose equivalent curie.

ICRP = International Commission of Radiological Protection.

Table A-2. Low-Level Burial Grounds Radiological Content Limits

Isotope	Mobile Radionuclide Reporting Limit (Curies per m ³)	Category 1 Waste Limit (Curies per m ³)	Category 3 Waste Limit (Curies per m ³)
H-3	4.4 E+00	9.9 E+04	NL
Be-7	NL	NL	NL
Be-10	NL	1.1 E+00	2.4 E+02
C-14	1.3 E-04	9.1 E-02	2.1 E+01
C-14 activated metal ^a	NL	9.1 E-01	2.1 E+02
Na-22	NL	NL	NL
P-32	NL	NL	NL
Si-32	NL	7.3 E-01	3.6 E+02
P-33	NL	NL	NL
S-35	NL	NL	NL
Cl-36	3.1 E-05	6.4 E-05	1.4 E-01
Ar-39	NL	NL	NL
K-40	NL	1.8 E-03	3.8 E-01
Ca-41	NL	1.9 E-01	4.1 E+01
Ar-42	NL	NL	NL
Ti-44	NL	6.3 E-03	4.7 E+02
Ca-45	NL	NL	NL
Sc-46	NL	NL	NL
V-49	NL	NL	NL
Cr-51	NL	NL	NL
Mn-54	NL	NL	NL
Fe-55	NL	NL	NL
Co-56	NL	NL	NL
Co-57	NL	NL	NL
Co-58	NL	NL	NL
Fe-59	NL	NL	NL
Ni-59	NL	3.9 E+00	8.5 E+02
Fe-60	NL	NL	NL
Ni-59 activated metal ^a	NL	3.9 E+01	8.5 E+03
Co-60	NL	7.5 E+01	NL
Co-60 activated metal ^a	NL	7.5 E+02	NL
Ni-63	NL	5.9 E+00	2.0 E+04

Table A-2. Low-Level Burial Grounds Radiological Content Limits

Isotope	Mobile Radionuclide Reporting Limit (Curies per m ³)	Category 1 Waste Limit (Curies per m ³)	Category 3 Waste Limit (Curies per m ³)
Ni-63 activated metal ^a	NL	5.9 E+01	2.0 E+05
Zn-65	NL	NL	NL
Ge-68	NL	NL	NL
Se-75	NL	NL	NL
Se-79	3.4 E-05	5.1 E-01	1.1 E+02
Sr-82	NL	NL	NL
Rb-83	NL	NL	NL
Rb-84	NL	NL	NL
Kr-85	NL	NL	NL
Sr-85	NL	NL	NL
Rb-86	NL	NL	NL
Y-88	NL	NL	NL
Sr-89	NL	NL	NL
Sr-90 ^c	NL	1.6 E-02	5.4 E+04
Nb-91	NL	2.0 E+00	6.3 E+02
Mo-93	2.1 E-04	8.7 E-01	2.0 E+02
Nb-93m	NL	NL	NL
Zr-93	NL	2.50 E+00	5.40 E+02
Nb-94	NL	2.2 E-04	4.8 E-02
Nb-94 activated metal ^a	NL	2.2 E-03	4.8 E-01
Nb-95	NL	NL	NL
Zr-95 ^c	NL	NL	NL
Tc-99	2.1 E-04	2.3 E-02	5.0 E+00
Ru-103 ^c	NL	NL	NL
Ru-106 ^c	NL	NL	NL
Pd-107	NL	1.5 E+01	3.3 E+03
Ag-108m	NL	NL	NL
Cd-109	NL	NL	NL
Ag-110m ^c	NL	NL	NL
Cd-113m	NL	7.6 E-01	NL
Sn-113 ^c	NL	NL	NL
Sn-119m	NL	NL	NL

Table A-2. Low-Level Burial Grounds Radiological Content Limits

Isotope	Mobile Radionuclide Reporting Limit (Curies per m ³)	Category 1 Waste Limit (Curies per m ³)	Category 3 Waste Limit (Curies per m ³)
Sn-121m	NL	6.7 E-01	2.2 E+04
Te-121	NL	NL	NL
Te-123	NL	NL	NL
Sb-124	NL	NL	NL
I-125	NL	NL	NL
Te-125m	NL	NL	NL
Sb-125	NL	NL	NL
Sb-126	NL	NL	NL
Sn-126 ^c	NL	1.6 E-04	3.4 E-02
Te-127m ^c	NL	NL	NL
I-129	1.0 E-06	8.5 E-03	1.8 E+00
Te-129m ^c	NL	NL	NL
Xe-131m	NL	NL	NL
Ba-133	NL	7.1 E-01	NL
Cs-134	NL	NL	NL
Cs-135	NL	1.6 E-01	3.5 E+01
Cs-136	NL	NL	NL
Cs-137 ^c	NL	5.5 E-03	1.2 E+04
Ba-140 ^c	NL	NL	NL
Ce-141	NL	NL	NL
Ce-144 ^c	NL	NL	NL
Nd-147	NL	NL	NL
Pm-147	NL	NL	NL
Sm-147	NL	1.7 E-02	3.7 E+00
Eu-150	NL	1.4 E-03	6.7 E+02
Sm-151	NL	4.6 E+01	2.1 E+05
Eu-152	NL	4.8 E-02	NL
Gd-152	NL	6.4 E-03	1.4 E+00
Gd-153	NL	NL	NL
Eu-154	NL	7.5 E-01	NL
Eu-155	NL	NL	NL
Tm-170	NL	NL	NL

Table A-2. Low-Level Burial Grounds Radiological Content Limits

Isotope	Mobile Radionuclide Reporting Limit (Curies per m ³)	Category 1 Waste Limit (Curies per m ³)	Category 3 Waste Limit (Curies per m ³)
Hf-175	NL	NL	NL
Hf-181	NL	NL	NL
Ta-182	NL	NL	NL
W-185	NL	NL	NL
Re-187	3.3 E-02	3.6 E+01	7.8 E+03
Au-195	NL	NL	NL
Hg-203	NL	NL	NL
Tl-204	NL	NL	NL
Bi-207	NL	1.7 E-03	1.44 E+03
Pb-210	NL	3.7 E-02	2.1 E+06
Po-210	NL	NL	NL
Ra-226	NL	1.7 E-04	4.3 E-02
Ac-227	NL	4.2 E-03	3.0 E+05
Ra-228	NL	1.7 E+01	NL
Th-228	NL	NL	NL
Th-229	NL	4.4 E-04	9.8 E-02
Th-230	NL	2.1 E-03	1.5 E-01
Pa-231	NL	1.4 E-04	3.0 E-02
Th-232	NL	1.1 E-04	2.3 E-02
Total U	1.4 E-05	NL	NL
U-232	See Total U	4.6 E-04	4.6 E+00
U-233	See Total U	7.4 E-03	9.7 E-01
Th-234	NL	NL	NL
U-234	See Total U	8.9 E-03	1.9 E+00
U-235	See Total U	2.8 E-03	5.0 E-01
Pu-236	NL	NL	NL
U-236	See Total U	9.5 E-03	2.0 E+00
Np-237 ^b	1.1 E-05	6.8 E-04	1.5 E-01
Pu-238 ^b	NL	4.7 E-03	2.4 E+01
U-238	See Total U	5.7 E-03	1.2 E+00
Pu-239 ^b	NL	1.9 E-03	4.2 E-01
Pu-240 ^b	NL	1.9 E-03	4.3 E-01

Table A-2. Low-Level Burial Grounds Radiological Content Limits

Isotope	Mobile Radionuclide Reporting Limit (Curies per m ³)	Category 1 Waste Limit (Curies per m ³)	Category 3 Waste Limit (Curies per m ³)
Am-241 ^b	NL	2.1 E-03	8.5 E-01
Pu-241	NL	6.1 E-02	2.5 E+01
Am-242m ^b	NL	1.9 E-03	1.6 E+00
Cm-242	NL	NL	NL
Pu-242 ^b	NL	2.0 E-03	4.3 E-01
Am-243 ^b	NL	1.0 E-03	2.3 E-01
Cm-243 ^b	NL	1.8 E-02	3.4 E+02
Cm-244	NL	1.4 E-01	1.6 E+02
Pu-244 ^b	NL	6.1 E-04	1.3 E-01
Cm-245 ^b	NL	1.3 E-03	2.2 E-01
Cm-246 ^b	NL	1.8 E-03	4.2 E-01
Bk-247 ^b	NL	1.5 E-03	3.8 E-01
Cm-247 ^b	NL	5.6 E-04	1.2 E-01
Cm-248 ^b	NL	5.1 E-04	1.1 E-01
Cf-249 ^b	NL	7.8 E-04	3.6 E-01
Cf-250	NL	3.8 E-01	1.5 E+02
Cm-250 ^b	NL	9.3 E-05	2.1 E-02
Cf-251 ^b	NL	1.3 E-03	3.8 E-01
Cf-252	NL	NL	NL
Es-254	NL	NL	NL

a. Limit for isotope in activated metal.

b. TRU isotope (half-life >20 years).

c. Daughters with half-life less than 10 days and with parent radionuclide half-life greater than the daughter are not reportable.

Ci/m³ = curies per cubic meter

NL = no applicable limit

Source:

WHC-EP-0645, 1995, *Performance Assessment for the Disposal of Low-Level Waste in the 200 West Area Burial Grounds*, Westinghouse Hanford Company, Richland, Washington, and WHC-SD-WM-TI-730, 1996, *Performance Assessment for the Disposal of Low-Level Waste in the 200 East Area Burial Grounds*, Rev. 0, Westinghouse Hanford Company, Richland, Washington.

This page intentionally left blank.

Appendix B
Fissionable Material Content Limits

This page intentionally left blank.

B1 Fissionable Material Content Limits

The following subsections describe the limits for fissionable material content in waste packages or bulk waste sent to treatment, storage, and/or disposal (TSD) units covered by the criteria provided in this document. Fissionable material inventories for a given container shall be restricted to ensure they do not exceed the applicable fissionable material limit, including measurement uncertainty. For some waste packages, the generator must provide distribution of the fissionable material or moderating materials in the container to determine the applicable specification and whether criticality limits are met. Meeting criticality limits does not ensure that the container will be accepted, as Waste Isolation Pilot Plant (WIPP) and disposal limits may be more restrictive.

B1.2 Exempt Materials

Waste packages or bulk waste shipments are exempt from criticality safety controls and fissile labeling at all TSD units if the fissile gram equivalence (FGE) for the contained fissionable material is less than 1 FGE. Natural uranium (i.e., 0.72 percent uranium-235) and depleted uranium (i.e., <0.72 percent) is normally exempt for criticality purposes at the TSD units; however, the total mass of uranium-235 is counted for WIPP acceptance.

B1.3 Measurement Uncertainty for Nonexempt Materials

Measured values of operating parameters subject to criticality safety limits (e.g., the mass of a given isotope) shall conservatively account for assessed biases and uncertainties for the measurement methods.

The measurement uncertainty will be accounted for in the following ways.

- For transuranic (TRU) waste destined for the WIPP, the sum of the measured mass and the mass corresponding to the 2 sigma total measurement uncertainty shall be less than the fissile material quantity limits in Table G-2.

For measurements of fissionable material under a critical mass limit, where the accuracy of the fissile mass measurement method is determined from NDA measurements performed in accordance with HNF-RD-10484 or equivalent NDA QA program, the measured FGE plus one total measurement uncertainty (TMU) shall not exceed the values for a qualified program in Table B-2 (presented at the end of this appendix). The TMU of any measurement system shall not exceed 30 percent for any drum with a measured value (without measurement uncertainty applied) greater than 50 FGE when establishing compliance with the Table B-2 FGE limits. The 95 percent confidence measurement value is to be used for establishing compliance of boxes with the Table B-2 FGE limits.

The acceptance of containers based on methods not equivalent to HNF-RD-10484 may be allowed based on Waste & Fuels Management (WFMP) criticality representative review for acceptability under the alternative "Acceptable Knowledge" (AK) values specified in Table B-2.

B1.4 Non-Exempt Materials in Standard Containers

Certain non-exempt materials in standard packaging configurations (per Table B-2) are acceptable at the Low-Level Burial Grounds (LLBG), the Central Waste Complex (CWC), the T Plant Complex, and the Waste Receiving and Processing (WRAP) Facility. The fissionable material limits are expressed in plutonium-239 FGE as defined in HNF-5134, *CSEER 00-005, Determination of Fissile Gram Equivalence for Hanford Solid Waste Operations*, and described in Section A1.1.2. Table B-1, presented at the end of this appendix, is used to determine the total FGE of fissionable material in a waste container by multiplying the gram quantity of each listed isotope by the correction factor and summing the results.

Note that when waste contains a significant quantity of non-exempt uranium-235, the FGE calculation will be conservative, as it does not account for the poisoning effect of uranium-238 in the mixture. If a container approaches or exceeds a limit of Table B-2, due in part to the uranium-235 content, the method provided in Section B1.1.6 can be used to correct the contribution of uranium-235 to the total FGE. This will be applied for waste disposal and may be used for waste retrieval operations as needed.

Some of the specific container limits are shown in Table B-2, which addresses the most common containers and CPSs. Additional requirements are detailed in the CPSs. Other container limits or acceptable configurations may be available. Exceptions can be requested as specified in Section 1.6. If a new criticality safety evaluation report (CSER) is required for a new waste stream, the generator will need to provide funding for performing the evaluation.

Assumptions and controls from the CSER for box receipt and storage in addition to the total fissile content specified in Table B-1 that must be met include the following for each box. Note that other containers, which are not technically boxes, may be accepted under the box CSER as long as the containers meet these requirements.

- Discard of fissionable materials was minimized, or individual equipment pieces are 350 FGE or less
- Hydrogenous material containers of 15 FGE or less
- Free liquid of 2 L (0.53 gal) or less
- High-efficiency particulate air (HEPA) filters are treated as hydrogenous waste, or limited to 10 FGE/ft³
- Box must be of robust construction and resistant to water intrusion.

Note that for disposal of non-TRU waste in the LLBG, containers are also limited to 128.5 FGE per drum equivalent volume and 42.4 FGE per ft² cross sectional area (CPS-SW-008).

Liquids and absorbed liquids with non-exempt quantities of fissionable material must normally be packaged in 3.8-L (1-gal) containers or limited to less than 2.2 L (0.58 gal). Specific Plutonium Finishing Plant waste streams, however, are allowed for direct disposal into absorbent in 208-L (55-gal) drums with 90-mil liners.

B1.5 Non-Exempt Materials in Non-Standard Containers or Bulk Waste

Waste packages that have non-exempt quantities of fissionable material but are not in Table B-2 standard containers (e.g., in 114-L [30-gal] drums, concrete or wooden boxes, small boxes, ion exchange modules, or bulk waste shipments) may still be received for storage and disposal. Waste packages of this type may be accepted up to a maximum of 128.5 FGE, per drum equivalent volume and 42.4 FGE per ft² cross sectional area (CPS-SW-008). Other transportation limits might apply to the entire shipment.

B1.6 Non-Exempt Quantities of Fissionable Radionuclides in Other Configurations

Limits for configurations other than those shown in Sections B1.1.3 and B1.1.4 may already be available or may be requested as described in Section 1.6. If a new CSER is required for a new waste stream, the generator will need to provide funding for performing the evaluation.

B1.7 Calculation of Uranium-235 FGE

HNF-5134 provides a detailed method for calculating FGE that takes into account the poisoning effect of uranium-238. The maximum enrichment, or actual distribution for a mixture of enrichments, is required to perform this calculation. If uranium is not a significant factor, FGE may be calculated as shown in Section A1.1.2. The uranium-235 FGE value for the uranium in a waste package is calculated by one of the following methods.

- FGE for uranium-235 may be calculated using the conversion factor in Table B-1. Uranium-235 also may be excluded in calculating FGE if it is in natural or depleted uranium (less than or equal to 0.72 weight percent uranium-235 in uranium); however, the FGE from uranium-235 is counted for WIPP acceptance. The WFMP facility criticality safety representative may also exempt homogeneous uranium solutions in solid or liquid form up to 1.0 weight percent enrichment of uranium-235.
- The FGE for uranium-235 may be conservatively calculated by including all uranium-235 present with no exemptions on a 1 gram = 1 FGE basis. This conservative method of conversion was typically used for older waste packages.

The methods discussed above result in over counting the contribution of uranium-235 to the fission process by neglecting the effects of uranium-238 in reducing the neutron population available for fission (i.e., poisoning). These methods are adequate (safe) for accepting waste containers if the amount of uranium-235 is less than the criticality mass limit, but such usage may unnecessarily restrict shipping of containers with greater than 1 gram of uranium-235.

B2 References

- CPS-SWOC-001, *Criticality Prevention Specification: SWOC Storage, Movement, and Non-Intrusive Operations* Fluor Hanford, Inc., Richland, Washington.
- CPS-SW-008, *Criticality Prevention Specification: Burial of Non-TRU Fissile Material in the Lined Trenches*, Fluor Hanford, Inc., Richland, Washington.
- HNF-5134, 2000, CSER 00-005: *Determination of Fissile Gram Equivalence for Hanford Solid Waste Operations*, Fluor Hanford, Inc., Richland, Washington.
- HNF-RD-10484, 2006, *Nondestructive Assay Management Program*, Fluor Hanford, Inc., Richland, Washington.

B3 Bibliography

- HNF-7098, 2006, *Criticality Safety Program*, Fluor Hanford, Inc., Richland, Washington. (Use most current version.).

B4 Tables

Table B-1. Fissile Gram Equivalent Conversion Factors (Fissile Gram Equivalent per Gram)

Isotope	Conversion Factor	Isotope	Conversion Factor
U-233	1.0*	Am-242m	3.46 E+1
U-235	6.43 E-1	Am-243	1.29 E-2
Np-237	1.5 E-2	Cm-243	5.0 E+0
Pu-238	1.13 E-1	Cm-244	9.0 E-2
Pu-239	1.0 E+0	Cm-245	1.5 E+1
Pu-240	2.25 E-2	Cm-247	5.0 E-1
Pu-241	2.25 E+0	Cf-249	4.5 E+1
Pu-242	7.5 E-3	Cf-251	9.0 E+1
Am-241	1.88 E-2	—	—

*Value used for U233 was previously 0.9.

Source: Table 4-2 in HNF-5134, 2000, *CSEER 00-005: Determination of Fissile Gram Equivalence for Hanford Solid Waste Operations*, Rev. 0, Fluor Hanford, Inc., Richland, Washington.

Table B-2. Summary of Fissile Material Limits for Standard Waste Containers

Container	Additional Container or Content Specifications	Maximum FGE without Handling Restrictions (CPS-SWOC-001)	Maximum FGE with Handling Restrictions (CPS-SWOC-001)	Maximum WIPP FGE
208-L (55-gal) Drum or Larger	FGE Based on Qualified Program <32 kg Pb, <140 kg drum weight	250	340	200 ^a /100 ^b
	FGE Based on AK <32 kg Pb, <140 kg drum weight	128	179	Not acceptable
	FGE Based on Qualified Program >32 kg Pb, <800 kg drum weight	216	Not acceptable	200 ^a /100 ^b
	FGE Based on AK >32 kg Pb, <800 kg drum weight	108	Not acceptable	Not acceptable
	FGE Based on Qualified Program No Limit	180	250	Not acceptable
	FGE Based on AK No Limit	87	128	Not acceptable

Table B-2. Summary of Fissile Material Limits for Standard Waste Containers

Container	Additional Container or Content Specifications	Maximum FGE without Handling Restrictions (CPS-SWOC-001)	Maximum FGE with Handling Restrictions (CPS-SWOC-001)	Maximum WIPP FGE
	Liquid Lab Pack with FGE per Qualified Program	170	Non specified	Not acceptable
	Liquid Lab Pack with FGE Based on AK	80	Non specified	Not acceptable
WIPP SWB and Other Boxes (only SWBs are Allowed for WIPP)	SWB with Unrestricted H/X and FGE Based on Qualified Program	325-380	325-380	100-325 ^e
	Waste Box with Minimum Dimension of (2.5 ft) and FGE Based on Qualified Program	250	1,000	100-325 ^e (SWB only)
	Waste Box with Minimum Dimension of (2.5 ft) and FGE Based on AK	125	500	Not acceptable
TDOP	Up to 10 Drums with FGE Based on a Qualified Program	325	325	325

- a. 200 g FGE for 55, 85, or 100 gal drums containing less than 1% by wt. Be or BeO
- b. 100 g FGE for 55, 85, or 100 gal drums containing greater than 1% by wt. Be or BeO
- c. 325 g FGE for SWB containing less than 1% by wt. Be or BeO

250 g FGE for SWB containing machine compacted waste, ≤1% by wt. Be or BeO

100 g FGE for SWB containing greater than 1% by wt. Be or BeO.

All measured FGE limits include uncertainty (2 TMU for WIPP; 1 TMU for SWOC).

WIPP and SWOC acceptance of SWBs over 325 FGE up to 380 FGE is dependent on the ²⁴⁰Pu content.

Exceptions for fissile containers:

Drums over 200 FGE may be acceptable at WIPP when overpacked in an SWB or TDOP.

Non-steel drums are allowed with WFMP CSR concurrence, but handling restrictions may be required.

Waste storage drums are assumed to have nominal dimensions of 84.46 cm (33.25 in.) inner height, 88.9 cm (35 in.) outer height, 57.15 cm (22.5 in.) inner diameter, and 60.96 cm (24 in.) outer diameter. Drums smaller than these dimensions may be allowed only if overpacked in a container meeting this assumption.

Fissile boxes smaller than 1.5 m x 1.2 m x 0.9 m (5 ft x 4 ft x 3 ft) (L x W x H) may be allowed with WFMP CSR concurrence.

Over 2.2 L (0.58 gal) liquid in a container may be allowed with WFMP CSR concurrence, but FGE limits are reduced and handling restrictions may be required.

Other containers may be acceptable at SWOC based on specific CSERs.

SWOC normally excludes depleted or natural uranium from FGE calculations—WIPP does not.

Additional process controls may be required by the applicable CPSs.

Additional disposal requirements apply (CPS-SW-008) (see Sections B1.1.13 and B1.1.14).

- CPS = criticality prevention specification
- SWB = standard waste box
- CSER = criticality safety evaluation report
- SWOC = Solid Waste Operations Complex

Table B-2. Summary of Fissile Material Limits for Standard Waste Containers

Container	Additional Container or Content Specifications	Maximum FGE without Handling Restrictions (CPS-SWOC-001)	Maximum FGE with Handling Restrictions (CPS-SWOC-001)	Maximum WIPP FGE
CSR	=	criticality safety representative		
TDOP	=	ten drum overpack		
FGE	=	fissile gram equivalent		
TMU	=	total measurement uncertainty		
GW	=	gross weight		
VIPAC	=	vibratory compaction fuel pins		
HEPA	=	high-efficiency particulate air		
WIPP	=	Waste Isolation Pilot Plant		
H/X	=	Hydrogen to fissile atom ratio		
WFMP	=	Waste & Fuels Management		

Appendix C
Labeling of Waste Containers

This page intentionally left blank.

C1 Labeling of Waste Containers

Containers sent to Hanford Site treatment, storage, and/or disposal (TSD) units must be labeled for identification and to communicate information needed for proper waste management. Table C-1, presented at the end of this appendix, shows the standard labeling required on containerized waste. The following sections provide general requirements for labels and markings.

C1.1 Bar Code

Each container shall be labeled with a bar code showing the unique container identification number (CIN). Bar-coded CINs will be assigned as follows.

- For containers purchased through the Hanford Site procurement system, the bar code will be attached to the containers when the containers are received at the Central Stores warehouse. The CIN is a unique seven-digit number.
- For containers not purchased through the Hanford Site procurement system, Hanford Site generators will assign a CIN. The CIN must be a unique number. The suggested format to ensure that the CIN is unique is: "Facility ID-Year-Sequential #," where the Facility ID is the generating facility's unique four-character (letter and/or number) identifier, "Year" is the last two digits of the year the CIN was assigned, and "Sequential #" is the generator's sequential numbering of containers for that year.
- For offsite generators, a bar code will be attached when the container is received on the Hanford Site. The CIN will be the unique container identification number provided by the waste generator. (NOTE: Offsite generators should contact the Waste & Fuels Management [WFMP] acceptance organization for guidance on assigning a unique identification number.)

C1.2 Durability

Labels and markings must be durable, fade-resistant, water-resistant paints, vinyl stickers, or another system that is sufficiently durable to remain intact and legible during management of the waste before disposal.

C1.3 Placement of Labels

Labels and markings shall be positioned so that all required information is visible on the same side of the container as the bar code. If drums are palletized, the drums must be oriented on the pallet such that a complete set of labels is visible.

C1.4 Size of Labels

Standard labels defined by regulations (e.g., U.S. Department of Transportation [DOT] label, hazardous waste label, polychlorinated biphenyl [PCB] label, asbestos label) should be the conventional size specified by the regulations. Characters on other labels (e.g., gross weight, major risk label) must be a minimum of 2.54 cm (1 in.) high or as specified by the regulations.

C1.5 Labeling Inner Containers in Lab Packs

Each inner container in a lab pack must be labeled with an identification number or waste name cross-referenced against the contents inventory sheet. These labels must be sufficiently durable to remain legible for 20 years. Prior to DOT transportation and during dangerous waste accumulation in Washington State, DOT markings can be used instead of DOT labels to communicate dangerous waste

major risk(s) (e.g., if the major risk of a dangerous waste is flammability, the container may be marked “Flammable” as opposed to being labeled with the Class 3 Flammable label). However, at the point of transportation, the waste must be labeled with the applicable DOT hazard class label. Major risk markings requirements are as follows (HNF-PRO-15333).

- State-only/Non-DOT dangerous waste: The words “hazardous waste” or “dangerous waste” are sufficient.
- State-only/DOT and federal hazardous waste: The words “hazardous waste” or “dangerous waste” and the DOT hazard class label or mark are sufficient.

C2 References

40 CFR 61, “National Emission Standards for Hazardous Air Pollutants,” *Code of Federal Regulations*, as amended.

40 CFR 761, “Polychlorinated Biphenyls (PCBs) Manufacturing, Processing, Distribution in Commerce, and Use Prohibitions,” *Code of Federal Regulations*, as amended.

49 CFR, “Transportation,” *Code of Federal Regulations*, as amended.

DOE/RL-2001-36, 2003, *Hanford Sitewide Transportation Safety Document*, U.S. Department of Energy, Richland Operations Office, Richland, Washington. (Use most current version.)

HNF-PRO-15333, *Environmental Protection Processes*, Fluor Hanford, Inc., Richland, Washington.

C3 Tables

Table C-1. Required Labeling for Waste Containers^d

Label	When Required	Location on Drum	Location on Box
Bar code with container identification number	All containers	Bottom third of drum	Short side of box
Gross weight in kg (kilogram units must appear on label)	All containers	Same side as bar code	Same side as bar code
Applicable DOT labeling	All containers	As specified in 49 CFR	As specified in 49 CFR
Dangerous waste or hazardous waste label	Dangerous and mixed waste containers	Same side as bar code	Same side as bar code
Major risk label(s) ^a	Dangerous and mixed waste containers	Same side as bar code	Same side as bar code
PCB label ^b	Waste that is regulated for PCB content under 40 CFR 761	Same side as bar code	Same side as bar code
Asbestos label	As required per 40 CFR 61 Subpart M	Same side as bar code	Same side as bar code
SWITS-generated fissile label (printed with a barcode printer) and fissile trefoil label (or symbol) ^c	Containers with 1 FGE or more fissionable material	Same side as bar code	Same side as bar code

- a. Refer to Table C-2 for major risk labeling of dangerous, mixed, and TRUM waste.
- b. Label in accordance with 40 CFR 761.40 and 40 CFR 761.45. The label placed on containers holding PCB items must include the date the item was removed from service. For PCB articles and containers, the label must include the date the waste was placed into storage, including 30-day temporary storage areas.
- c. These labels might conflict with the DOT fissile label; for shipments of waste from offsite and many onsite generators, these labels should be placed on the containers at the time the waste arrives on the Hanford Site or at the receiving facility.
- d. For packages shipped within a Special Packaging Zone as allowed by DOE/RL-2001-36, the minimum marking and labeling requirements are the bar code with container identification number and gross weight in kg.

DOT = U.S. Department of Transportation

PCB = polychlorinated biphenyl

TRU = transuranic

Source:

40 CFR 61, "National Emission Standards for Hazardous Air Pollutants," *Code of Federal Regulations*, as amended.

40 CFR 761, "Polychlorinated Biphenyls (PCBs) Manufacturing, Processing, Distribution in Commerce, and Use Prohibitions," *Code of Federal Regulations*, as amended.

49 CFR, "Transportation," *Code of Federal Regulations*, as amended.

DOE/RL-2001-36, 2003, *Hanford Sitewide Transportation Safety Document*, U.S. Department of Energy, Richland Operations Office, Richland, Washington. (Use most current version.)

Table C-2. Selection of Major Risk Labeling

Hazard or Risk	Acceptable Labels and Markings
Flammable Liquid	DOT Class 3 label (Flammable Liquid) FLAMMABLE LIQUID COMBUSTIBLE LIQUID
Flammable Solid	DOT Division 4.1 label (Flammable Solid) FLAMMABLE SOLID
Water-reactive	DOT Division 4.3 label (Dangerous When Wet) DANGEROUS WHEN WET WATER-REACTIVE
Oxidizer	DOT Division 5.1 label (Oxidizer) OXIDIZER
Organic Peroxide	DOT Division 5.2 label (Organic Peroxide) ORGANIC PEROXIDE
Poison or Toxic	DOT Division 6.1 label (Poison) or (Inhalation Hazard) POISON or TOXIC POISON—INHALATION HAZARD or TOXIC— INHALATION HAZARD
Corrosive Liquid or Corrosive Solid	DOT Class 8 label (Corrosive) CORROSIVE
Hazardous Wastes—DOT Class 9 Only	DOT Class 9 label (Miscellaneous) and "Hazardous Waste" or "Dangerous Waste" marking
WA State-Only Dangerous Wastes—Non DOT	"Hazardous Waste" or "Dangerous Waste" marking

Choose the label or marking, or combination of labels or markings that most clearly communicates the major risk(s) associated with the waste. Markings in Table C-2 must be applied for dangerous waste major risk(s) regardless of the DOT radioactive labeling status. If the dangerous waste is only DOT radioactive hazard class 7, the "Dangerous Waste" or "Hazardous Waste" marking suffices as the dangerous waste major risk. DOT labels must be used when required by the DOT.

DOT = U.S. Department of Transportation

Appendix D

Selection of Compatible Containers, Coatings, and Liners

This page intentionally left blank.

D1 Selection of Compatible Containers, Coatings, and Liners

WAC 173-303-630 (4) requires that containers used for storage of dangerous waste be made of, or lined with, materials that are compatible with the waste and will not react with the waste such that the ability of the container to contain the waste is not impaired. A variety of factors affect the compatibility of a container/liner combination, including the properties of chemical constituents in the waste, the physical form of the waste (e.g., free liquid, sorbed liquid, dry waste), and the anticipated length of storage.

The compatibility of the container/liner and the waste is determined using chemical compatibility charts, manufacturer's compatibility data, and/or other applicable data. Any combination of container(s) and/or liner(s) can be used that is compatible with the waste.

Hanford Site procurement specifications for metal drums (HNF-7403) and boxes (HNF-7656) identify several options for container coatings, with varying degrees of chemical resistance. The document WHC-SD-TP-ES-002, *Justification for Packaging Acceptance Criteria*, describes a set of standard packages from the Hanford Site that generally will be compatible with the types of waste generated on the Hanford Site. Table D-1, presented at the end of this appendix, provides baseline coating and liner combinations for metal containers based on WHC-SD-TP-ES-002. These container/liner combinations generally provide a compatible container, although compatibility data must demonstrate the container is compatible with the waste. (NOTE: The Hanford Site specifications and Table D-1 are provided for information purposes only. It is not necessary to select packaging according to Hanford Site specifications.)

D2 References

HNF-7403, 2003, *Specification for Packaging of Hanford Site Performance-Based Drums*, Rev. 0, Duratek Federal Services, Inc., Northwest Operations, Richland, Washington.

HNF-7656, 2001, *Specification for Packaging of Hanford Site Performance-Based Steel Boxes*, Rev. 0, Duratek Federal Services, Inc., Northwest Operations, Richland, Washington.

WAC 173-303, "Dangerous Waste Regulations," *Washington Administrative Code*, as amended.

WHC-SD-TP-ES-002, 1996, *Justification for Packaging Acceptance Criteria*, Rev. 0, Westinghouse Hanford Company, Richland, Washington.

D3 Table

Table D-1. Standard Container/Liner Combinations

WSRd Series	SubGroup ^a	Minimum Coatings/Liners ^b
100—Low-level waste	Low-level dry waste for disposal	LPC/no liner
	Low-level absorbed liquids	LPC/10-mil liner
200—TRU waste	Dry debris and soil	LPC/10-mil liner MPC/no liner
	Sorbed or solidified corrosive (acid or caustic) liquids	LPC/90-mil liner HPC/no liner
	Sorbed or solidified noncorrosive liquids, sludges, and wet soil	MPC/10-mil liner LPC/90-mil liner
	Organic liquids (noncorrosive)	MPC/10-mil liner LPC/90-mil liner
400—Mixed waste overpacked and lab-packed liquids	Corrosive (acidic or caustic) or oxidizing liquids	HPC/no liner LPC/90-mil liner
	Other noncorrosive waste	MPC/10-mil liner LPC/90-mil liner
	Sorbed organic liquids or sludges (noncorrosive)	MPC/10-mil liner LPC/90-mil liner
500—Mixed waste solids, sorbed liquids, and soils	Corrosive (acidic or caustic) or oxidizing waste	HPC/no liner LPC/90-mil liner
	Noncorrosive sorbed liquid, sludges, or wet soils	MPC/10-mil liner LPC/90-mil liner
	Noncorrosive dry solids or dry soils	MPC/no liner LPC/10-mil liner
	Corrosive (acidic or caustic) or oxidizing debris	HPC/no liner LPC/90-mil liner
600—Mixed debris waste	Other noncorrosive debris	MPC/no liner LPC/10-mil liner
	Lead solids, beryllium powder	LPC/no liner
800—Mixed waste with specific treatment standards	Elemental mercury	LPC/10-mil (0.6 in.) liner
	Batteries containing acids or caustics	HPC/no liner LPC/90-mil liner
	Other	Case-by-case evaluation
	Solid corrosive waste	HPC/no liner LPC/90-mil liner
900—State-only mixed waste and LDR-compliant mixed waste	Other	MPC/no liner LPC/10-mil liner

Table D-1. Standard Container/Liner Combinations

WSRd Series	SubGroup ^a	Minimum Coatings/Liners ^b
-------------	-----------------------	--------------------------------------

a. For mixed hazards, the most protective combination of coatings/liners should be chosen.

b. Container coating/liner abbreviations are as follows.

10-mil liner—10-mil or thicker nylon-reinforced polyethylene liner.

90-mil liner—90-mil or thicker high-density polyethylene rigid liner.

HPC = high performance coating

LDR = land disposal restrictions

LPC = low performance coating

MPC = medium performance coating

TRU = transuranic

WSRd = waste specification record

This page intentionally left blank

Appendix E

Selection and Use Of Void Fillers, Sorbents, and Stabilizing Materials

This page intentionally left blank.

E1 Selection and Use of Void Fillers, Sorbents, and Stabilizing Materials

A variety of materials can be added as void filler to meet the void space requirements of Chapters 3 and 4.

Sorbents and stabilizing materials can be used to meet free liquid requirements or to provide a safer waste form for handling and storage. All sorbents and stabilizing materials must be nonhazardous, compatible with the waste being sorbed or stabilized, and nonbiodegradable as defined in Title 40 *Code of Federal Regulations* (CFR) 264.314(e). Table E-1, presented at the end of this appendix, lists the general types of sorbents and stabilizing materials that can be used for major Hanford Site waste streams. Specific products used must meet the definitions of Section E1.1 that have been listed on an approved Waste Profile Sheet.

Note that use of these materials to meet radiological stabilization (i.e., to meet Category 3 or mobile radionuclide stabilization requirements) or *Resource Conservation and Recovery Act of 1976* (RCRA) land disposal restrictions treatment standards is not addressed in this appendix. More specific evaluation must be performed as specified previously in this document to demonstrate radiological stabilization or land disposal restrictions compliance.

E1.1 General Types of Sorbents and Stabilizing Materials Potentially Allowed

The general types of sorbents and stabilizing materials potentially allowed include the following.

- Inorganic mineral sorbents including aluminosilicates, clays, vermiculite, zeolites, lime, silica, diatomaceous earth, perlite, fly ash, and other inorganic materials used for absorption.
- High molecular weight synthetic polymers (polymer sorbents) including polyethylene, high-density polyethylene, polypropylene, polyacrylate, and other synthetic polymers. This excludes polymers derived from biological material (e.g., cellulose-based materials), and polymers specifically designed to be degradable.
- Stabilizing materials including concrete, portland cement, lime/pozzolans, and a variety of other inorganic materials.

NOTE: Selection of specific materials must be in accordance with Section E1.1.2.

Specialty stabilization agents for organic liquids include certain products that stabilize organic liquids. These products chemically react with organic liquids to prevent their release in the disposal environment.

E1.2 Selection and Use of Sorbents and Stabilizing Materials

Selection and use of a specific product for sorption of a given waste must address the following.

- Determine from Table E-1 what general classes of materials can be used and the conditions for use. The allowable types of sorbents for various waste streams are based on the anticipated treatment/disposal methods.
- Select a product that is appropriate for the material to be treated. Generators can request approval of products in the waste stream profile sheet by providing data to support the intended use. Approval of the profile constitutes approval of the product.
- Obtain manufacturer's instructions and limitations for use of the product. It is critical to use sorbents and stabilizing materials in accordance with the manufacturer's instructions. Information required includes the following.

- Compatibility of the sorbent or stabilizing material with the waste
- The recommended ratio of sorbent to waste for the liquid being sorbed
- For stabilizing materials, the exact ratio of liquid to stabilizing materials and methods of mixing.

It might be necessary to run a test of the waste or a surrogate to ensure that the product works adequately with the waste requiring sorption or stabilization.

E1.3 Hanford Site Requirements for Use of Sorbents

Sorbents used for Hanford Site treatment, storage, and/or disposal (TSD) units must be used in sufficient quantity to meet the following requirement.

Use twice the minimum amount of sorbent. Based on data from the manufacturer or testing, the minimum ratio of sorbent to liquid is determined. For all Hanford Site applications, a minimum of twice the minimum amount of sorbent shall be used.

E2 References

40 CFR 264, "Standards for Owners and Operators of Hazardous Waste Treatment, Storage and Disposal Facilities," *Code of Federal Regulations*, as amended.

Resource Conservation and Recovery Act of 1976, 42 USC 6901 et seq.

E3 Table

Table E-1. Sorbent Selection Based on Waste Specification Records

WSRd Series	Subgroup	Allowable Sorbents/Stabilizing Materials
100—Low-level waste	Low-level liquids for disposal	Mineral sorbents Polymer sorbents Stabilizing materials
	Low-level organic liquids (>1%) and chelating agents (>1%) for disposal	Stabilizing materials
200—TRU waste	TRUM waste	Mineral sorbents Polymer sorbents Stabilizing materials
	TRU waste (not mixed)	Mineral sorbents Polymer sorbents Stabilizing materials
400—Mixed waste overpacked and lab packed liquids ^a	All types	Mineral sorbents Polymer sorbents
500—Mixed waste solids, sorbed liquids and soils	Non-thermal treatment WSRds (520 series)	Mineral sorbents Polymer sorbents
	Thermal treatment WSRds (500 series)	Mineral sorbents Polymer sorbents
600—Mixed debris waste	Thermal treatment WSRds (620 series)	Mineral sorbents Polymer sorbents
	Non-thermal treatment WSRds (640 series)	Mineral sorbents Polymer sorbents
800—Other mixed waste with specific treatment standards	All types	Polymer sorbents (or as specified in waste stream profile)
900—State-only mixed waste and LDR-compliant mixed waste	Thermal treatment WSRds (920 series)	Mineral sorbents Polymer sorbents
	Other WSRds	Mineral sorbents Polymer sorbents

a. Sorbent for lab packs is placed around containers, not mixed with liquids.

LDR = land disposal restrictions

TRU = transuranic

WSRd = waste specification record

This page intentionally left blank.

Appendix F
Radiological Release of Waste

This page intentionally left blank.

F1 Radiological Release of Waste

Appendix F has been retired. Radiological release information is reflected in the following two documents:

PRC-PRO-RP-20377, Determination of the Radiological Status of RCRA/TSCA Waste, CH2MHill Plateau Remediation Company, Richland, Washington.

PRC-PRO-RP-40026, Standard Radiological Release Surveys for Material and Equipment, CH2MHill Plateau Remediation Company, Richland, Washington.

This page intentionally left blank.

Appendix G

Contact-Handled Transuranic Waste Certification Requirements

This page intentionally left blank.

G1 Contact-Handled Transuranic Waste Certification Requirements

As a generator of TRU and TRUM waste destined for disposal at the Waste Isolation Pilot Plant (WIPP), the Hanford Site must ensure its contact-handled (CH) TRU waste meets the requirements of U.S. Department of Energy (DOE) Order 435.1, *Radioactive Waste Management*, DOE/WIPP-02-3122, and the CH-TRAMPAC document. DOE/WIPP-02-3122 establishes the specific physical, chemical, radiological, and packaging criteria for acceptance of defense TRU waste shipments at the WIPP as required depending on waste material form and packaging configurations.

In addition to meeting the Solid Waste Operations Complex (SWOC) treatment, storage, and/or disposal (TSD) requirements identified in this document, the following are the specific TRU waste acceptance criteria.

G1.1 Remote-Handled Transuranic Criteria

See Appendix I.

G1.2 Contact-Handled Transuranic Criteria

- Waste must be segregated by waste specification record, including segregation of defense from non-defense waste. Non-defense waste is prohibited for shipment to WIPP, but may be shipped to a SWOC facility for storage using the exception process in Section 1.6.

Defense waste is waste generated, in whole or in part, by the Secretary of the Department of Energy (DOE) (and predecessor agencies) while carrying out any of these functions: naval reactors development; weapons activities, including defense inertial confinement fusion; verification and control technology; defense nuclear material production; defense nuclear waste and materials byproduct management; defense nuclear materials security investigations; and defense research and development.

The generator must supply sufficient information for the TRU Program to prepare and document an appropriate defense determination. Final approval of the defense determination will be made by DOE Richland Operations Office (RL) technical, RL Chief Counsel, RL TRU Project Director, Carlsbad Field Office (CBFO) technical, CBFO Chief Counsel, and (if necessary) DOE Headquarters (HQ) General Counsel.

- Waste must meet all requirements in Tables G-1 through G-5 except as allowed with profile sheet approval. The Hanford TRU Program may determine additional requirements for specific TRU waste are necessary, beyond those listed in Tables G-1 through G-5.
- Waste will be characterized and certified for shipment to WIPP under a centralized TRU program. Generators are not responsible for certification of TRU waste; however, generators are responsible for providing TRU waste that is certifiable and AK to support this certification. Generator-supplied documentation demonstrating compliance with the requirements in Tables G-1 through G-5 will ensure the TRU waste is certifiable.
- Newly generated waste that cannot be verified using nondestructive examination (radiography) must be packaged using the visual examination. This requirement, if applicable, will be communicated to the generator as a waste stream profile condition of approval. Waste Services personnel are available to conduct visual examinations at the generator location. If the waste cannot be verified using NDE, and cannot be packaged using visual examination, the waste must be packaged following the "Contact-Handled Transuranic Waste Packaging Instructions" (Marcinowski 2008). As a waste

stream profile condition of approval for waste packaged using the Packaging Instructions, documentation generated as a result of this packaging shall be provided to Waste Services and the TRU Program for retention as quality records.

- Newly generated TRU waste requires WIPP certification of the nondestructive assay equipment used to quantify the radiological properties. This requirement, if applicable, will be communicated to the generator as a waste stream profile condition of approval.
- Acceptable Knowledge (AK) data must be provided through use of a waste stream profile sheet from the *Hanford Site Solid Waste Acceptance Program* Internet Web site. The profile sheet is located at <http://www.hanford.gov/?page=581>.
- Packaging requirements will be established and communicated to the generator as a waste stream profile condition of approval. Generators must obtain waste stream profile approval prior to generating and/or packaging their contact-handled TRU (CH TRU) waste.

Generators unable to meet the above CH TRU criteria may request an exception to the waste acceptance criteria per Section 1.6 of this document.

The Hanford TRU program must be consulted before any waste containing plutonium in excess of 20 percent by weight is submitted for storage or disposal.

G2 References

49 CFR, "Transportation," *Code of Federal Regulations*, as amended.

49 CFR 173, "Shippers—General Requirements for Shipments and Packagings," *Code of Federal Regulations*, as amended.

40 CFR 262.32, Subpart C, "Standards Applicable to Generators of Hazardous Waste, Pre-Transport Requirements, Marking," *Code of Federal Regulations*, as amended.

40 CFR 761.40, Subpart C, "Polychlorinated Biphenyls (PCBs) Manufacturing, Processing, Distribution in Commerce, and Use Prohibitions, Marking of PCBs and PCB Items, Marking Requirements," *Code of Federal Regulations*, as amended. DOE O 435.1, 2001, *Radioactive Waste Management*, Chg. 1, U.S. Department of Energy, Washington, D.C.

DOE/WIPP-02-3122, 2008, *Transuranic Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, Rev. 6.2, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico.

Marcinowski, F, 2008, "Contact-Handled Transuranic Waste Packaging Instructions," Rev. 0, U.S. Department of Energy, Washington Sept. 30.

Hanford Site Solid Waste Acceptance Program. Available at: <http://www.hanford.gov/?page=577>.

Public Law 102-579, *Waste Isolation Pilot Plant Land Withdrawal Act*.

Resource Conservation and Recovery Act of 1976, 42 USC 6901 et seq.

G3 Tables

Table G-1. Container Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
Payload container description	DOT Type A or equivalent 208-L (55-gal) drums (direct fill or containing a pipe component) 208-L (55-gal) drums are <393 cm (24 in.) in diameter (including gasket, locking ring, and torqued accordingly) and <573 cm (34 - 15/16 in.) tall (fully assembled) SWBs (standard waste box) 322-L (85-gal) drum (208-L [55-gal] drum overpack, only)	Site procurement specifications and quality assurance QA acceptance reports, or manufacturer's fabrication documentation and records demonstrating equivalency with DOT Type A requirements, or testing records showing compliance with 49 CFR 173.461, or comparison to technical criteria/industry standards. Pipe overpack containers' and SWB's specifications procured consistent with CH-TRAMPAC requirements. Visual inspection to verify container integrity.
Container weights	<454 kg (1,000 lb)/55- or 85-gal (208- or 322-L) drum <1,814 kg (4,000 lb)/SWB 208-L (55-gal) drum with inner pipe component—contact Hanford TRU Program	Records of loaded container weights.
Removable surface contamination	For individual containers and payload assemblies: <20 dpm/100 cm ² for alpha <200 dpm/100 cm ² for beta-gamma The fixing of surface contamination to meet these limits is not allowed	Records of surface contamination surveys taken on individual containers prior to release from a radiological contamination area.
Container identification and marking	Bar code label consisting of a unique container identification number Shipping category Yellow and Magenta—DOT radioactive sticker Mixed—TRU waste marked as "Hazardous Waste" per 40 CFR 262.32 TRU waste containing PCBs marked per 40 CFR 761.40	Visual inspection at time of shipment.
Confinement requirements	Maximum layers of confinement allowed is six, including the liners Smaller number of confinement layers may be required as a waste stream profile condition of approval Newly generated waste must be packaged with filtered bags or be horsetailed Filtered bags are considered layers of confinement	Contents inventory records, which clearly indicate the number of confinement layers.

Table G-1. Container Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
Filter vents	Payload containers vented using one or more filter(s) that meet the WIPP Hazardous Waste Facility Permit and the CH-TRAMPAC Section 2.5.1 specification. Drums with vent clips are not considered vented.	Site procurement specifications and QA acceptance reports, manufacturer's fabrication documentation, and/or records of visual inspection.
CH-TRAMPAC	= contact-handled TRU waste authorized methods for payload control	
DOT	= U.S. Department of Transportation	
PCB	= polychlorinated biphenyl	
SWB	= standard waste box	
WIPP	= Waste Isolation Pilot Plant	
Source:		
	49 CFR 173, "Shippers—General Requirements for Shipments and Packagings," <i>Code of Federal Regulations</i> , as amended.	
	40 CFR 262.32, Subpart C, "Standards Applicable to Generators of Hazardous Waste, Pre-Transport Requirements, Marking," <i>Code of Federal Regulations</i> , as amended.	
	40 CFR 761.40, Subpart C, "Polychlorinated Biphenyls (PCBs) Manufacturing, Processing, Distribution in Commerce, and Use Prohibitions, Marking of PCBs and PCB Items, Marking Requirements," <i>Code of Federal Regulations</i> , as amended.	

Table G-2. Radiological Properties for Non-machine Compacted Waste Only

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
Radionuclide composition	Assay measurements Information on radionuclide composition, with emphasis on quantification of Am-241, Pu-238, Pu-239, Pu-240, Pu-242, U-233, U-234, U-238, Sr-90, Cs-137, and other radionuclides contributing to 95 percent of the radiologic activity of the container	Records of assay data and/or acceptable knowledge (AK) documentation.
Fissile material quantity (Pu-239 fissile gram equivalent) ^a	<200 g (55-gal) drum (direct fill or containing a pipe component) if Be < 1% by weight < 200 g (85-gal) drum if Be < 1% by weight <325 g/SWB if Be < 1% by weight < 100 g/container for all containers if Be >1% by wt. of the waste (up to 100 kg [220 lb] in a 55- or 85-gal drum, or up to 18.14 kg [39.9 lb] in a SWB and is particulate) Note that uncertainty must be accounted for in accordance with HNF-EP-0063 Appendix B, Section B.1.1.2	Records of assay data or AK documentation and calculations using isotopic composition, specific activity of the isotopes, and measured assay values to calculate Pu-239 FGE
TRU alpha activity concentration	>100 nCi of alpha-emitting TRU isotopes with half-lives greater than 20 years per gram of waste	Records of assay data or AK documentation and records of calculations showing concentrations of the total TRU radionuclides in the waste matrix.
Pu-239 equivalent	<u>Untreated waste:</u> <80 PE-Ci/ 208 L (55-gal) drum or 322 L	Records of assay data or AK documentation and records of conversion and calculations using Appendix B of the WIPP waste

Table G-2. Radiological Properties for Non-machine Compacted Waste Only

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
activity (PE-Ci)	(85 gal) drum <560 PE-Ci/SWB <1,100 PE-Ci/undamaged 208-L (55-gal) drum overpacked in a 322-L (85-gal) drum <1,200 PE-Ci/ undamaged 208-L (55-gal) or 322-L (85-gal) drum overpacked into a SWB, no single payload container within the SWB can exceed 1100 PE-Ci.* <1,800 PE-Ci/208 L (55-gal) drum containing a pipe component <u>Solidified/vitrified waste:</u> ≤1,800 PE-Ci/any payload container	acceptance criteria.
Radiation dose rate	<200 mrem/h at the surface of the payload (waste) container and the TRUPACT-II <10 mrem/h at 2 m (6.5 ft) < 179 mrem/hr for S100 pipe overpack containers < 155 mrem/hr for S300 pipe overpack containers	Measurements shall be made on each CH TRU waste container with instruments calibrated using sources traceable to a national standard. Internal payload container shielding cannot be used to meet dose rate requirements except for the approved pipe component configuration.
Decay heat	≤Limit established per waste stream profile	Compliance will be per direction in the waste stream profile and will be based on generator-supplied isotopic and loading data.

a. Waste containing beryllium and/or has been machine compacted has more restrictive critical safety requirements. Contact TRU Program for these more restrictive requirements.

*When overpacking one or more damaged waste containers, the direct-loaded PE-Ci limits apply.

- AK = Acceptable Knowledge
- CH TRU = contact-handled TRU
- g/SWB = gram per standard waste box
- mrem/h = millirem per hour
- nCi = nanocurie
- PE-Ci = plutonium equivalent curie
- TRU = transuranic
- TRUCON = TRUPACT-II Content Code
- TRUPACT II = transuranic package transporter II
- WIPP = Waste Isolation Pilot Project

Table G-3. Physical Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
Liquids	<p>Liquid waste is prohibited in payload containers except for residual amounts as follows:</p> <p>The waste shall contain as little residual liquid as is reasonably achievable by pouring, pumping, and/or aspirating.</p> <p><u>Residual liquid:</u></p> <p><1 volume percent of external container</p> <p><2.5 cm (1 in.) in bottom of internal containers</p> <p>Residual liquids containing PCBs are prohibited</p> <p>No detectable liquid in EPA code U134 (hydrofluoric acid) waste</p> <p><u>Liquid identification:</u></p> <p>Generators must specify the quantity and location of all liquids in the container</p>	<p>AK, radiography, visual examination, and/or packaging records will be used to determine the presence of residual liquids and to ensure the quantity of liquid satisfies the acceptance criteria.</p>
Sealed containers	<p>No sealed containers greater than 4 L (1 gal) except for Waste Material Type II.2 packaged in metal containers</p> <p>Sealed containers greater than 4 L (1 gal) including rigid liners, shall be vented</p> <p>Heat-sealed plastic bags must have at least one filter vent</p> <p>NOTE: See CH-TRAMPAC (Section 2.8,) for waste material type II.2 definition.</p>	<p>AK, radiography, visual examination, and/or packaging records</p> <p>Taping a lid around the edges to secure it without venting the lid is considered a sealed container</p> <p>Cross-taping across the lid, or crimping the container are acceptable methods for securing materials in internal containers</p>
AK	=	Acceptable Knowledge
CH-TRAMPAC	=	contact-handled TRU waste authorized methods for payload control
PCB	=	polychlorinated biphenyl

Table G-4. Chemical Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
Pyrophoric materials	<p><1 percent (by weight) radionuclide pyrophorics, generally dispersed in the waste</p> <p>No nonradionuclide pyrophorics</p>	<p>AK documentation and/or records of procedures, processes, or evidence that shows no presence of pyrophorics or treatment to eliminate the characteristic</p>
Hazardous waste	<p>Limited to EPA hazardous waste numbers identified as allowable in the WIPP Hazardous Waste Facility Permit and all Washington State waste codes</p> <p>Ignitable (D001), corrosive (D002), and reactive (D003) waste prohibited</p>	<p>Approved Standardized Waste Profile Sheet</p> <p>AK documentation and/or records of procedures, processes, or evidence that shows hazardous waste codes as listed in Table G-5</p>
Chemical compatibility	<p>No wastes incompatible with backfill, seal and panel closures materials, container, and packaging materials, shipping container materials, or other wastes</p>	<p>AK documentation and/or records of sampling and analysis, records of verification by visual examination or radiography³ that the waste meets the assigned waste stream description in the waste profile</p>
Explosives,	No explosives, corrosives, or compressed	Radiography records, visual examination

Table G-4. Chemical Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
corrosives, and compressed gases	gases (pressurized containers)	records, or AK documentation, and site policies/procedures prohibiting these items
Polychlorinated biphenyls	PCB-contaminated TRU and PCB-contaminated TRU waste mixed with a hazardous waste, including PCB remediation waste, PCB articles, and PCB bulk product waste may be stored and disposed at the WIPP There can be no free-flowing liquids in PCB waste	AK and/or records of sampling and analysis Information from the generator must include the earliest date of waste generation (i.e., the date of removal from service for disposal), the estimated weight of PCBs in kg, and a description of the type of PCB waste (e.g., PCB remediation waste, PCB bulk product waste, etc.)

AK = Acceptable Knowledge

EPA = U.S. Environmental Protection Agency

PCB = polychlorinated biphenyl

WIPP = Waste Isolation Pilot Plant

Table G-5. WIPP-Acceptable RCRA Hazardous Waste Codes

"D" Series	"F" Series	"P" Series	"U" Series
D004	F001	P015	U002
D005	F002	P030	U003
D006	F003	P098	U019
D007	F004	P099	U037
D008	F005	P106	U043
D009	F006	P120	U044
D010	F007		U052
D011	F009		U070
D018			U072
D019			U078
D021			U079
D022			U103
D026			U105
D027			U108
D028			U122
D029			U133
D030			U134
D032			U151
D033			U154

Table G-5. WIPP-Acceptable RCRA Hazardous Waste Codes

"D" Series	"F" Series	"P" Series	"U" Series
D034			U159
D035			U196
D036			U209
D037			U210
D038			U220
D039			U226
D040			U228
D043			U239

RCRA = Resource Conservation and Recovery Act of 1976

WIPP = Waste Isolation Pilot Plant

Appendix H
Approved Vents

This page intentionally left blank.

H1 Approved Vents

Containers requiring a vent shall have a vent installed (HNF-14741). Table H-1 provides a list of the approved vents. The NucFil-019 DS is the preferred vent for newly generated TRU waste packages; other vents will be approved on a case-by-case basis in the waste profile.

H2 References

HNF-14741, 2007, *Master Documented Safety Analysis (MDSA) for the Solid Waste Operations Complex (SWOC)*, Fluor Hanford, Inc., Richland, Washington. (Use most current version.)

H3 Table

Table H-1. Approved Vents

Manufacturer	Model Number
Fairey ^a	98867 ^b
Fairey	99421
Nuclear Filter Technology	NucFil ^c -012
Nuclear Filter Technology	NucFil-013
Nuclear Filter Technology	NucFil-013 GorTex
Nuclear Filter Technology	NucFil-013 SSS
Nuclear Filter Technology	NucFil-015 DS
Nuclear Filter Technology	NucFil-016
Nuclear Filter Technology	NucFil-016 SS HP
Nuclear Filter Technology	NucFil-019
Nuclear Filter Technology	NucFil-019 DS
Nuclear Filter Technology	NucFil-019-EPD
Nuclear Filter Technology	NucFil-019-HCR
Nuclear Filter Technology	NucFil-019SDS
Nuclear Filter Technology	NucFil-020
Nuclear Filter Technology	NucFil-407DS
Nuclear Filter Technology	NucFil-049
Nuclear Filter Technology	NucFil-049LS
Nuclear Filter Technology	NucFil-049S
Nuclear Filter Technology	NucFil-050 ^d
Nuclear Filter Technology	NucFil-051
Nuclear Filter Technology	NucFil-051CT
Nuclear Filter Technology	NucFil-007
Nuclear Filter Technology	NucFil-7DS

Table H-1. Approved Vents

Manufacturer	Model Number
Nuclear Filter Technology	NucFil-007LS
Nuclear Filter Technology	NucFil-007S
Nuclear Filter Technology	NucFil-072
Nuclear Filter Technology	NucFil-072 SSS
Nuclear Filter Technology	NucFil-073
Nuclear Filter Technology	NucFil-074
Nuclear Filter Technology	NucFil-075
Nuclear Filter Technology	NucFil-DVS3
Nuclear Filter Technology	NucFil-DVS3A
Nuclear Filter Technology	NucFil-DVS3 IP
Nuclear Filter Technology	NucFil-DVS307
Nuclear Filter Technology	NucFil-NFS7A
UltraTech ^e	9400
UltraTech	9402
UltraTech	9408
UltraTech	9412
UltraTech	9413
UltraTech	9414
UltraTech	9415
UltraTech	9416
UltraTech	9450
UltraTech	9460
UltraTech	9500
UltraTech	9550
West	WTM01D

- a. Fairey is a registered trademark of the Fairey Holdings Limited Company, Middlesex, England
- b. Wildcard designator used by manufacturer
- c. NucFil is a registered trademark of the Nuclear Filter Technology Corporation, Lakewood, Colorado
- d. Not approved for TRU package transporter-model II-authorized methods for payload control applications
- e. UltraTech is a registered trademark of Copeland Corporation, Sidney, Ohio.

Appendix I

Remote-Handled Transuranic Waste Acceptance Criteria

This page intentionally left blank.

11 Remote-Handled Transuranic Waste Acceptance Criteria

As a generator of remote-handled (RH) TRU (RH TRU) waste and RH TRU mixed (RH TRUM) waste destined for disposal at the Waste Isolation Pilot Plant (WIPP), the Hanford Site must ensure the RH TRU waste meets the requirements of U.S. Department of Energy (DOE) Order 435.1, *Radioactive Waste Management*, DOE/WIPP 02-3122, and the RH-TRAMPAC document. DOE/WIPP 02-3122 establishes the requirements for the characterization and certification of RH TRU to meet the requirements of the U.S. Environmental Protection Agency (EPA) for disposal of RH TRU waste at WIPP. Additional and/or different characterization requirements may be in place by the time the Hanford RH TRU Program is certified. RH TRU waste may be transported to WIPP in either of two U.S. Nuclear Regulatory Commission (NRC)-approved shipping casks, the RH TRU 72-B or the CNS 10-160B. The waste characterization and packaging requirements for these casks are contained in the *Safety Analysis Report for the RH-TRU 72-B Shipping Package* (NRC, 2002) and the *Safety Analysis Report for the CNS-10-160B Shipping Package* (NRC, 2005), respectively.

RH TRU waste may be packaged in 114-L or 208-L (30-gal or 55-gal) drums for shipment to the appropriate facility within the Solid Waste Operations Complex (SWOC). If the waste is to be transported to WIPP in the RH-72B shipping cask, the drums will be overpacked into RH-72B canisters prior to shipment to WIPP. The requirements for packaging and shipping in the RH-TRU 72-B cask must be met before the RH-TRU waste can be accepted into a SWOC facility. Waste generators may also directly load RH-72B canisters prior to shipment to a SWOC facility. Newly generated RH TRU waste must be visually examined by Waste Services personnel during packaging.

11.1 Remote-Handled Transuranic Waste Criteria

- Waste must be segregated by waste specification record, including segregation of defense from non-defense waste. Non-defense waste is prohibited for shipment to WIPP, but may be shipped to a SWOC facility for storage using the exception process in Section 1.6.

Defense waste is waste generated, in whole or in part, by the Secretary of the Department of Energy (DOE) (and predecessor agencies) performed in whole or in part in carrying out any of the following functions: naval reactors development; weapons activities, including defense inertial confinement fusion; verification and control technology; defense nuclear material production; defense nuclear waste and materials byproduct management; defense nuclear materials security investigations; and defense research and development.

The generator must supply sufficient information for the TRU Program to prepare and document an appropriate defense determination. Final approval of the defense determination will be made by DOE, Richland Operations Office (RL) technical, RL Chief Counsel, RL TRU Project Director, Carlsbad Field Office (CBFO) technical, CBFO Chief Counsel, and (if necessary) DOE Headquarters (HQ) General Counsel.

- Waste must meet all requirements of Tables I-1 through I-5, except as allowed with profile sheet approval. The Hanford TRU Program may determine additional requirements are necessary for specific TRU waste, beyond those listed in Tables I-1 through I-5.
- Waste will be characterized and certified prior to shipment to WIPP. Generators are not responsible for certification of TRU waste; however, they are responsible for providing TRU waste that is certifiable. Generator-supplied documentation demonstrating compliance with the requirements in Tables I-1 through I-5 will ensure the TRU waste is certifiable.

- Newly generated waste must undergo visual examination by Waste Services at the time of packaging and may require sampling to verify the radioisotopic properties of the waste. It is recommended that packaging operations be recorded on video/audio media. If the waste generator does not propose to record the packaging on video/audio media, prior approval is required by Waste Services.
- Retrievably stored RH TRU waste, i.e., waste that is already packaged, may be shipped to a SWOC facility. The generator must provide Acceptable Knowledge (AK) information related to the physical form, originating process, and radioactive contents of the waste.
- AK data must be provided through the use of a waste profile sheet from the *Hanford Site Solid Waste Acceptance Program* Internet Web site. The profile sheet is located at <http://www.hanford.gov/?page=581>.
- Packaging requirements will be established by the Hanford TRU Program and communicated to the generator as a waste stream profile condition of approval. Generators must obtain waste stream profile approval prior to generating and/or packaging their RH TRU waste. The RH TRU 72-B is the preferred method of shipment to WIPP and Tables I-1 through I-5 are based on shipping using the RH TRU 72-B. Generators packaging waste for shipment in the CNS 10-160B must consult with the TRU Program for packaging guidance.
- Generators unable to meet the above RH TRU criteria may request an exception to the waste acceptance criteria per Section 1.6 of this document.

I2 References

- DOE O 435.1, 2001, *Radioactive Waste Management*, Chg. 1, U.S. Department of Energy, Washington, D.C.
- DOE/WIPP-02-3122, 2008, *Transuranic Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico.
- DOE/WIPP-02-3214, 2003, *RH TRU Waste Characterization Program Implementation Plan (WCPIP)*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico. (Use most current version.)
- Hanford Site Solid Waste Acceptance Program*. Available at: <http://www.hanford.gov/?page=577>.
- NRC, 2002, *Safety Analysis Report for the RH-TRU 72-B Shipping Package*, NRC Docket No. 71-9212, U.S. Nuclear Regulatory Commission, Washington, D.C. (Use most current version.)
- NRC, 2005, *Safety Analysis Report for the CNS 10-160B Shipping Package*, draft, not yet released, U.S. Nuclear Regulatory Commission, Washington, D.C.

I3 Bibliography

- 49 CFR, "Transportation," *Code of Federal Regulations*, as amended.
- 49 CFR 173, "Shippers – General Requirements for Shipments and Packagings," *Code of Federal Regulations*, as amended.
- DOE/WIPP-02-3214, 2003, *RH TRU Waste Characterization Program Implementation Plan (WCPIP)*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico. (Use most current version.)

DOE/WIPP 02-3283, 2003, *RH Packaging Program Guidance*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico. (Use most current version.)

DOE/WIPP 02-3284, 2003, *RH Packaging Operations Manual*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico. (Use most current version.)

DOE/WIPP 02-3285, 2004, *RH Packaging Maintenance Manual*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico. (Use most current version.)

Public Law 102-579, *Waste Isolation Pilot Plant Land Withdrawal Act*.

I4 Tables

Table I-1. Container Properties for Shipment in RH TRU 72-B

Container Attribute	Waste Acceptance Criteria	Compliance Method
Payload Container Description	RH TRU Waste Canister—Direct Loaded or Drum Loaded 208-L (55-gal) DOT 7A drums	Site procurement specifications and QA acceptance reports.
Container Weights	Removable Lid Canister (direct or drum loaded) 1,923 kg (4,240 lb) Welded Lid Canister (direct loaded) 2,381 kg (5,250 lb) Welded Lid Canister (drum loaded) 2,712 kg (5,980 lb) 208 L (55-gal) drum—454 kg (1,000 lb)	Records of measurement of loaded container weight The canister and contents may be weighed separately.
Removable Surface Contamination	≤20 dpm/100 cm ² (3,531 ft ³) for alpha ≤200 dpm/100 cm ² (3,531 ft ³) for beta-gamma	Records of surface contamination surveys taken on individual containers prior to release from a radiological contamination area.
Container Identification and Marking	Each payload container shall be marked with a unique container identification number Yellow and magenta “Radioactive Material” label – DOT Mixed – TRU marked as “Hazardous waste” per 40 CFR 262.32	Records that the container number was visually verified The record shall include the name of the person that verified the container number and the date of verification. ^a
Filter Vents	RH TRU canisters and any inner sealed containers greater than 4 L (1 gal) in size must be vented or filtered in accordance with the RH-TRU 72-B packaging Certificate of Compliance	Site procurement specifications and QA acceptance reports, manufacturer’s fabrication documentation, and records of visual inspection. ^a

a. Newly Generated RH TRU waste must be visually examined by Waste Services personnel during packaging. Retrievably stored RH TRU waste must have records (e.g., visual examination data forms, packaging logs, loading sheets or contents inventory sheets) available that demonstrate the attribute has been met.

DOT = U.S. Department of Transportation

RH TRU = Remote-Handled TRU

Table I-2. Radiological Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Method
-----------------	---------------------------	-------------------

Table I-2. Radiological Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Method
Radionuclide Composition	<p>Information on radionuclide composition, with emphasis on the activities and masses of ²⁴¹Am, ²³⁸Pu, ²³⁹Pu, ²⁴⁰Pu, ²⁴²Pu, ²³³U, ²³⁴U, ²³⁸U, ⁹⁰Sr, and ¹³⁷Cs</p> <p>Information on radionuclides contributing to ²³⁹Pu equivalent Curies and other radionuclides contributing to 95% of the radioactive hazard for the payload container</p> <p>The total activity shall not exceed 82.5 Dose Equivalent Curies per container for acceptance at SWOC facilities</p> <p>Note: For WIPP acceptance the maximum activity level may not exceed 23 curies per L (averaged over the volume of the RH TRU canister).</p>	<p>Acceptable Knowledge (AK) documentation, records of radioassay, dose-to-curie conversion, and/or radiochemistry as required by DOE/WIPP 02-3214</p>
Fissile Material Quantity (Pu-239 FGE)	<p>Non-machine compacted waste only</p> <p>325 g (11.5 oz) when Be/BeO limited to <1% by weight of the waste up to <25 kg (55 lb) including credit taken for >5 g (.17 oz.) of Pu-240 poisoning</p> <p>315 g (11.11 oz) when Be/BeO limited to <1% by weight of the waste up to <25 kg (55 lb)</p> <p>305 g (10.75 oz) when Be/BeO limited to >1% by weight of the waste up to <25 kg (55 lb) and is chemically or mechanically bound</p> <p>100 g (3.52 oz) when Be/BeO limited to >1% by weight of the waste up to <25 kg (55 lb) and is not chemically or mechanically bound</p> <p>Note that uncertainty must be accounted for in accordance with HNF-EP-0063 Appendix B, Section B.1.1.2</p>	<p>Records of radioassay, dose-to-curie conversion, radiochemistry, and/or AK documentation</p>
TRU Alpha Activity Concentration	<p>The RH TRU canister shall contain more than 100 nCi/g of alpha-emitting TRU isotopes with half-lives greater than 20 years</p>	<p>Records of radioassay, dose-to-curie conversion, radiochemistry, and/or AK documentation</p> <p>Records of calculations demonstrating compliance with DOE/WIPP 02-3214</p>
PE-Ci Limits	<p>RH-TRU Waste Canister with solidified or vitrified waste - <1,800 PE-Ci RH-TRU</p> <p>Waste Canister with all other approved waste forms - < 240 PE-Ci</p>	<p>Records of radioassay, dose to curie conversion, radiochemistry, and/or AK documentation</p>

Table I-2. Radiological Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Method
Radiation Dose Rate	<p>The external radiation dose equivalent rate of individual payload containers shall be greater than or equal to 200 mrem/hr and less than or equal to 1000 rem/hr at the surface of an individual container</p> <p>Note: No more than 5 percent by volume of the RH TRU waste received at the WIPP may have a surface dose rate in excess of 100 rem/hr</p> <p>Waste generators must coordinate planning with the Hanford TRU Project Group if they will generate RH TRU waste with dose rates greater than 100 rem/hr for approval on a case-by-case basis</p> <p>For waste containers that contain shielding, e.g., lead-lined drums, the generator must provide both the actual dose rate and the calculated dose rate if the shielding was not present</p> <p>Note: For storage at SWOC facilities, waste containers must be shielded to less than 200 mrem at contact. This may be accomplished through the use of shielded overpack containers. Contact Waste Services for guidance. An exception is not required to use shielded overpack containers for storing certifiable TRU waste.</p>	Records of radiation dose surveys
Decay Heat	≤Limit established per waste stream profile	Compliance will be per direction in the waste stream profile and will be based on generator-supplied isotopic and loading data

Source:

DOE/WIPP-02-3214, 2003, *RH TRU Waste Characterization Program Implementation Plan (WCPIP)*, U.S. Department of Energy, Carlsbad Area Office, Carlsbad, New Mexico. (Use most current version.)

- AK = Acceptable Knowledge
- FGE = fissile gram equivalent
- RH TRU = Remote-Handled TRU
- SAR = Safety Analysis Report
- WIPP = Waste Isolation Pilot Plant

Table I-3. Physical Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Method
Liquids	<p>Waste shall contain as little residual liquid as is reasonably achievable by pouring, pumping, and/or aspirating, and internal containers shall contain less than 2.5 cm (1 in.) of liquid in the bottom of the container</p> <p>Total residual liquid in any RH TRU waste container must be less than 1 percent by volume of the waste container</p> <p>RH TRU waste with EPA Code U134 (hydrofluoric acid) waste shall have no detectable liquid</p> <p>Residual liquids containing PCBs are prohibited</p>	AK documentation, records of radiography, and/or visual examination ^a
Sealed Containers	<p>Sealed containers greater than 4 L (1 gal) in size are prohibited, except for metal containers packaging solid inorganic waste</p> <p>All waste containers with inner rigid containers greater than 4 L (1 gal) shall be vented</p>	AK documentation, records of radiography, and/or visual examination ^a

- a. Newly generated RH TRU waste must be visually examined by Waste Services personnel during packaging. Retrievably stored RH TRU waste must have records (e.g., visual examination data forms, packaging logs, loading sheets, or contents inventory sheets) available that demonstrate the attribute has been met.

AK = Acceptable Knowledge

CPR = cellulose, plastics, and rubber

PCB = polychlorinated biphenyls

TRU = transuranic

WIPP = Waste Isolation Pilot Plant

Table I-4. Chemical Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
Pyrophoric Materials	<p><1 percent (by weight) pyrophoric radionuclides</p> <p>No nonradionuclide pyrophoric materials</p>	AK documentation, Records of radiography and/or visual examination ^a
Hazardous Waste	<p>Limited to EPA hazardous waste numbers identified as allowable in the WIPP Hazardous Waste Facility Permit and all Washington State waste codes</p> <p>No hazardous wastes not occurring as co-contaminants with TRUM wastes (non-mixed hazardous wastes)</p>	AK documentation showing the waste contains no EPA codes other than those listed in Table I-5
Chemical Compatibility	No wastes incompatible with backfill, seal, and panel closures materials, container and packaging materials, shipping container materials, or other wastes	AK documentation and/or records of verification by visual examination or radiography ³ that the waste meets the assigned waste stream description in the waste profile
Explosives or Compressed Gasses	No wastes containing explosives or compressed gases (pressurized containers)	AK documentation with verification through radiography or visual examination ^a
Polychlorinated	PCB-contaminated TRU and PCB-contaminated TRU waste mixed with a hazardous waste	AK documentation with records of verification through radiography or

Table I-4. Chemical Properties

Waste Attribute	Waste Acceptance Criteria	Compliance Methods
biphenyls	including PCB remediation waste, PCB Articles, and PCB bulk product waste may be stored and disposed at the WIPP There can be no free-flowing liquids in PCB waste	visual examination ^a Information from the generator must include the earliest date of waste generation (i.e., the date of removal from service for disposal), the estimated weight of PCBs in kg, and a description of the type of PCB waste (e.g., PCB remediation waste, PCB bulk product waste, etc.)
Reactives, Corrosives, or Ignitables	No wastes exhibiting the characteristic of ignitability, corrosivity, or reactivity (EPA Hazardous Waste Numbers of D001, D002, or D003)	AK documentation with verification through radiography or visual examination ^a

a. Newly generated RH TRU waste must be visually examined by Waste Services personnel during packaging. Retrievably stored RH TRU waste must have records (e.g., visual examination data forms, packaging logs, loading sheets, or contents inventory sheets) available that demonstrate the attribute has been met.

AK = Acceptable Knowledge
 EPA = S. Environmental Protection Agency
 PCB = polychlorinated biphenyls

Table I-5. WIPP-Acceptable RCRA Hazardous Waste Numbers

"D" Series	"F" Series	"P" Series	"U" Series
D004	F001	P015	U002
D005	F002	P030	U003
D006	F003	P098	U019
D007	F004	P099	U037
D008	F005	P106	U043
D009	F006	P120	U044
D010	F007		U052
D011	F009		U070
D018			U072
D019			U078
D021			U079
D022			U103
D026			U105
D027			U108
D028			U122
D029			U133

Table I-5. WIPP-Acceptable RCRA Hazardous Waste Numbers

"D" Series	"F" Series	"P" Series	"U" Series
D030			U134
D032			U151
D033			U154
D034			U159
D035			U196
D036			U209
D037			U210
D038			U220
D039			U226
D040			U228
D043			U239

RCRA = Resource Conservation and Recovery Act of 1976

WIPP = Waste Isolation Pilot Plant